

# FILTER OVERVIEW WITH SERVICE INTERVALS AND CAPACITIES

## 3R Final Tier 4 (FT4) Series Compact Utility Tractors - 3033R, 3038R, 3039R, 3045R, 3046R

### FILTER PAK 3033R, 3039R, 3046R - [LVA21038](#)

M806419, LVA13065, MIU803127, RE68048, MIU802421  
Each kit contains above filters, offering a complete solution for your maintenance needs to keep your tractor running at peak performance.

### CAB RECIRCULATION AIR FILTER [MIU10011](#) (2)

Clean or replace after every 50 hours and as required.

### CAB FRESH AIR FILTER - [MIU10010](#)

Clean or replace after every 50 hours and as required.

### ENGINE FUEL FILTER 3033R, 3038R, 3045R - [M811032](#) 3033R, 3039R, 3046R - [MIU802421](#), [MIU803127](#)

Replace after every 400 hours or annually, whichever occurs first.

### TRANSMISSION OIL FILTER - [LVA13065](#)

Replace initially after 400 hours and change after every 1200 hours or 3 years.

(Click here for [capacity](#))

### ENGINE OIL FILTER - [M806419](#)

Replace after every 200 hours or annually, whichever occurs first.

(Click here for [capacity](#))

### HYDRAULIC FUEL FILTER - [LVA12726](#)

Replace after every 400 hours.

### ENGINE PRIMARY AIR FILTER - [RE68048](#) SECONDARY AIR FILTER - [RE68049](#)

Check after every 600 hours and replace as required.



# JOHN DEERE

Genuine Parts and Service

# CAPACITIES

## 3R Final Tier 4 (FT4) Series Compact Utility Tractors - 3033R, 3038R, 3039R, 3045R, 3046R

### CAPACITIES (Approximate):

#### Fuel Tank:

Open Operator Station ..... 51.1 L (13.5 gal)  
Cab ..... 44.5 L (11.8 gal)

#### Cooling System:

##### Cool-Gard™ II

Open Operator Station ..... 5.3 L (1.4 gal)  
Cab ..... 7 L (1.85 gal)

#### Crankcase with Filter:

##### Plus-50™ II

3033R, 3038R, 3039R ..... 4.3 L (1.14 gal)  
3045R, 3046R ..... 5.7 L (1.51 gal)

#### Transmission and Hydraulic System:

##### HY-Gard™

..... 25.7 L (6.8 gal)

#### Front Axle:

##### HY-Gard™

..... 4.8 L (1.27 gal)

[Return to Filter Overview](#)

