

FILTER OVERVIEW WITH SERVICE INTERVALS AND CAPACITIES

3R Series Compact Utility Tractors - 3033R (L000001-), 3039R (L000001-), 3046R (L000001-)

CAB

RECIRCULATION AIR FILTER (2)
[MIU10011](#)

Replace as required.

FILTER PAK [LVA21038](#)

M806419, LVA13065, MIU803127, RE68048, MIU802421 kit contains and offering a complete solution for your maintenance needs to keep your tractor running at peak performance.

CAB

FRESH FILTER - [MIU10010](#)

Clean or replace every 50 hours and as required.

ENGINE

DIESEL PARTICULATE FILTER -
(3033R) [MIU803093](#)
(3039R, 3046R) [MIU803232](#)

See your John Deere™ dealer or qualified service provider.

ENGINE

PRIMARY FUEL FILTER - [MIU802421](#)
FINAL FUEL FILTER - [MIU803127](#)

Replace every 400 hours or annually, whichever occurs first.

ENGINE

OIL FILTER - [M806419](#)

Replace every 400 hours or annually, whichever occurs first.
(Click here for [capacity](#))

HYDRAULIC

TRANSMISSION OIL FILTER - [LVA13065](#)
OIL COOLER HYDRAULIC FILTER
(3033R) - [LVA12726](#)
FRONT PTO OIL FILTER (3033R) -
[LVA23443](#)

Replace every 400 hours.
(Click here for [capacity](#))

ENGINE

PRIMARY AIR FILTER - [RE68048](#)
SECONDARY AIR FILTER - [RE68049](#)

Replace as needed.



CAPACITIES

3R Series Compact Utility Tractors - 3033R (L000001-), 3039R (L000001-), 3046R (L000001-)

CAPACITIES (Approximate):

Fuel Tank:

Open Operator Station 37.4 L (9.8 gal)
Cab 47.6 L (12.6 gal)

Cooling System:

Cool-Gard™ II

Open Operator Station 5.7 L (1.5 gal)
Cab 6.8 L (1.8 gal)

Crankcase with Filter:

Plus-50™ II

3038R 4.0 L (1.1 gal)
3045R 5.8 L (1.5 gal)

Transmission and Hydraulic System:

HY-Gard™

..... 25.7 L (6.8 gal)

Front Axle:

HY-Gard™

..... 4.8 L (1.3 gal)

[Return to Filter Overview](#)

