

FILTER OVERVIEW WITH SERVICE INTERVALS AND CAPACITIES

3R Series Compact Utility Tractors - 3038R (HJ200001 -), 3039R (HJ100001 -), 3045R (HJ200001 -)

FILTER PAK 3039R - [LVA21038](#)

M806419, LVA13065, MIU803127, RE68048, MIU802421
Each kit contains above filters, offering a complete solution for your maintenance needs to keep your tractor running at peak performance.

CAB RECIRCULATION AIR FILTER [MIU10011](#) (2)

Clean or replace after every 50 hours and as required.

CAB FRESH AIR FILTER - [MIU10010](#)

Clean or replace after every 50 hours and as required.

ENGINE FUEL FILTER 3038R, 3045R - [MIU800645](#) 3039R - [MIU802421](#), [MIU803127](#)

Replace after every 400 hours or annually, whichever occurs first.

TRANSMISSION OIL FILTER - [LVA13065](#), [LVA12678](#)

Replace after every 400 hours.
(Click here for [capacity](#))

ENGINE OIL FILTER - [M806419](#)

Replace after every 200 hours or annually, whichever occurs first.
(Click here for [capacity](#))

HYDRAULIC FUEL FILTER - [LVA12726](#)

Replace after every 400 hours.

ENGINE PRIMARY AIR FILTER - [RE68048](#) SECONDARY AIR FILTER - [RE68049](#)

Check after every 600 hours and replace as required.



JOHN DEERE
Genuine Parts and Service

CAPACITIES

3R Series Compact Utility Tractors - 3038R (HJ200001 -), 3039R (HJ100001 -), 3045R (HJ200001 -)

CAPACITIES (Approximate):

Fuel Tank:

Open Operator Station 51.1 L (13.5 gal)
Cab 44.5 L (11.8 gal)

Cooling System:

Cool-Gard™ II

Open Operator Station 5.3 L (1.4 gal)
Cab 7 L (1.85 gal)

Crankcase with Filter:

Plus-50™ II

3038R 4.3 L (1.14 gal)
3045R 5.7 L (1.51 gal)

Transmission and Hydraulic System:

HY-Gard™

..... 25.7 L (6.8 gal)

Front Axle:

HY-Gard™

..... 4.8 L (1.27 gal)

[Return to Filter Overview](#)