

FILTER OVERVIEW WITH SERVICE INTERVALS AND CAPACITIES

3R Series Compact Utility Tractors - 3033R (HJ100001 -), 3038R (HJ200001 -), 3039R (HJ100001 -), 3045R (HJ200001 -), 3046R (HJ100001 -)

FILTER PAK

3033R, 3039R, 3046R - [LVA21038](#)

M806419, LVA13065, MIU803127, RE68048, MIU802421

Each kit contains above filters, offering a complete solution for your maintenance needs to keep your tractor running at peak performance.

CAB

RECIRCULATION AIR FILTER
[MIU10011](#) (2)

Clean or replace after every 50 hours and as required.

CAB

FRESH AIR FILTER - [MIU10010](#)

Clean or replace after every 50 hours and as required.

ENGINE

FUEL FILTER

3033R, 3038R, 3045R - [MIU800645](#), [M811032](#)
3039R, 3046R - [MIU802421](#), [MIU803127](#)

Replace after every 400 hours or annually, whichever occurs first.

TRANSMISSION

OIL FILTER - [LVA13065](#), [LVA23443](#)

Replace initially after 400 hours and change after every 1200 hours or 3 years.

(Click here for [capacity](#))

ENGINE

OIL FILTER - [M806419](#)

Replace after every 200 hours or annually, whichever occurs first.

(Click here for [capacity](#))

ENGINE

PRIMARY AIR FILTER - [RE68048](#)

SECONDARY AIR FILTER - [RE68049](#)

Check after every 600 hours and replace as required.

HYDRAULIC

FUEL FILTER - [LVA12726](#)

Replace after every 400 hours.



JOHN DEERE

Genuine Parts and Service

CAPACITIES

**3R Series Compact Utility Tractors - 3033R (HJ100001 -), 3038R (HJ200001 -), 3039R (HJ100001 -),
3045R (HJ200001 -), 3046R (HJ100001 -)**

CAPACITIES (Approximate):

Fuel Tank:

Open Operator Station 51.1 L (13.5 gal)
Cab 44.5 L (11.8 gal)

Cooling System:

Cool-Gard™ II

Open Operator Station 5.3 L (1.4 gal)
Cab 7 L (1.85 gal)

Crankcase with Filter:

Plus-50™ II

3033R, 3038R, 3039R 4.3 L (1.14 gal)
3045R, 3046R 5.7 L (1.51 gal)

Transmission and Hydraulic System:

HY-Gard™

..... 25.7 L (6.8 gal)

Front Axle:

HY-Gard™

..... 4.8 L (1.27 gal)

[Return to Filter Overview](#)

