

FILTER OVERVIEW WITH SERVICE INTERVALS AND CAPACITIES


4005 and 4105 Compact Utility Tractors

TRANSMISSION/HYDRAULIC OIL FILTER

– [LVA13065](#)

Replace after initial 50 hours,
then every 200 hours.

(Click here for [capacity](#))



FILTER PAK

– [LVA21202](#)

Kit contains M806419, MIU800645, RE68048,
LVA13065 offering a complete solution for your
maintenance needs to keep your tractor running
at peak performance.

ENGINE


PRIMARY AIR FILTER

– [RE68048](#)

SECONDARY AIR FILTER

– [RE68049](#)

Replace as required.



ENGINE OIL FILTER

– [M806419](#)

Replace every 200 hours or
annually, whichever occurs
first.

(Click here for [capacity](#))



ENGINE FUEL FILTER

– [MIU800645](#) and [M811032](#)

Replace every 500 hours.



JOHN DEERE

Genuine Parts and Service

CAPACITIES

4005 and 4105 Compact Utility Tractors

CAPACITIES (Approximate):

Fuel Tank:

4005.....	32 L (8.5 gal)
4105.....	43.5 L (11.5 gal)

Cooling System: Cool-Gard™ II

4005.....	5.8 L (1.53 gal)
4105.....	5.3 L (1.4 gal)

Crankcase with Filter: Plus-50™ II

4005.....	5.3 L (1.4 gal)
4105.....	4.3 L (1.13 gal)

Transmission and Hydraulic System:

Low Viscosity Hy-Gard™

4005.....	26 L (6.9 gal)
4105.....	31.4 L (8.3 gal)

Front Axle:

GL-5 Lubricant 80W-90

4005.....	7.5 L (1.98 gal)
-----------	------------------

Low Viscosity Hy-Gard™

4105.....	4.5 L (1.19 gal)
-----------	------------------

[Return to Filter Overview](#)

