

REPLACEMENT PARTS GUIDE

4M Series Heavy Duty Tractors - 4052M, 4066M

ENGINE



DIESEL PARTICULATE FILTER (DPF) [MIU802216](#)

See your John Deere™ dealer or qualified service provider.



PRIMARY AIR FILTER [RE68048](#)



SECONDARY AIR FILTER [RE28228](#)

Replace after cleaning 6 times or annually whichever occurs first.



OIL FILTER [M806419](#)

Replace after every 200 hours or annually, whichever occurs first.



PRIMARY FUEL FILTER [MIU802421](#)

FINAL FUEL FILTER [MIU803127](#)

Replace after every 400 hours or annually, whichever occurs first.

TRANSMISSION



HYDRAULIC OIL FILTER [RE45864](#)

Replace after every 400 hours change every 1200 hours or 3 years.

HYDRAULIC



HYDRAULIC OIL FILTER [LVA10419](#)

Replace after every 400 hours.



JOHN DEERE
Genuine Parts and Service

CAPACITIES

4M Series Heavy Duty Tractors - 4052M, 4066M

CAPACITIES (Approximate):

Fuel Tank:

Open Operator Station..... 56.9 L (15 gal)

Cab..... 55.6 L (14.7 gal)

Cooling System:

Cool-Gard™ II

Open Operator Stati..... 6.4 L (1.4 gal)

Cab..... 7.6 L (1.6 gal)

Engine Crankcase with Filter:

Plus-50™ II

..... 5.3 L (1.2 gal)

Transmission and Hydraulic System:

Hy-Gard™

..... 47.3 L (12.5 gal)

Front Axle:

Hy-Gard™

..... 5 L (1.1 gal)

REPLACEMENT PARTS GUIDE

4M Series Heavy Duty Tractors - 4052M, 4066M

ENGINE



FAN BELT DRIVE

[LVU29376](#) (ALTERNATOR)



ALTERNATOR

[LVA18613](#) (ALL)




BATTERY

[TA15225](#) (WET CHARGED BATTERY)(ALL)

[TY26442B](#) (WET CHARGED BATTERY)
(ALL)

[TY26442](#) (DRY CHARGED BATTERY)(ALL)



CLUTCH DISK

[SJ13448](#)



BRAKE DISK

[LVA17440](#) (PTO)(ALL)

[LVA17426](#) (FRICTION PLATE) (ALL)

[LVU23536](#) (SEPARATOR PLATE) (ALL)



CAB



SEAT

[LVA22459](#)

AXLE



TIE ROD

[LVA14951](#) (MFWD)

[LVA14171](#) (POWER STEERING CYLINDER) (ALL)



JOHN DEERE
Genuine Parts and Service

CLICK PART NUMBER TO BUY