

FILTER OVERVIEW WITH SERVICE INTERVALS AND CAPACITIES

4M Final Tier 4 (FT4) Series Compact Utility Tractors - 4044M (HJ100001 -), 4049M (HJ200001 -), 4052M (HJ100001 -), 4066M (HJ100001 -)



ENGINE

OIL FILTER – [M806419](#)

Replace after every 200 hours or annually, whichever occurs first.

(Click here for [capacity](#))

FILTER PAK (4044M, 4052M, 4066M) – [LVA21039](#)

Each kit contains M806419, LVA10419, MIU803127, RE45864, RE68048 and MIU802421, offering a complete solution for your maintenance needs to keep your tractor running at peak performance.



CAB (IF EQUIPPED)

FRESH AIR FILTER (4049M) – [MIU10010](#)

Clean or replace after every 50 hours and as required.

RECIRCULATION AIR FILTER (4049M) – [MIU10011](#) (2)

Clean or replace after every 50 hours and as required.



ENGINE

PRIMARY FUEL FILTER (4044M, 4052M, 4066M) – [MIU802421](#)

FINAL FUEL FILTER (4044M, 4052M, 4066M) – [MIU803127](#)

FUEL FILTER (4049M) – [MIU800645](#)

Replace after every 400 hours or annually, whichever occurs first.



ENGINE

DIESEL PARTICULATE FILTER (DPF)

(4044M) – [MIU803276](#)

(4052M, 4066M) – [MIU802216](#)

See your John Deere™ dealer or qualified service provider.



TRANSMISSION

OIL FILTER – [RE45864](#), [LVA23443](#)

Replace after every 400 hours change every 1200 hours or 3 years.

(Click here for [capacity](#))




HYDRAULIC

OIL FILTER – [LVA10419](#)

Replace after every 400 hours.

(Click here for [capacity](#))



ENGINE

PRIMARY AIR FILTER – [RE68048](#)

SECONDARY AIR FILTER – [RE68049](#)

Check after every 600 hours and replace as required.



JOHN DEERE

Genuine Parts and Service

http://www.deere.com/en_US/parts/service/support/filteroverviews

CAPACITIES

4M Final Tier 4 (FT4) Series Compact Utility Tractors - 4044M (HJ100001 -), 4049M (HJ200001 -),
4052M (HJ100001 -), 4066M (HJ100001 -)

CAPACITIES (Approximate):

Fuel Tank:

Open Operator Station 49.2 L (13 gal)
Cab 52 L (13.8 gal)

Front Axle: Hy-Gard™

..... 5 L (1.3 gal)

[Return to Filter Overview](#)

Cooling System:

Cool-Gard™ II

Open Operator Station 6 L (1.5 gal)
Cab 8 L (2.1 gal)

Crankcase with Filter:

Plus-50™ II

..... 5.4 L (1.4 gal)

Transmission and Hydraulic System:

Hy-Gard™

..... 47.3 L (12.5 gal)

