


# FILTER OVERVIEW WITH SERVICE INTERVALS AND CAPACITIES

4R Final Tier 4 (FT4) Series Compact Utility Tractors - 4044R, 4052R, 4066R, 4049R

## CAB

RECIRCULATION AIR FILTER – [MIU10011](#) (2)

Clean or replace after every 50 hours and as required.



## FILTER PAK – [LVA21039](#)

M806419, LVA10419, MIU803127, RE45864, RE68048, MIU802421  
Each kit contains above filters and offering a complete solution for your maintenance needs to keep your tractor running at peak performance.

## CAB

FRESH AIR FILTER – [MIU10010](#)


Clean or replace after every 50 hours and as required.



## ENGINE

PRIMARY AIR FILTER – [RE68048](#)  
SECONDARY AIR FILTER – [RE68049](#)

Check after every 600 hours and replace as required.



## ENGINE

DIESEL PARTICULATE FILTER (DPF)  
(4044R) – [MIU803276](#)  
(4052R, 4066R) – [MIU802216](#)

See your John Deere™ dealer or qualified service provider.



## ENGINE

OIL FILTER – [M806419](#)

Replace after every 200 hours or annually, whichever occurs first.

(Click here for [capacity](#))



## HYDRAULIC

HYDRAULIC OIL FILTER – [LVA10419](#)

Replace after every 400 hours.

(Click here for [capacity](#))



## ENGINE

PRIMARY FUEL FILTER (4044R, 4052R, 4066R) –

[MIU802421](#)

FINAL FUEL FILTER (4044R, 4052R, 4066R) –

[MIU803127](#)

FUEL FILTER (4049R) – [MIU800645](#)

Replace after every 400 hours or annually, whichever occurs first.



## TRANSMISSION

OIL FILTER – [RE45864](#), [LVA23443](#)

Replace after every 400 hours change every 1200 hours or 3 years.

(Click here for [capacity](#))



**JOHN DEERE**  
Genuine Parts and Service

# CAPACITIES

## 4R Final Tier 4 (FT4) Series Compact Utility Tractors - 4044R, 4052R, 4066R, 4049R

### CAPACITIES (Approximate):

#### Fuel Tank:

Open Operator Station ..... 49.2 L (13 gal)  
Cab ..... 52 L (13.8 gal)

#### Front Axle: Hy-Gard™

..... 5 L (1.3 gal)

[Return to Filter Overview](#)

#### Cooling System:

##### Cool-Gard™ II

Open Operator Station ..... 6 L (1.5 gal)  
Cab ..... 8 L (2.1 gal)

#### Crankcase with Filter:

##### Plus-50™ II

..... 5.4 L (1.4 gal)

#### Transmission and Hydraulic System:

##### Hy-Gard™

..... 47.3 L (12.5 gal)

