

REPLACEMENT PARTS GUIDE

5D Series - 5039D Tractor (TREM IIIA Engine) (India Edition)



HYDRAULIC / TRANSMISSION



OIL FILTER
[RE45864](#)

ROCKSHAFT OIL FILTER
[SJ11062](#)

[RE280728](#)

Replace after initial 500 hours and change every 1100 hours and every 1250 hours.

ENGINE



OIL FILTER
[RE507204](#) (For India)
[T19044](#) (For Export)

Change every 100 hours and 250 hours and annually.



PRIMARY AIR FILTER
[RE68048](#)



SECONDARY AIR FILTER
[RE68049](#)

Change after every 250 hours and annually.



PRIMARY FUEL FILTER
[RE508953](#)



FINAL FILTER
[RE508954](#)

Replace after every 250 hours.



JOHN DEERE
Genuine Parts and Service

CAPACITIES

5D Series - 5039D Tractor (TREM IIIA Engine) (India Edition)

CAPACITIES (Approximate):

Fuel Tank:

..... 60 L (15.85 gal)

Cooling System:

Cool-Gard™ II

..... 9.82 L (2.59 gal)

Transmission and Hydraulic System:

Hy-Gard™

Grease Axle 30 L (7.92 gal)


Oil Axle 32 L (8.45 ga)





REPLACEMENT PARTS GUIDE


5D Series - 5039D Tractor (TREM IIIA Engine) (India Edition)


ENGINE

 **CLUTCH DISK**
[SJ29350](#) (DUAL)
[RE242274](#) (PTO)
[SJ23064](#) (SINGLE)

 **BATTERY**
[TY25879](#)


 **BRAKE DISK**
[SJ18395](#)
[SJ18396](#) (2100 RPM)

 **FAN BELT DRIVE**
[SU63793](#) (LGTH = 1340 mm)
[SU38901](#) (LGTH = 1300 mm)
[SU64566](#) (LGTH = 1315 mm)


 **ALTERNATOR**
[RE258846](#)



CAB

 **SEAT**
[SJ34660](#) (ASSEMBLY)
[RE73192](#) (BOTTOM)
[RE212692](#) (BACK)
[SJ26883](#) (POWER STEERING)
[SJ18041](#) (BOTTOM)
[RE73193](#) (BACK)
[SJ18538](#) (FIXED)

AXLE

 **TIE ROD**
[RE234118](#) (FONT) (ASSEMBLY)
[RE190506](#) (RH)
[RE190481](#) (LH)
[RE208624](#) (POWER STEERING)
[SJ12068](#) (DANA)