

REPLACEMENT PARTS GUIDE

5D (Tier 2) Series Tractors - 5045D and 5055D

ENGINE



PRIMARY AIR FILTER [RE68048](#) SECONDARY AIR FILTER [RE68049](#)

Service after every 250 hours or annually, and as required per conditions.



OIL FILTER [RE519626](#)

Replace after initial 100 hours, then every 250 hours or annually. If Plus-50™ II oil and John Deere™ filter is used interval may be extended to 500 hours.



FUEL FILTER [RE60021](#)

Replace after every 500 hours.



HYDRAULIC



HYDRAULIC OIL FILTER [RE45864](#)

Replace after every 400 hours change every 1200 hours or 3 years.

CAPACITIES

5D (Tier 2) Series Tractors - 5045D and 5055D

CAPACITIES (Approximate):

Fuel Tank:

5D Tractors (Open Operator Station) 60 L (15.85 gal)

Cooling System:

5D Tractors 9.5 L (2.5 gal)

Engine Oil:

5D Tractors 8.5 L (2.25 gal)

Transmission and Hydraulic System:

5D Tractors (2WD)..... 38 L (10 gal)

Grease Axle 30 L (7.92 gal)

Oil Axle 32 L (8.5 gal)

REPLACEMENT PARTS GUIDE

5D (Tier 2) Series Tractors - 5045D and 5055D

ENGINE



CLUTCH DISK
[SJ29350](#) (TRACTION)
[RE242274](#) (PTO)



BRAKE DISK
[SJ18395](#)



ALTERNATOR
[RE23471](#) (43 A)



FAN BELT DRIVE
[R216949](#)



BATTERY
[TY25272A](#) (WET CHARGED BATTERY)(ALL)
[TY26442B](#) (WET CHARGED BATTERY)(5045D)



CAB



SEAT
[RE258488](#) (BACK)
[RE258487](#) (SEAT)

AXLE



TIE ROD
[RE217616](#) (2WD)
[RE217817](#) (TIE ROD END)
[RE217819](#) (BALL JOINT)
[R225906](#) (SUPPORT TOP LINK)