

FILTER OVERVIEW WITH SERVICE INTERVALS AND CAPACITIES

6010 Series Self-Propelled Forage Harvester - 6610, 6710, 6810, 6910

CAB

RECIRCULATION AIR FILTER [Z62223](#)

Clean after every 250 hours and replaced as required.

CAB

FRESH AIR FILTER [AZ43412](#)

Clean after every 250 hours and replaced as required.

ENGINE

SECONDARY AIR FILTER (6610) – [AT166136](#)

SECONDARY AIR FILTER (6710-6910) – [AZ45867](#)

Replace after every 1,500 hours and as required.

ENGINE

PRIMARY AIR FILTER (6610) – [AZ39761](#) (6710-6910) – [AZ45868](#)

Replace after every 1,500 hours and as required.

ENGINE

COOLANT FILTER (6710) – [RE11992](#) (6810-6910) W/ ENGINE N14 – [PMWF2075](#) (6810-6910) W/ ENGINE NTA855A – [RE42052](#)

Replace after every 250 hours.

(Click here for [capacity](#))

ENGINE

OIL FILTER (6610) – [DZ101880](#) (6710 SN -500277) – [RE21748](#) (6710 SN -500277) – [RE21058](#) (6710 SN 500278-) – [RE44647](#) (6810-6910) – [RE21058](#) (6810-6910) – [RE42051](#)

Replace after first 100 hours and every 250 hours, thereafter.

(Click here for [capacity](#))

ENGINE

FUEL FILTER (6610-6710) – [AR86745](#) (6610-6710) – [AR86755](#) (6810-6910) W/ ENGINE N14 – [PMFS1212](#) (6810-6910) W/ ENGINE NTA855A – [RE42050](#)

Replace after every 250 hours.

HYDRAULICS

HYDRAULIC OIL FILTER ALL – [AT120444](#)

Replace after the first 100 hours, then every 500 hours thereafter.

(Click here for [capacity](#))

HYDRAULICS

HYDROSTATIC CHARGE FILTER, ALL – [AH128449](#)

Replace after the first 100 hours, then every 500 hours thereafter.

(Click here for [capacity](#))



JOHN DEERE

Genuine Parts and Service

https://www.deere.com/en_US/parts/parts_by_industry/ag/fmi/filter_maintenance_information.page

CAPACITIES

6010 Series Self-Propelled Forage Harvester - 6610, 6710, 6810, 6910

CAPACITIES (Approximate):

Fuel Tank:

6610-6910 (Standard) 700 L (185 gal)

Cooling System (Complete): John Deere™ Low Silicate Antifreeze

6610 47 L (12.4 gal)

6710 55 L (14.4 gal)

6810-6910 64 L (16.9 gal)

Engine with Filter: Plus-50™

6610 24 L (6.3 gal)

6710 35.5 L (9.4 gal)

6810-6910 42 L (11.1 gal)

Transmission:

Hy-Gard™

..... 9.5 L (2.5 gal)

Final Drives (Each):

Hy-Gard™

..... 5.1 L (1.34 gal)

Hydraulic System:

Hy-Gard™

Hydraulic System 46 L (12.2 gal)

Hydraulic System (with Rear Wheel Drive) 39 L (10.3 gal)

[Return to Filter Overview](#)

