

FILTER OVERVIEW WITH SERVICE INTERVALS AND CAPACITIES


6B Series Tractors - 6095B, 6110B, 6120B, 6135B

HYDRAULICS

FILTER ELEMENT – [SJ11792](#)

Replace after 100 and then every 500 hours.

(Click here for [capacity](#))



ENGINE

OIL FILTER – [RE504836](#)

Replace after 100 and 500 hours and then every 500 hours.

If neither John Deere PLUS-50 nor an oil meeting ACEA E5 or E4 is used, carry out this service on tractors with engine serial number from 800000 every 250 hours. Engine oil must be changed at least once a year.

(Click here for [capacity](#))




ENGINE: 4045HCP04, 4045HCP08
(6095B TRACTOR)

PRIMARY FUEL FILTER – [RE509208](#)
FINAL FUEL FILTER – [RE526557](#)

ENGINE: 4045HCP05, 4045HCP10,
4045HCP11
(6110B, 6120B, AND 6135B TRACTORS)

PRIMARY FUEL FILTER – [RE546336](#)
FINAL FUEL FILTER – [RE544394](#)

Replace every 500 hours.



ENGINE

SECONDARY AIR FILTER – [SU29685](#)
(6095B TRACTORS)

Replace annually. Clean as required.

ENGINE

PRIMARY AIR FILTER – [SU29684](#)
(6095B TRACTORS)

Replace annually. Clean as required.

ENGINE


SECONDARY AIR FILTER – [AL150288](#)
(6110B, 6120B, AND 6135B TRACTORS)

Replace annually. Clean as required.

ENGINE

PRIMARY AIR FILTER – [AL172780](#)
(6110B, 6120B, AND 6135B TRACTORS)

Replace annually. Clean as required.



JOHN DEERE

Genuine Parts and Service

CAPACITIES

6B Series Tractors - 6095B, 6110B, 6120B, 6135B

CAPACITIES (Approximate):

Fuel Tank:

6095B Tractors	150 L (39.62 gal)
6110B, 6120B, and 6135B Tractors	220 L (58.12 gal)

Cooling System:

Cool-Gard™II Premix

6B Tractors	18 L (4.76 gal)
-------------------	-----------------

Crankcase with Filter:

Plus-50™II

6B Tractors	15 L (3.96 gal)
-------------------	-----------------

Transmission Case:

Hy-Gard™II

6B Tractors	60 L (15.65 gal)
-------------------	------------------

MFWD Axle Housing:

GL-5

6095B, 6110B Tractors	5.5 L (1.45 gal)
6120B, 6135B Tractors	5 L (1.32 gal)

MFWD Wheel Hub (Each Side):

Grease-Gard™

6095B, 6110B Tractors	1.1 L (0.29 gal)
6120B, 6135B Tractors	0.8 L (0.21 gal)

[Return to Filter Overview](#)

