

FILTER OVERVIEW WITH SERVICE INTERVALS AND CAPACITIES

9400, 9500 and 9600 Maximizer and Sidehill Combines

ENGINE

PRIMARY AIR FILTER

(9400 Combine Serial Numbers -655288, 9500 Combine Serial Numbers -645200, 9600 Combine Serial Numbers -645300) – [AR80652](#), [AR82915](#)

PRIMARY AIR FILTER

(9400 Combine Serial Numbers 655289-, 9500 Combine Serial Numbers 645201-665977, 9600 Combine Serial Numbers 645301-666172) – [AR70106](#)

PRIMARY AIR FILTER

(9500 Combine Serial Numbers 665978-, 9600 Combine Serial Numbers 666173-) – [AR95758](#)

Change annually and clean or change as required.



ENGINE

SECONDARY AIR FILTER

(9400 Combine Serial Numbers -655288, 9500 Combine Serial Numbers -645200, 9600 Combine Serial Numbers -645300) – [AR80653](#), [AR81313](#)

SECONDARY AIR FILTER

(9400 Combine Serial Numbers 655289-, 9500 Combine Serial Numbers 645201-665977, 9600 Combine Serial Numbers 645301-666172) – [AR70107](#)

SECONDARY AIR FILTER

(9500 Combine Serial Numbers 665978-, 9600 Combine Serial Numbers 666173-) – [AR95759](#)

Change only with primary filter.

ENGINE

OIL FILTER (9500, 9600) – [RE57394](#)

OIL FILTER (9400) – [T19044](#)

For Engine 6359T Upto Combine Serial Numbers (-640100)

OIL FILTER (9400) – [RE59754](#)

For Engine 6068HH050 From Combine Serial Numbers (701246 -)

OIL FILTER (9400) – [AH128448](#)

For Upto Combine Serial Numbers (-650370)

Minimum hours before first engine oil change is 100 Hours. Extended engine oil change every 500 hours or annually, whichever come first. The extended 500 hour interval is only allowed if using Plus-50™ II oil with a John Deere filter and diesel fuel with sulfur content less than 15mg/kg (15ppm). If all conditions are not met, change oil and filter at 250 hours of operation.




CAB

RECIRCULATION AIR FILTER

(9400, 9500 AND 9600) – [AH115836](#)

Clean or replace every 200 hours and as required.



CAB

AIR FILTER, STANDARD

(9400, 9500 AND 9600) – [AH115833](#)

AIR FILTER, FOR OPERATORS WITH ALLERGIES

(9400, 9500 AND 9600) – [AH168783](#)

Clean or replace after 50 hours and as required.

ENGINE

FUEL WATER SEPARATOR FILTER

(9400, 9500 AND 9600) – [AT81478](#)

Replace every 500 hours and as required.



HYDRAULIC / HYDROSTATIC / ENGINE GEARCASE

OIL FILTER (9400, 9500 AND 9600) – [AH128449](#)

Replace every 400 hours or yearly.

Note: Replace all three filters at a time.



ENGINE

FUEL FILTER (9500, 9600) – [AR86745](#)

For Engine 6359T Upto Combine Serial Numbers (-640100)

FUEL FILTER (9400) – [RE62419](#)

For Engine 6068HH050 From Combine Serial Numbers (701246 -)

Replace every 500 hours and as required.



JOHN DEERE

Genuine Parts and Service

CAPACITIES

9400, 9500 and 9600 Maximizer and Sidehill Combines

CAPACITIES (Approximate):

Fuel Tank:

9400, 9500, 9500SH, 9600..... 530 L (140 gal)

**Cooling System with Heater:
Low Silicate Antifreeze**

9400, 9500, 9500SH, 9600 (Except Corn) 36 L (9.5 gal)
9600 Corn..... 40 L (10.5 gal)

**Engine Crankcase with Filter:
Torq-Gard Supreme™ or Plus-50™ II**

9400..... 18.9 L (4.99 gal)
9500, 9600..... 25 L (6.7 gal)
9500SH..... 23.2 L (6.12 gal)

**Transmission:
GL-5**

..... 9.6 L (2.5 gal)

**Final Drives (Each):
GL-5**

9400..... 8 L (2.11 gal)
9500..... 8.5 L (2.24 gal)
9500SH..... 7 L (1.84 gal)
9600 Ring and Pinion 8.5 L (2.2 gal)
9600 Planetary 6.2 L (1.6gal)

**Feeder House Reverser Gearcase:
GL-5**

9400, 9500, 9500SH, 9600..... 0.9 L (0.2 gal)

**Primary Countershaft Drive Gearcase:
GL-5**

9400, 9500, 9600..... 1.4 L (0.36 gal)
9500SH..... 1.7 L (0.44 gal)

**Straw Walker Drive Gearcase:
GL-5**

9400, 9500, 9500SH, 9600..... 0.7 L (0.18 gal)

**Dual-Range Cylinder Drive Gearcase:
GL-5**

9400, 9500SH, 9600..... 1.9 L (0.5 gal)

**Engine Gearcase:
Low Viscosity Hy-Gard™**

9400, 9500, 9500SH, 9600..... 16 L (4.2 gal)

**Loading Auger Gearcase:
GL-5**

9400..... 3.8 L (1 gal)
9500, 9500SH, 9600..... 4.7 L (1.2 gal)

**Hydraulic / Hydrostatic Reservoir:
Low Viscosity Hy-Gard™**

9400, 9500, 9500SH, 9600..... 34 L (9 gal)

[Return to Filter Overview](#)

