

FILTER OVERVIEW WITH SERVICE INTERVALS AND CAPACITIES

9560 STS, 9560i STS Series Combines

ENGINE AIR FILTER

SECONDARY AIR FILTER (9560)

[RE63932](#)

Used Up To Combine Serial Number (- 720100)

[AH212295](#)

Used From Combine Serial Number (720101 -)

SECONDARY AIR FILTER (9560i)

[AH212295](#)

Change secondary filter only with primary filter.



ENGINE AIR FILTER

PRIMARY AIR FILTER (9560)

[AH148880](#) – Used Up To Combine Serial Number (- 720100)

[AH212294](#) – Used From Combine Serial Number (720101 -)

PRIMARY AIR FILTER (9560i) – [AH212294](#)

Replace every 400 hours or service filters only when engine air filter light stays ON or change as required.
Note: Replace secondary filter also with primary filter.



ENGINE OIL FILTER

OIL FILTER (9560)

[RE509672](#) – For Engine 6081HH019-RG31818, 6081HH028-RE531333

[RE504836](#) – For Engine 6068HH058-RE526762

OIL FILTER (9560i)

[RE509672](#) – 6090HH005-RE528457

Minimum hours before first engine oil change is 100 hours. Extended engine oil change every 500 hours or annually, whichever come first. The extended 500 hour interval is only allowed if using Plus-50™ II oil with a John Deere filter and diesel fuel with sulfur content less than 15mg/kg (15ppm). If all conditions are not met, change oil and filter at 250 hours of operation.

CAB

AIR FILTER, HEAVY-DUTY [AH168783](#)

AIR FILTER, STANDARD [AH115833](#)

Clean or replace every 50 hours and as required.



CAB FILTER

RECIRCULATION AIR FILTER

[AH115836](#)

9560 - Used Up To Combine Serial Number(-720100)


9650i - Used Up To Combine Serial Number(-720200)

[H220870](#)

9560 - Used From Combine Serial Number (720101-)

9650i - Used From Combine Serial Number (720201-)

Clean or replace every 200 hours and as required.



HYDROSTATIC PUMP / ENGINE GEARCASE / MAIN HYDRAULIC FILTER

OIL FILTER – [AH128449](#)

Replace every 400 hours.

Note: Replace all three filters at a time.

(Click here for [capacity](#))



ENGINE FUEL FILTER

PRIMARY FUEL FILTER (9560)

[RE522372](#) – For Engine 66081HH019-RG31818

Up To Engine Serial Number (-232462)

[RE531703](#) – For Engine 6081HH019-RG31818

From Engine Serial Number (232463-)

PRIMARY AND FINAL FUEL FILTER (9560i)

[RE525523](#)

Replace every 500 hours.

ENGINE FUEL FILTER

FINAL FUEL FILTER (9560)

[R502778](#) – For Engine 6081HH019-RG31818 Up To Engine Serial Number (-232462)

[RE522688](#) – For Engine 66081HH019-RG31818 From Engine Serial Number (232463-)

For Engine 6081HH028-RE531333

[RE522878](#) For Engine 6068HH058-RE526762

Replace every 500 hours.



FUEL WATER SEPARATOR FILTER, STANDARD

[R502778](#) – (9560 - For CIS) (9560i)

[RE541922](#) (9560) – Used From

Combine Serial Number (720101 -)

Replace after first 50 hours and then every 500 hours.



JOHN DEERE

Genuine Parts and Service

CAPACITIES

9560 STS, 9560i STS Series Combines

CAPACITIES (Approximate):

Fuel Tank:

9560, 9560i..... 757 L (199.97 gal)

Cooling System with Heater:

Cool-Gard™

9560 (710251 - 720100)..... 40 L (10.56 gal)

9560 (720101-) (6.8 L Engine) 44 L (11.62 gal)

9560 (720101-) (8.1 L Engine) 53.3 L (14.08 gal)

9560i..... 53.3 L (14.08 gal)

Engine Crankcase with Filter:

Torq-Gard Supreme™ or Plus-50™ II

9560 (710251 - 720100)..... 29.5 L (7.79 gal)

9560 (720101-) (6.8 L Engine) 32 L (8.45 gal)

9560 (720101-)(8.1 L Engine) 29.5 L (7.79 gal)

9560i..... 29.5 L (7.79 gal)

Transmission:

GL-5

9560, 9560i..... 9.6 L (2.53 gal)

Final Drives:

GL-5

9560, 9560i..... 8 L (2.11 gal)

Feeder House Reverser Gearcase without Cooler:

GL-5

9560, 9560i..... 2.3 L (0.60 gal)

Feeder House Reverser High Capacity with Cooler:

GL-5

9560, 9560i..... 3.5 L (0.92 gal)

Countershaft Drive Gearcase:

GL-5

9560, 9560i..... 1.2 L (0.31 gal)

Loading Auger Gearcase:

GL-5

9560, 9560i..... 3.8 L (1 gal)

Two Speed Separator Drive Gearcase:

GL-5

9560..... 2.4 L (0.63 gal)

9560i..... 4.7 L (1.24 gal)

Engine Gearcase with Transfer:

Low Viscosity Hy-Gard™

9560, 9560i..... 21.3 L (5.62 gal)

Hydraulic / Hydrostatic Reservoir:

Low Viscosity Hy-Gard™

9560..... 34 L (8.98 gal)

9560i..... 35 L (9.24 gal)

[Return to Filter Overview](#)

