

FILTER OVERVIEW WITH SERVICE INTERVALS AND CAPACITIES

9RT Final Tier 4 (FT4) Series Track Tractors - 9470RT, 9520RT, 9570RT

9470RT, 9520RT - JD 13.5L Engine
9570RT - Cummins QSX15

ENGINE

CRANKCASE BREATHER FILTER ELEMENT (15L)
[RECCV5063400](#)
Replace after every 3000 hours.



CAB

**RECIRCULATION AIR FILTER – [RE291412](#)
[RE333569](#) (Carbon)**
Replace after every 1000 hours or annually,
whichever occurs first.
(Interval may vary according to operating conditions).



CAB

**FRESH AIR FILTER – [RE284091](#)
[RE333567](#) (Carbon)**
Replace after every 1000 hours or annually,
whichever occurs first.
(Interval may vary according to operating conditions.)




ENGINE

FUEL TANK VENT FILTER – [H216169](#) (Qty. 2)
Replace after 1500 hours or 1 year whichever
occurs first.
(Click here for [capacity](#))



SCV

OIL FILTER – [RE269061](#)
Replace after every 1500 hours.




ENGINE

DEF TANK VENT FILTER – [H216169](#)
Replace after 1500 hours or 1 year whichever
occurs first.
(Click here for [capacity](#))



ENGINE

SECONDARY AIR FILTER
[RE594853](#) (FT4) (Qty. 2)
[RE230985](#) (Tier 2 and Tier 3 Engine) (Qty. 2)
Replace after every 1000 hours or annually,
whichever occurs first. (Interval may vary according to
operating conditions.)



ENGINE

PRIMARY AIR FILTER
[RE594852](#) (FT4) (Qty. 2)
[RE312946](#) (Tier 2 and Tier 3 Engine) (Qty. 2)
Replace after every 1000 hours or annually,
whichever occurs first. (Interval may vary
according to operating conditions.)



ENGINE

DIESEL PARTICULATE FILTER (DPF)
(9470RT & 9520RT)
[DZ100175](#) - SIZE 7
[RE561844](#) - SIZE 8
[REC550603000](#) (9570RT)
Replace within 250 hours after warning light indicators are
illuminated. See your John Deere™ dealer or qualified service
provider.



ENGINE

OIL FILTER (9570RT) –
[RE574468](#) (FT4)
[RE572785](#) (Tier 2 and Tier 3 Engine)
[RE572785](#) (9470RT & 9520RT)
Initial oil and filter change at 100 hours, then after
every 400 hours or annually, whichever occurs first.
The extended 400 hour interval is only allowed if using
Plus-50™ II oil with a John Deere filter and diesel fuel
with sulfur content less than 15mg/kg (15ppm). If all
conditions are not met, change oil and filter at 250 hours
of operation.
(Click here for [capacity](#))



ENGINE

FUEL WATER SEPARATOR FILTER
(If equipped) [N378886](#) (- 920104)
[AT365869](#) (920105 -)
Change after every 500 hours.



OIL FILTER – [RE577612](#) (Qty. 2)
Replace after every 1500 hours or
as indicated, whichever occurs first.
(Click here for [capacity](#))



JOHN DEERE
Genuine Parts and Service

HYDRAULICS

STEERING PUMP FILTER –
[RE577250](#)
Replace after every 1500 hours.
(Click here for [capacity](#))



TRANSMISSION

TRANSMISSION SYSTEM FILTER
[RE577250](#)
TRANSMISSION LUBE FILTER
[RE577612](#)
Replace after every 1500 hours.
(Click here for [capacity](#))



ENGINE

DEF TANK HEADER FILTER
[DZ111004](#)
Replace after every 4500 hours.



ENGINE

DEF INLINE FILTER
[DZ100304](#) (- 062000)
[DZ110513](#) (062001 -)
Replace after every 1000 hours or
annually, whichever occurs first.



CAPACITIES

9RT Final Tier 4 (FT4) Series Track Tractors - 9470RT, 9520RT, 9570RT

CAPACITIES (Approximate):

Fuel Tank:

..... 1324 L (350 gal)

Cooling System:

Cool-Gard™II

9470RT & 9520RT 56.5 L (14.9 gal)

9570RT 62.0 L (16.3 gal)

Crankcase (including Filter):

Plus-50™

9470RT & 9520RT 48 L (12.7 gal)

9570RT 43.5 L (11.5 gal)

Transmission/Hydraulic/Rear Axle System:

Hy-Gard™

Hydraulic Reservoir Volume Reference Marks

Full - Cold 90.3 L (23.9 gal)

Min - Cold 79 L (20.9 gal)

High Volume Takeout Oil Mark 126.3 L (33.4 gal)

Reservoir Volume Between Min - Cold & Full - Cold 11.4 L (3 gal)

Transmission/Hydraulic Reservoir/Rear Axle System Volume:

Hy-Gard™

Total System Volume (without 3 Point and PTO) 300 L (79.3 gal)

Total System Volume (with 3 Point and PTO) 307.8 L (81.3 gal)

DEF Tank:

John Deere™ Diesel Exhaust Fluid

..... 93.9 L (24.8 gal)

[Return to Filter Overview](#)

