

# WEAR PARTS OVERVIEW

## 630D Cutting Platform

### REEL FINGERS

#### FULL BAT

[AH166489](#) (Set of 10)

[AH166493](#) (Set of 130)

#### LH BAT

[AH166490](#) (Set of 10)

#### RH BAT

[AH166491](#) (Set of 10)

#### NO BAT

[KXE10477](#) (Set of 10)

#### WIDE REEL FINGER

[H207933](#)

Improved sweeping action in short / light crops  
prongs "spear" into crop to minimize shatter.

### BELT

#### DRAPER BELT

[AXE14731](#) (Qty = 2, LGTH = 7547 mm)

### GUARDS

#### 4-INCH NON-CLOG KNIFE, HIGH WEAR

[HXE19625](#)

Recommended for heavy trash conditions or wet  
tangled crops.

#### 4-INCH DUAL DRIVE BOTTOM CENTER

[HXE19623](#) (RH)

[HXE18172](#) (LH)

Heat treated and boronized for extra wear life.

### KNIFE SECTIONS



#### [H153329](#) (Fine Tooth)

Small grains or grassy undergrowth  
conditions.



#### [H163131](#) (Coarse Tooth)

Coarse grains / soybeans.



#### [H215025](#) Short / Long (Fine Tooth)

Recommended for no-till. Can be used  
with standard or no-till guards.



#### [H215064](#) Short / Long (Coarse Tooth)

Recommended for no-till. Can be used with  
standard or no-till guards.

### KNIFE SECTIONS



#### END SECTIONS

[H161242](#) (Fine Tooth)

### GUARDS



#### 4-INCH DUAL DRIVE TOP CENTER

[AH226928](#)

#### DRAPER END

[H226528](#)



#### STANDARD LONG POINT

[H213405](#) (LSL)

[H213508](#) (SLS)

Heat treated & carburized for wear resistant  
outer surface.



#### HIGH WEAR LONG POINT

[H229539](#) (LSL)

[H229540](#) (SLS)

Heat treated and boronized for extra wear life.

