

# REPLACEMENT PARTS GUIDE

## 9030 Series Track Tractors - 9430T, 9530T, 9630T

### FILTER OVERVIEW WITH SERVICE INTERVALS

#### ENGINE

##### PRIMARY AIR FILTER

[RE261960](#)

Replace annually or as indicated. (Interval may vary according to operating conditions.)

##### SECONDARY AIR FILTER

[RE230985](#)

Replace annually or every second replacement of primary filter.

##### OIL FILTER

[RE572785](#)

Initial oil and filter change at 100 hours and then after every 250 hours. Scheduled interval of 250 hours can be extended to 375 hours if John Deere Plus-50 oil and John Deere filter is used.

##### PRIMARY FUEL FILTER

[RE532952](#)

##### SECONDARY FUEL FILTER

[DZ112918](#)

Replace after 100 hours, then after every 250 hours or as required, whichever occurs first. (Interval may vary according to operating conditions.)

##### MOTOR SEAL DRAIN FILTER

[AL221066](#)

Change annually or as required.

##### STEERING FILTER

[RE69054](#)

Replace after 1500 hours. (Interval may vary according to operating conditions.)

#### HYDRAULICS

##### RESERVOIR OIL FILTER

[AT101565](#)

Replace after every 750 hours. (Interval may vary according to operating conditions.)

#### CAB

##### RECIRCULATION AIR FILTER

[RE187966](#)

Clean after every 250 hours or as required. Replace annually and as required. (Interval may vary according to operating conditions.)

##### ACTIVATED CARBON RECIRCULATION FILTER

[RE199682](#)

Do NOT clean. Replace annually or as required. (Interval may vary according to operating conditions.)

##### AIR FILTER, STANDARD

[RE24619](#)

Clean after every 250 hours and replace annually. (Interval may vary according to operating conditions.)

##### OPERATION AIR FILTER

[RE199681](#)

Do NOT Clean. Change annually, after 500 hours, or as required.

##### FUEL TANK VENT FILTER

[RE52504](#)

Replace every 1000 hours. (Interval may vary according to operating conditions.)

#### TRANSMISSION

##### FILTER

[RE174130](#)

Replace after 100 hours, then after every 750 hours or as required, whichever occurs first.

#### HYDRAULICS

##### HYDRAULIC OIL FILTER

[RE174130](#)

Replace after 1500 hours, as required or as indicated. (Interval may vary according to operating conditions.)



RX532520

Jan 2024. Release Date.

# CAPACITIES

## 9030 Series Track Tractors - 9430T, 9530T, 9630T

**CAPACITIES (Approximate):**

**Fuel Tank:**

..... 1249 L (330 gal)

**Cooling System:  
Cool-Gard™ II**

..... 53 L (14 gal)

**Crankcase:  
Plus-50™**

9430T..... 40 L (10.5 gal)  
9530T-9630T..... 56 L (14.8 gal)

**Transmission / Axle-PST:**

**Hy-Gard™**

Axles Only ..... 178 L (47 gal)  
Transmission with Axle ..... 227 L (60 gal)  
With PTO ..... 230 L (61 gal)

**Hydraulic System:**

**Hy-Gard™**

Without Hitch ..... 102 L (27 gal)  
With Hitch ..... 104 L (27.5 gal)

# REPLACEMENT PARTS GUIDE

## 9030 Series Track Tractors - 9430T, 9530T, 9630T

### REPAIR PARTS

#### ENGINE

 **STARTER**  
[RE539584](#)


 **AUXILLARY DRIVE BELT**  
[R241746](#)

 **FAN DRIVE BELT**  
[R239551](#)

 **RADITOR CAP**  
[AT322214](#)

 **BELT TENSIONER**  
[RE243154](#)

 **WATER PUMP**  
[RE549117](#)

 **ENGINE BLOCK HEATER**  
[AR84185](#)

 **A/C COMPRESSOR**  
[RE52454](#)

 **ALTERNATOR**  
[RE555751](#)

 **FUEL INJECTION PUMP**  
[DZ124926](#) - 3712  
[DZ124927](#) - 3703


 **TORSIONAL DAMPER**  
[RE530733](#)

 **BATTERY**  
[TY25879B](#)



#### CAB

 **INTERNAL REAR VIEW**  
[AT186760](#)




 **EXTERNAL REAR VIEW**  
[AL78021](#) - Outer Rear View  
[R134059](#) - Remote Power






 **WIPER BLADE**  
[AL153661](#) - Front And Rear



 **TECHNOLOGY MOUNTING SOLUTION**  
[BRE10141](#) - Mounting Bracket  
[BRE10015](#) - Cell Phone Mount  
[BRE10255](#) - Tablet Mount

 **GAS CYLINDERS**  
[RE234165](#) - LH Door  
[RE234166](#) - Rear Window

#### HITCH AND SCV

**HITCH MAINTENANCE**  
 [R253500](#) - Sway Block RH  
 [R253501](#) - Sway Block LH  
 [RE334228](#) - Rockshaft Position Sensor

**SCV**  
 [RE577560](#) - Breakaway Coupler  
 [R186598](#) - Snap Ring  
 [RE186600](#) - Seal Kit  
 [RE220072](#) - Power Beyond Coupler Kit  
 [RE151894](#) - Hydraulic Motor Return Kit

**LIFT LINK PINS**  
 [R272197](#) - Pin  
 [R107278](#) - Draft Link Ball Stud

RX532520

Jan 2024. Release Date.


# REPLACEMENT PARTS GUIDE


## 9030 Series Track Tractors - 9430T, 9530T, 9630T

### WEAR PARTS





**ENGINE**

 **VARI-COOL™ FAN DRIVE**  
[RE588804](#) - Driven, 13.5 L

 **VARI-COOL™ FAN DRIVE**  
[RE588803](#) – Driver, 13.5L  
[RE592556](#) – Rotary Union

**ENGINE**

 **VARI-COOL™ FAN DRIVE**  
[R239551](#) - V-Belt, Variable Speed

 **VARI-COOL™ FAN DRIVE**  
[R569237](#) - Belt Gauge Tool