

REPLACEMENT PARTS GUIDE

8R Interim Tier 4/Stage IIIB Tractors (016001-090000) – 8235R, 8260R, 8285R, 8310R, 8335R, 8360R

FILTER OVERVIEW WITH SERVICE INTERVALS

CAB

RECIRCULATION AIR FILTER

[RE291412](#)

Replace after every 1000 hours, annually or as required, whichever occurs first.

FRESH AIR FILTER

[RE284091](#)

Replace after every 1000 hours, annually or as required, whichever occurs first. (Interval may vary according to operating conditions.)

SCV

OIL FILTER

[RE269061](#)

Replace every 1500 hours.

HYDRAULIC/TRANSMISSION

OIL FILTER

[RE210857](#)

Replace every 1500 hours or as indicated, whichever occurs first.

ENGINE

FUEL WATER SEPARATOR FILTER

[N378886](#) - If equipped

Clean after every 500 hours, then after every fifth back flushing of water separator assembly or as necessary.

DIESEL PARTICULATE FILTER

[RE541834](#) - (8235R, 8260R, 8285R)

[RE542183](#) - (8310R, 8335R, 8360R)

Replace within 250 hours after warning light indicators are illuminated. See your John Deere dealer or qualified service provider.

ENGINE

PRIMARY AIR FILTER

[RE587793](#)

Clean after every 250 hours and as required.

Replace after every 1000 hours, annually or as indicated, whichever occurs first.

SECONDARY AIR FILTER

[RE587794](#)

Replace after every 1000 hours or as indicated, whichever occurs first.

FUEL TANK VENT FILTER

[H216169](#)

Clean after every 1000 hours and replace after every 1500 hours.

(Interval may vary according to operating conditions.)

OIL FILTER

[RE509672](#)

Initial oil and filter change at 100 hours and then after every 500 hours or annually, whichever comes first.

The extended 500 hour interval is only allowed if using Plus-50™ II oil with a John Deere filter and diesel fuel with sulfur content less than 15mg/kg (15ppm).

If all the conditions are not met, change oil and filter at 250 hours of operation.

(ENGINE OPTION CODE 3521)

PRIMARY FUEL FILTER

[RE539465](#)

SECONDARY FUEL FILTER

[DZ112918](#)

(ENGINE OPTION CODE 3523)

FUEL FILTER KIT

[RE525523](#) - Include Both Primary and Final Fuel Filters

Replace after every 500 hours, annually, or as indicated whichever comes first. Always replace both filters at same time.



CAPACITIES

8R Interim Tier 4/Stage IIIB Tractors (016001-090000) – 8235R, 8260R, 8285R, 8310R, 8335R, 8360R

CAPACITIES (Approximate):

Fuel Tank:

..... 695 L (184.0 gal)

Cooling System:

Cool-Gard™ II

.....41 L (10.8 gal)

Transmission / Hydraulics:

Hy-Gard™

MFWD165 L (43.0 gal)

Independent Link Suspension (ILS™)..... 175 L (46.0 gal)

Crankcase 2WD or 1300 MFWD:

Plus-50™ II

8235R, 8260R, 8285R..... 25 L (6.6 gal)

Crankcase 1500 MFWD:

Plus-50™ II

..... 28 L (7.4 gal)

Crankcase Independent Link Suspension:

Plus-50™ II

..... 27.5 L (7.3 gal)

1300 MFWD Axle Housing:

Hy-Gard™

..... 13.6 L (3.6 gal)

1500 MFWD Axle Housing:

Hy-Gard™

..... 18.7 L (4.9 gal)

MFWD Hubs (Each):

GL-5

..... 3.8 L (1.0 gal)

REPAIR PARTS

8R Interim Tier 4/Stage IIIB Tractors (016001-090000) – 8235R, 8260R, 8285R, 8310R, 8335R, 8360R

CAB



INTERNAL MIRRORS
[AT186760](#)



WIPER BLADES
[AL153661](#) - Front and Rear



EXTERNAL MIRRORS
[RE307815](#) - Head Power
[RE320917](#) - Power Tilt
[RE322784](#) - W/ Manual, W/O Wide angle



TECHNOLOGY MOUNTING SOLUTION
[RE317435](#) - Mounting Bracket
[BXE10606](#) - Cell Phone Mount
[BXE10607](#) - Tablet Mount



GAS CYLINDERS
[RE261887](#) - LH Door
[RE261886](#) - Rear window

HITCH AND SCV



HITCH MAINTENANCE
[R210605](#) - Sway Block Wear Plate RH
[R207665](#) - Sway Block RH
[R210604](#) - Sway Block Wear Plate LH
[R207666](#) - Sway Block LH
[RE334232](#) - Rockshaft position sensor



SCV
[RE577560](#) - Breakaway coupler
[R186598](#) - Snap Ring
[RE186600](#) - Seal Kit
[RE281166](#) - Power Beyond Coupler Kit
[AR114664](#) - Hydraulic Motor Return



LIFT LINK PINS
[R169163](#) - Pin
[R107278](#) - Draft Link Ball Stud

ENGINE



BATTERY
[TY25879B](#)



TORSIONAL DAMPER
[RE586976](#)



ENGINE



STARTER
[RE549229](#) - IT4/ Stage IIIB
[RE529661](#) - T2



FUEL INJECTION PUMP
[RE571640](#) - T2
[RE543262](#) - IT4/ Stage IIIB



FAN DRIVE BELT
[R568198](#)



AUXILIARY BELT FOR WATER PUMP
[R211183](#) - W/O Air Brake
[R210808](#) - W/ Air Brake



ENGINE BLOCK HEATER
[RE42139](#) - 120V
[RE524675](#) - 240V



BELT TENSIONER
[RE582500](#)



RADIATOR CAP
[RE312969](#)



WATER PUMP
[DZ102107](#) - IT4/ Stage IIIB
[RE530194](#) - T2



A/C COMPRESSOR
[RE52454](#)



ALTERNATOR
[RE555751](#)

ENGINE



TIE ROD ENDS
[RE583653](#) - ILS™
[RE173541](#) - LH, 1300 MFWD
[RE173540](#) - RH, 1300 MFWD
[RE586457](#) - 1500 MFWD

For Company Use : RX532590

Apr 2022. Release Date.



JOHN DEERE
Genuine Parts and Service

CLICK PART NUMBER TO BUY

*See operator's manual for additional details