

REPLACEMENT PARTS GUIDE

T660 COMBINE (MY 2007 - 2015)



ENGINE



**SHORT FILTER
PRIMARY AIR FILTER**
[AH148880](#)
SECONDARY AIR FILTER
[RE63932](#)

Change as require or when Diagnostic Trouble Code (DTC) is generated.



OIL FILTER
[RE509672](#)

Change after every 250 hours or every year.



MAIN ENGINE GEARCASE FILTER
[CE19990](#)

Change after every 400 hours or every year



DIESEL PARTICULATE FILTER
[DZ100174](#)

Check Every 4500 hours or Diagnostic Trouble Code (DTC) is generated..



**LONG FILTER
PRIMARY AIR FILTER**
[AH164062](#)
SECONDARY AIR FILTER
[AH164063](#)

Change as require or when Diagnostic Trouble Code (DTC) is generated.



**FUEL FILTER
PRIMARY FUEL FILTER**
[RE520906](#)
PRIMARY AND SECONDARY FUEL FILTER
[RE525523](#)

Change as require or when Diagnostic Trouble Code (DTC) is generated..



HYDRAULIC OIL FILTER
[AL203061](#)

Change every 400 hours



**MAIN ENGINE GEARCASE FILTER
(PRODRIVE™ TRANSMISSION)**
[AH128449](#)

Change after first 100 hours.

CAB



FRESH AIR FILTER
[RE284091](#)
(MY 2012 - 2015)



RECIRCULATION AIR FILTER
[L214634](#)
(MY 2012 - 2015)
[H220870](#)
(MY 2007 - MY 2011)
Clean or replace every 50 hours and as required



FUEL PRECLEANER FILTER
[R502778](#)
PREMIUM FUEL PRECLEANER FILTER
[N378886](#)
Drain every 50 hours or weekly

ENGINE



**FINAL TIER 4
PRIMARY FUEL FILTER**
[RE539465](#)
SECONDARY FUEL FILTER
[DZ112918](#)

Change as require or when Diagnosti Trouble Code (DTC) is generated



**HYDROSTATIC DRIVE CHARGE PUMP FILTER
(PRODRIVE™ TRANSMISSION)**
[AN207368](#)



NON-PRODRIVE™ TRANSMISSION
[AH128449](#)

Change after every 400 hours



1

2

3

4

5

6

7

8

9

10

11

12

13



JOHN DEERE
Genuine Parts and Service

CLICK PART NUMBER TO BUY

*See operator's manual for additional details.

For Company Use - ZX543869

Sep.2022. Release Date.

CAPACITIES

T660 Combine (MY 2007 - 2015)

CAPACITIES (Approximate):

Fuel Tank:	800 L (210 gal)
Grain Tank (MY 2014 - 2015)	9000 L (2378 gal)
(MY 2007 – 2013)	11000 L(2905 gal)
Cooling System with Heater: (Cool-Gard II)	45 L (11.88 gal)
Engine Crankcase with Filter (Plus-50™ II)	29 L (7.6 gal)
Transmission (3-Speed Mechanical Shift and Push Button Shift) – (GL-5) (MY 2014 - 2015)	7 L (1.85 gal)
(MY 2007 – 2013)	9.6 L (2.53 gal)
Final Drive (GL-5) (MY 2014 - 2015)	7 L (1.85 gal)
(MY 2007 – 2013)	8.5 (2.24 gal)

Engine Gearcase with Transfer (3-Speed Mechanical Shift and Push Button Shift Machines) – (Hy-Gard™)	16 L (4.22 gal)
Engine Gearcase with Transfer (ProDrive™ Machines) –(Hy-Gard™)	20 L (5.25 gal)
Hydraulic System Reservoir (Hy-Gard™)	34 L (9.51 gal)
Feeder house reverser gear case (ISO VG 460 Fully Synthetic)	2 L (0.5 gal)
Countershaft drive gear case (GL-5)	1.2 L (0.32 gal)
Loading Auger Gearcase (GL-5)	3.8 L (1 gal)

[RETURN TO FILTER OVERVIEW ENGINE GEARCASE WITH TRANSFER](#)

REPLACEMENT PARTS GUIDE

T660 COMBINE

THRESHING

MY11-22

[AZ58905](#) – RASP BARS

Paired by weight with deep heat treatment for excellent threshing, good drum balancing and long lifetime.

MY11-15

[AXE53048](#) - UNIVERSAL CONCAVE

MY16-18

**[AXE68051](#) - HIGH-DIVERSITY
UNIVERSAL CONCAVE**

Perfect fit and versatility with the adjustable booster bar.

[AXE53100](#) - SMALL GRAIN CONCAVE

MY16-18

**[AXE68168](#) - HIGH-DIVERSITY SMALL
GRAIN CONCAVE**

Exactly welded for easy adjustment and perfect threshing.

MY19-22

[AXE59411](#) - HIGH VERSATILITY CONCAVE

**[AXE59409](#) - CONCAVE INSERT SMALL
GRAIN**

**[BXE10909](#) - ROUND BAR CONCAVE
INSERT KIT**

High versatility with easy-to-exchange inserts.



STRAW CHOPPER

PREMIUM KNIVES

Induction hardened to resist wear and tear at the punched hole and the cutting edge.



MY11-15

**[Z103205](#) - PREMIUM CHOPPER SERRATED
KNIFE**



**[Z103376](#) - PREMIUM CHOPPER SMOOTH
KNIFE**

**[Z75874](#) - PREMIUM CHOPPER
STATIONARY KNIFE**

MY11-22

**[Z105500](#) - PREMIUM HEAVY-DUTY
SERRATED KNIFE**

STANDARD KNIVES

Induction hardened to resist wear and tear at the punched hole and the cutting edge.



MY11-15

**[Z77601](#) - STANDARD CHOPPER
SERRATED KNIFE**



**[Z42176](#) - STANDARD CHOPPER CORN
KNIFE**



MY11-15, MY11-15

**[HXE13024](#) - STANDARD CHOPPER
STATIONARY KNIFE SMOOTH**



MY11-22

**[Z53454](#) - STANDARD CHOPPER SMOOTH
KNIFE**



**[HXE13023](#) - STANDARD CHOPPER
STATIONARY KNIFE SERRATED**

REPLACEMENT PARTS GUIDE

T660 COMBINE

FEEDERHOUSE

OUTER CHAIN

Made for smooth running, resisting load spikes and minimal elongation.



MY11-15

[AZ63336](#)



[AZ102573](#) (HEAVY DUTY)



MY16-22

[AXE41939](#)

INNER CHAIN

Made for smooth running, resisting load spikes and minimal elongation.



MY11-15

[AZ63337](#)



[AZ102574](#) (HEAVY DUTY)



MY16-22

[AXE41940](#)



GRAIN HANDLING

[AZ101808](#) - CLEAN GRAIN ELEVATOR CHAIN

Made for smooth running, resisting load spikes and minimal elongation.



STRAW WALKER

MY16-22

[AZ45586](#) - BEARING

Original John Deere bearings don't warp, open, crack or break, nor will they seize on the shaft.

