

For the installation of software on the Starfire™ 6000, there are two options to initiate programming of the receiver.

Option I – Starfire™ 6000 Receiver USB Direct

At Computer

1. Download the new software and save the .zip file to your computer (desktop).
2. Select the file that is now on your desktop and **extract** the data (this is the same as unzip) to your desktop.
3. Using a USB storage device a specific file structure will need to be created. (*Note - the folder names will need to be in the English Language*)
 - a. First create a folder and title it “**Programs**”
 - b. Create a secondary folder within the “Programs” folder titled “**Receiver**”
4. Copy the extracted file to the USB storage device file structure - **Programs > Receiver**
 - a. Verify that you have a **.gst** file on our USB storage device within the receiver folder.

If you have a **.gst** file in the receiver folder the software is now ready to be installed.

At Machine

1. Identify the StarFire 6000 USB port on the bottom of the receiver
2. Insert your USB with the correct **.gst** file embedded and proceed to the display within the cab to initiate download.
3. At the display, follow the steps below to initiate the programming of the StarFire 6000
 - a. Select “Main Menu”
 - b. Select “StarFire 6000” icon
 - c. Select “USB Drive” (softkey “A”)
 - d. Select “Update Receiver”
 - e. Select correct file for programming

Note – the process typically takes 3 minutes to process completely

 - f. When prompted, select “continue” button to proceed to normal working functionality

Option II- Starfire™ 6000 Receiver with GreenStar™ Display

At Computer

Necessary tools: USB or Datacard for specific display

1. Verify your storage device has 'Live Update'
 - a. 'Live Update' is available for download via Stellar Downloads & Updates
 - b. Save the 'Live Update' for the correct display to the corresponding storage device
2. Download the new software for the Starfire™ 6000 and save the .zip file to your computer (desktop)
3. Select the file that is now on your desktop and **extract** the data (this is the same as unzip).
 - a. Copy the extracted .gst file to the **Receiver** folder located inside the **Programs** folder.
4. Verify that you have a .gst file on our storage device within the receiver folder.

At Machine

1. Insert the storage device into the display.
2. Using the menu, select **Message Center**.
3. Select softkey "A" (Reprogram Device).
4. Highlight **GPS Receiver** and select **Reprogram Device**.
5. In the drop-down box beside **Change to Version**, select your desired software version.
6. Select the Accept button.

Note - process typically takes 40-60 minutes to complete
7. When prompted, select "continue" button to proceed to normal working functionality