



JOHN DEERE

NOTHING RUNS LIKE A DEERE



# FULL SIZE CROSS OVER XUV835E / XUV865E



PERFORMANCE	UPTIME	COST OF OPERATION
<p>Tilted steering and adjustable operator seat</p> <p>Room for 3 passengers</p> <p>Easily adjustable suspension for varying payloads</p> <p>Standard 4-wheel drive system and diff lock</p> <p>Front and Rear Independent suspension</p>	<p>Easy access to key service points reduces downtime</p>	<p>Self-servicing kit reduces cost of maintenance</p> <p>Improved drive belt design, which reduces down time and replacement cost</p> <p>Maintenance free ball joints</p>

# SPEIFICATIONS

MODEL	XUV835E	XUV865E
-------	---------	---------

## Engine

Displacement	812 cc	854 cc
Power	43* kW 54* hp	17.0* kW 22.8 hp
Type	4-cycle gas, Electronic Fuel Injection (EFI)	4-cycle diesel

## Drivetrain

Descent control	Yes	Yes
Final drive	Two speed, oil bath	Two speed, oil bath
Four-wheel drive	On-demand true four-wheel drive system	On-demand true four-wheel drive system
Max. traveling speed	0-72 hi forward, 0-47 lo forward, 0-53 reverse km/h	0-51 hi forward, 0-24 lo forward, 0-29 reverse km/h
Transmission	Continuously Variable Transmission (CVT) with clutch enclosure	Continuously Variable Transmission (CVT) with clutch enclosure

## Suspension

Front   Rear	Fully independent dual A-Arm with adjustable coils; 7.9 inches (200.7 mm) of travel Fully independent dual A-Arm with adjustable coils and sway bar; 9.1 inches (231.14 mm) of travel	Fully independent dual A-Arm with adjustable coils; 7.9 inches (200.7 mm) of travel Fully independent dual A-Arm with adjustable coils and sway bar; 9.1 inches (231.14 mm) of travel
--------------	--	--

## Dimensions / Capacities

Cargo box capacity	454 kg	454 kg
Fuel capacity	42.4 L	42.4 L
Ground clearance	284 mm	284 mm
Payload capacity	680 kg	680 kg
Towing capacity	907 kg	907 kg

# FULL SIZE CROSS OVER XUV835M / XUV865M

## (open station, cab, HVAC cab)



PERFORMANCE	UPTIME	COST OF OPERATION
Tilted steering and adjustable operator seat	Easy access to key service points reduces downtime	Self-servicing maintenance kits reduces cost of maintenance
Room for 3 passengers	Factory installed wiring in order to connect more attachments and accessories.	Improved drive belt design, which reduces down time and replacement cost
Easily adjustable suspension for varying payloads		Maintenance free ball joints
Factory Installed Power Steering		
Standard 4-wheel drive system and diff lock		
Front and Rear Independent suspension		

# SPEIFICATIONS

MODEL	XUV835M Open	XUV835M Cab / HVAC	XUV865M Open	XUV865M Cab / HVAC
-------	--------------	--------------------	--------------	--------------------

## Engine

Displacement	812 cc	812 cc	854 cc	854 cc
Power	43* kW 54* hp	43* kW 54* hp	17.0* kW 22.8 hp	17.0* kW 22.8 hp
Type	4-cycle gas, Electronic Fuel Injection (EFI)		4-cycle diesel	

## Drivetrain

Descent control	Yes	Yes	Yes	Yes
Final drive	Two speed, oil bath	Two speed, oil bath	Two speed, oil bath	Two speed, oil bath
Four-wheel drive	On-demand true four-wheel drive system		On-demand true four-wheel drive system	
Max. traveling speed	0-72 hi forward, 0-47 low forward 0-53 reverse km/h		0-51 hi forward, 0-24 low forward, 0-29 reverse km/h	
Transmission	Continuously Variable Transmission (CVT) with clutch enclosure			

## Suspension

Front   Rear	Fully independent dual A-Arm with adjustable coils; 200.7 mm of travel Fully independent dual A-Arm with adjustable coils and sway bar; 231.14 mm of travel
--------------	--

## Dimensions / Capacities

Cargo box capacity	454 kg	454 kg	454 kg	454 kg
Fuel capacity	42.4 L	42.4 L	42.4 L	42.4 L
Ground clearance	284 mm	284 mm	284 mm	284 mm
Payload capacity	680 kg	680 kg	680 kg	680 kg
Towing capacity	907 kg	907 kg	907 kg	907 kg
Power steering	Yes	Yes	Yes	Yes



# FULL SIZE CROSS OVER XUV835R / XUV865R



PERFORMANCE	UPTIME	COST OF OPERATION
<p>Tilted steering and adjustable operator seat</p> <p>Room for 3 passengers</p> <p>Easily adjustable suspension for varying payloads</p> <p>Factory Installed Power Steering</p> <p>Standard 4-wheel drive system and diff lock</p> <p>Front and Rear Independent suspension</p>	<p>Easy access to key service points reduces downtime</p> <p>Factory installed wiring in order to connect more attachments and accessories.</p>	<p>Self-servicing maintenance kits reduces cost of maintenance</p> <p>Improved drive belt design, which reduces down time and replacement cost</p> <p>Maintenance free ball joints</p>

# SPESIFICATIONS

MODEL	XUV835R	XUV865R
-------	---------	---------

## Engine

Displacement	812 cc	854 cc
Power	43* kW 54* hp	17.0* kW 22.8 hp
Type	4-cycle gas, Electronic Fuel Injection (EFI)	4-cycle diesel

## Drivetrain

Descent control	Yes	Yes
Final drive	Two speed, oil bath	Two speed, oil bath
Four-wheel drive	On-demand true four-wheel drive system	On-demand true four-wheel drive system
Max. traveling speed	0-72 hi forward, 0-47 lo forward, 0-53 reverse km/h	0-51 hi forward, 0-24 lo forward, 0-29 reverse km/h
Transmission	Continuously Variable Transmission (CVT) with clutch enclosure	

## Suspension

Front   Rear	Fully independent dual A-Arm with adjustable coils; 200.7 mm of travel Fully independent dual A-Arm with adjustable coils and sway bar; 231.14 mm of travel
--------------	--

## Dimensions / Capacities

Cargo box capacity	454 kg	454 kg
Fuel capacity	42.4 L	42.4 L
Ground clearance	284 mm	284 mm
Payload capacity	680 kg	680 kg
Towing capacity	907 kg	907 kg
Power steering	Yes	Yes