

The Perfect Match

CULTIVATOR

Enhanced Productivity

Highly Durable

Low Maintenance Cost

Superior Quality



Specially designed for
John Deere 5000 series tractors

GREENSYSTEM[™]

TECHNICAL SPECIFICATIONS

| | Standard Duty Rigid Type | | | Heavy Duty Rigid Type | | | Duck Foot Cultivator | | |
|--|---------------------------|--------|--------|----------------------------|--------|--------|--------------------------|--------------|--------|
| | RC1009 | RC1011 | RC1013 | RC1209 | RC1211 | RC1213 | RC1005 | RC1007 | RC1009 |
| Tynes | 9 | 11 | 13 | 9 | 11 | 13 | 5 | 7 | 9 |
| Working Width, (m) | 1.8 | 2.1 | 2.3 | 1.8 | 2.1 | 2.3 | 1.9 | 2.1 | 2.7 |
| Mainframe & Size, (mm) | Square Pipe, 72 x 72 x 5 | | | Welded Angles, 65 x 65 x 8 | | | Square Pipe, 72 x 72 x 5 | | |
| Tine Thickness, (mm) | 22 | | | 32 | | | 32 | | |
| Soil Opener | Shovel Type, 8 mm | | | Shovel Type, 8 mm | | | 432 mm (17') | 356 mm (14') | |
| Size of Tyne Support (mm) | Angle, 65 x 65 x 8 | | | Plate, 174 x 110 x 15 | | | 65 x 8 | | |
| Gap between front & rear tynes, (mm) | 457 | | | 483 | | | 686 | | |
| Depth of Operation (mm) | 100 to 175 | | | 100 to 175 | | | 100 to 175 | | |
| | Standard Duty Spring Type | | | Heavy Duty Spring Type | | | | | |
| | SC1009 | SC1011 | SC1013 | SC1209 | SC1211 | SC1213 | | | |
| Tynes | 9 | 11 | 13 | 9 | 11 | 13 | | | |
| Working Width, (m) | 1.8 | 2.1 | 2.3 | 1.8 | 2.1 | 2.3 | | | |
| Mainframe & Size, (mm) | Channel, 75 x 40 x 5 | | | Channel, 75 x 40 x 5 | | | | | |
| Tine Thickness, (mm) | 19 | | | 25 | | | | | |
| Soil Opener | Shovel Type, 8 mm | | | Shovel Type, 8 mm | | | | | |
| Size of Tyne Support (mm) | 8 mm Flat | | | Angle, 65 x 65 x 6 | | | | | |
| Spring Length, coil dia & no. of turns | 354, 10 mm, 28 turns | | | 354, 10 mm, 28.5 turns | | | | | |
| Depth of Operation (mm) | 100 to 175 | | | 100 to 175 | | | | | |

SALIENT FEATURES

RIGID

- Cat II hitch Geometry with 24" mast height
- Adjustable tyne spacing in heavy duty rigid cultivators
- Superior paint quality
- Prime steel for better durability

SPRING

- Cat II hitch Geometry with 24" mast height
- Heavy duty springs to absorb sudden impact
- Heavy duty forged tines for better durability
- Superior paint quality

Duck Foot

- Cat II hitch Geometry with 24" mast height
- Higher underbody & underframe clearance
- Superior paint quality

CULTIVATOR



John Deere India Private Limited

3rd floor, Tower-15, Cybercity, Magarpatta City,
Hadapsar, Pune - 411013. Maharashtra. | www.JohnDeere.co.in

For more information, please contact our authorised dealer or nearest area office. Sales & Service through John Deere authorized dealers only.



Please note: Improvement in the product is a continuous process. Hence the information given in this brochure is subject to change without prior notice. Accessories shown are not the part of standard equipment.

GREENSYSTEM™