TECHNICAL SPECIFICATION

		2WD	4WD
ENGINE		63 HP (46 kW), 2100 RPM, 3 cylinder, Direct injection, Turbo charged, Inline FIP, coolant cooled with over flow reservoir	
AIR FILTER		Dry type, dual element	
TRANSMISSION	Clutch	Dual	
	Gear Box	12 Forward + 4 Reverse, Collar Shift	
	Speeds	Forward 2.0 - 32.6 kmph Reverse 3.5 - 22.9 kmph	
BRAKES		Self Adjusting, Self Equalising, Hydraulically Actuated, Oil immersed disk brakes	
HYDRAULICS	Maximum Lifting capacity	2000 kgf	
	3 Point linkage	Category II, Automatic depth & draft control (ADDC)	
STEERING		Power Steering , Tilt steering# : tiltable up to 25° with lock latch	
POWER TAKE OFF	Type	Independent , 6 splines	
	RPM	Dual PTO Standard : 540 @ 2100 ERPM Economy : 540 @ 1600 ERPM	
FUEL TANK CAPACITY		68 L	
WHEELS AND TYRES	Front	6.5 x 20 (0.17 x 0.51 m), 8 PR	11.2 x 24 (0.28 x 0.61 m), 8 PR 9.5 x 24 (0.24 x 0.61 m), 8 PR (Optional)
	Rear	16.9 x 30 (0.43 x 0.76 m), 12 PR 16.9 x 28 (0.43 x 0.71 m), 12 PR (Optional)	16.9 x 30 (0.43 x 0.76 m), 12 PR 16.9 x 28 (0.43 x 0.71 m), 12 PR (Optional)
ELECTRICAL SYSTEM		88 Ah, 12 V battery, 40 Amp. Alternator, 2.5 kW starter motor	
DIMENSIONS AND WEIGHT	Total weight	2280 kg	2570 kg
	Wheel base	2050 mm	2050 mm
	Overall length	3515 mm	3585 mm
	Overall width	1870 mm	1910 mm
	Ground clearance	0425 mm	0425 mm
	Turning radius with brakes	3181 mm	3181 mm
OPTIONAL ACCESSORIES		• Ballast Weight • Canopy • Canopy Holder • Draw Bar • Wagon Hitch	

#Optional feature.

5405 GearPro™ 63 HP 46 kW

FACTORY FITTED OPTIONS

- Adjustable front axle
- Heavy duty front axle
- Reverse PTO - (Std + Reverse)
- Single PTO
- EQRL system
- Synchromesh Transmission - (TSS)
- Selective Control Valve - (SCV)

ADDITIONAL FEATURES

- Single piece hood with gas strut mechanism
- Side bar, exhaust muffler guard & finger guard
- Water bottle holder
- Mobile charging point with holder
- Sway bar
- Seat with arm rest

Note: All the options / features may not be available in a single variant.

5405 02 0921 ENG

John Deere Genuine Parts

I Economical I Reliable I
I Easily available I

John Deere India Private Limited
3rd floor, Tower-15, Cybercity, Magarpatta City, Hadapsar,
Pune - 411013. Maharashtra. www.JohnDeere.co.in

For more information, please contact our authorised dealer or nearest area office.

- Tractors • Implements
- Harvesters • Finance

JOHN DEERE

Please note: Improvement in the product is a continuous process. Hence the information given in this brochure is subject to change without prior notice. Accessories shown are not the part of standard equipment.

Zindagi ka Best Decision!™

JOHN DEERE

DUM HAI !

The 4 Range Tractor

5405 GearPro™ 63 HP 46 kW

12F+4R

John Deere Promise
5 YEARS WARRANTY*
— TECHNOLOGY LEADERSHIP —

*Conditions apply

63 HP

5405 GearPro™ 63 HP 46 kW

12F+4R

Mobile Charging Point with Holder
Stay connected anytime

Power Brakes
Self adjusting, self equalising, hydraulically actuated, Oil immersed disc brakes

Hood Lock
Totally secure

Planetary Gear with Straight Axle
Low noise, less vibration, highly durable

Modern dashboard, with Digital Hour Meter and Combo-switch

Dry type air filter
99.9% clean air ensures longer engine life

Power Steering with Tilt Steering
Work hard.
Drive smooth.

Oil Jet for Piston Cooling

John Deere 3029H engine
Powerful and fuel efficient