HP2025 - Hydraulic Power Unit, 25 HP - U.S.

Equipment for Base Machine

Function: Hydraulic Power Unit
Pressure: 2700 psi
Flow: 16 gpm
Reservoir Capacity: 15 gal.
System Capacity: 17 gal.
System Features: Pressure relieve valve, filter, temperature and oil level gauge, and thermal protection switch
Hoses, Tips, and Brackets included
Tractor RPM: 540 RPM
PTO Manufacturer: Comer

Parking Stand: Standard
Hitch Category: Category I
Quick Hitch Compatibility:
iMatch Compatible
Approximate Set-Up Time: 120 Minutes

Code	Attachment Identifier	Description	List Price Suggested USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1601XF		HP2025 - Hydraulic Power Unit, 25 HP - U.S. *Must be used with SB2164 Snowblower and SW2160 Rotary Broom. Can be used with SW2172 Rotary Broom and BL2130 Debris Blower. Includes rear tractor wiring harness. Front implement wiring harness is not included in base.*	7,785.00
		OIL COOLER	
2000		Oil Cooler for HP2025 and HP2134 Hydraulic Power Units *Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.*	In Base Price
2095		Less Oil Cooler	-1,989.00
		WIRING HARNESS	
9040		Additional Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors *Includes complete wiring harness from battery to switch in the console.*	110.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous	
	5RDF0036	Oil Cooler for HP2025 and HP2134 Hydraulic Power Units *Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.*	2,063.60
	5RDF0038	Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors *Includes complete wiring harness from battery to switch in the console.*	114.40
	5RDF0078	Wiring Harness for HP2025 and HP2134 Hydraulic Power Units to control Loader Mounted Attachment *Includes complete wiring harness from switch in the console to 3 cavities connectors for front implements.*	159.51

HP2025 - Hydraulic Power Unit, 25 HP - U.S.
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

HP2134 - Hydraulic Power Unit, 34 HP - U.S.

Equipment for Base Machine

Function: Hydraulic Power Unit
Pressure: 2700 psi
Flow: 16 gpm
Reservoir Capacity: 15 gal.
System Capacity: 17 gal.
System Features: Pressure relieve valve, filter, temperature and oil level gauge, and thermal protection switch
Hoses, Tips, and Brackets included
Tractor RPM: 540 RPM
PTO Manufacturer: Comer

Parking Stand: Standard
Hitch Category: Category I
Quick Hitch Compatibility:
iMatch Compatible
Approximate Set-Up Time: 120 Minutes

Code	Attachment Identifier	Description	List Price Suggested USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
1611XF		HP2134 - Hydraulic Power Unit, 34 HP - U.S. *Must be used with SB2176 Snowblower and SW2184 Rotary Broom. Can be used with SW2172 Rotary Broom and BL2130 Debris Blower. Includes rear tractor wiring harness. Front implement wiring harness is not included in base.*	7,919.00
		OIL COOLER	
2000		Oil Cooler for HP2025 and HP2134 Hydraulic Power Units *Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.*	In Base Price
2095		Less Oil Cooler	-1,989.00
		WIRING HARNESS	
9040		Additional Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors *Includes complete wiring harness from battery to switch in the console.*	110.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous	
	5RDF0036	Oil Cooler for HP2025 and HP2134 Hydraulic Power Units *Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.*	2,063.60
	5RDF0038	Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors *Includes complete wiring harness from battery to switch in the console.*	114.40
	5RDF0078	Wiring Harness for HP2025 and HP2134 Hydraulic Power Units to control Loader Mounted Attachment *Includes complete wiring harness from switch in the console to 3 cavities connectors for front implements.*	159.51

HP2134 - Hydraulic Power Unit, 34 HP - U.S.
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

AS10H - 6 Ft. Standard Duty Snow Push with Fixed Edge fits Current 300 and 400 Series Carrier

Equipment for Base Machine

Cutting Width: 73.75 In.
Loader Series:
 300 and 400 Only (Not 500 Series)
Dimensions:
 W74.5 In. x H30.75 In. x D34 In.
Capacity:
 3.5 Cubic Foot
Operational Weight: 440 lbs.

Shipping Weight: 490 lbs.

Code	Attachment Identifier	Description	List Price Suggested USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
2191XF		AS10H - 6 Ft. Standard Duty Snow Push with Fixed Edge fits Current 300 and 400 Series Carrier *Fixed cutting edge is rubber.* *Reference Frontier Loader Attachment Compatibility Chart for specific loader compatibility.*	2,254.00
		OPERATOR'S MANUAL AND DECAL KIT	
9200		French Operator's Manual and Decal Kit for AS10, AS11 Series Snow Push	No Added Cost
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous	
	5MP43052	FRENCH OM/DECAL-LDR ATTACHMENTS	0.00
	5MP76312XES	French Operator's Manual and Decal Kit	See Parts

AS10H - 6 Ft. Standard Duty Snow Push with Fixed Edge fits Current 300 and 400 Series Carrier

Continued

THIS PAGE INTENTIONALLY LEFT BLANK

AS10H - 7 Ft. Standard Duty Snow Push with Fixed Edge fits Current 300 and 400 Series Carrier

Equipment for Base Machine

Cutting Width: 85.75 In.
Loader Series:
 300 and 400 Only (Not 500 Series)
Dimensions:
 W86.25 In. x H30.75 In. x D34 In.
Capacity:
 4 Cubic Foot
Operational Weight: 477 lbs.

Shipping Weight: 527 lbs.

Code	Attachment Identifier	Description	List Price Suggested USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
2192XF		AS10H - 7 Ft. Standard Duty Snow Push with Fixed Edge fits Current 300 and 400 Series Carrier *Fixed cutting edge is rubber.* *Reference Frontier Loader Attachment Compatibility Chart for specific loader compatibility.*	2,497.00
		OPERATOR'S MANUAL AND DECAL KIT	
9200		French Operator's Manual and Decal Kit for AS10, AS11 Series Snow Push	No Added Cost
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous	
	5MP43052	FRENCH OM/DECAL-LDR ATTACHMENTS	0.00
	5MP76312XES	French Operator's Manual and Decal Kit	See Parts

AS10H - 7 Ft. Standard Duty Snow Push with Fixed Edge fits Current 300 and 400 Series Carrier

Continued

THIS PAGE INTENTIONALLY LEFT BLANK

AS10H - 8 Ft. Standard Duty Snow Push with Fixed Edge fits Current 300 and 400 Series Carrier

Equipment for Base Machine

Cutting Width: 85.75 In.
Loader Series:
 300 and 400 Only (Not 500 Series)
Dimensions:
 W86.25 In. x H30.75 In. x D34 In.
Capacity:
 4 Cubic Foot
Operational Weight: 477 lbs.

Shipping Weight: 527 lbs.

Code	Attachment Identifier	Description	List Price Suggested USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
2193XF		AS10H - 8 Ft. Standard Duty Snow Push with Fixed Edge fits Current 300 and 400 Series Carrier *Fixed cutting edge is rubber.* *Reference Frontier Loader Attachment Compatibility Chart for specific loader compatibility.*	2,761.00
		OPERATOR'S MANUAL AND DECAL KIT	
9200		French Operator's Manual and Decal Kit for AS10, AS11 Series Snow Push	No Added Cost
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous	
	5MP43052	FRENCH OM/DECAL-LDR ATTACHMENTS	0.00
	5MP76312XES	French Operator's Manual and Decal Kit	See Parts

AS10H - 8 Ft. Standard Duty Snow Push with Fixed Edge fits Current 300 and 400 Series Carrier

Continued

THIS PAGE INTENTIONALLY LEFT BLANK

AS11E - 8 Ft. Medium Duty Snow Push with Trip Edge fits Current 300, 400, and 500 Series Carrier

Equipment for Base Machine

```
Cutting Width: 98 In.
Loader Series:
 300, 400, and 500
Dimensions:
 W98.38 In. x H39.8 In. x D41.5 In.
Capacity:
 7 Cubic Foot
Optional Bolt-on Pull Back Kit Weight:
 163 lbs.
Operational Weight: 900 lbs.
Shipping Weight: 950 lbs.
```

Code	Attachment Identifier	Description	List Price Suggested USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
2201XF		AS11E - 8 Ft. Medium Duty Snow Push with Trip Edge fits Current 300, 400, and 500 Series Carrier *Reference Frontier Loader Attachment Compatibility Chart for specific loader compatibility.*	3,994.00
		OPERATOR'S MANUAL AND DECAL KIT	
9200		French Operator's Manual and Decal Kit for AS10, AS11 Series Snow Push	No Added Cost
		BACK DRAG ATTACHMENT	
9000		Back Drag Attachment *For 8 Ft. Model*	803.00
		RUBBER EDGE KIT	
9010		Rubber Edge Kit *8 Ft. Back Drag attachment required.*	429.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous	
	5FP10730	Back Drag Attachment for 8 Ft. AS11E (Less Rubber Edge)	1,132.08
	5MP43052	FRENCH OM/DECAL-LDR ATTACHMENTS	0.00
	5MP76312XES	French Operator's Manual and Decal Kit	See Parts
	5FP10733	Rubber Edge Kit for 8 Ft. AS11E *5FP10730 - 8 Ft. Back Drag attachment required.*	560.57

AS11E - 8 Ft. Medium Duty Snow Push with Trip Edge fits Current 300, 400, and 500 Series Carrier

Continued

THIS PAGE INTENTIONALLY LEFT BLANK

AS11E - 9 Ft. Medium Duty Snow Push with Trip Edge fits Current 300, 400, and 500 Series Carrier

Equipment for Base Machine

```
Cutting Width: 110 In.
Loader Series:
 300, 400, and 500
Dimensions:
 W110.38 In. x H39.8 In. x D41.5 In.
Capacity:
 7.8 Cubic Foot
Optional Bolt-on Pull Back Kit Weight:
 175 lbs.
```

```
Operational Weight: 943 lbs.
Shipping Weight: 993 lbs.
```

Code	Attachment Identifier	Description	List Price Suggested USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
2202XF		AS11E - 9 Ft. Medium Duty Snow Push with Trip Edge fits Current 300, 400, and 500 Series Carrier *Reference Frontier Loader Attachment Compatibility Chart for specific loader compatibility.*	4,394.00
		OPERATOR'S MANUAL AND DECAL KIT	
9200		French Operator's Manual and Decal Kit for AS10, AS11 Series Snow Push	No Added Cost
		BACK DRAG ATTACHMENT	
9000		Back Drag Attachment *For 9 Ft. Model*	834.00
		RUBBER EDGE KIT	
9010		Rubber Edge Kit *9 Ft. Back Drag attachment required.*	478.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous	
	5FP10731	Back Drag Attachment for 9 Ft. AS11E (Less Rubber Edge)	1,368.78
	5MP43052	FRENCH OM/DECAL-LDR ATTACHMENTS	0.00
	5MP76312XES	French Operator's Manual and Decal Kit	See Parts
	5FP10734	Rubber Edge Kit for 9 Ft. AS11E *5FP10731 - 9 Ft. Back Drag attachment required.*	496.11

AS11E - 9 Ft. Medium Duty Snow Push with Trip Edge fits Current 300, 400, and 500 Series Carrier

Continued

THIS PAGE INTENTIONALLY LEFT BLANK

AS11E - 10 Ft. Medium Duty Snow Push with Trip Edge fits Current 300, 400, and 500 Series Carrier

Equipment for Base Machine

```
Cutting Width: 119.5 In.
Loader Series:
 300, 400, and 500
Dimensions:
 W110.875 In. x H39.8 In. x D41.5 In.
Capacity:
 8.5 Cubic Foot
Optional Bolt-on Pull Back Kit Weight:
 185 lbs.
```

```
Operational Weight: 980 lbs.
Shipping Weight: 1030 lbs.
```

Code	Attachment Identifier	Description	List Price Suggested USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
2203XF		AS11E - 10 Ft. Medium Duty Snow Push with Trip Edge fits Current 300, 400, and 500 Series Carrier *Reference Frontier Loader Attachment Compatibility Chart for specific loader compatibility.*	4,783.00
		OPERATOR'S MANUAL AND DECAL KIT	
9200		French Operator's Manual and Decal Kit for AS10, AS11 Series Snow Push	No Added Cost
		BACK DRAG ATTACHMENT	
9000		Back Drag Attachment *For 10 Ft. Model*	875.00
		RUBBER EDGE KIT	
9010		Rubber Edge Kit *10 Ft. Back Drag attachment required.*	524.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous	
	5FP10732	Back Drag Attachment for 10 Ft. AS11E (Less Rubber Edge)	907.51
	5MP43052	FRENCH OM/DECAL-LDR ATTACHMENTS	0.00
	5MP76312XES	French Operator's Manual and Decal Kit	See Parts
	5FP10735	Rubber Edge Kit for 10 Ft. AS11E *5FP10732 - 10 Ft. Back Drag attachment required.*	682.10

AS11E - 10 Ft. Medium Duty Snow Push with Trip Edge fits Current 300, 400, and 500 Series Carrier

Continued

THIS PAGE INTENTIONALLY LEFT BLANK

AS10F - 48 in. Snow Push

Equipment for Base Machine

Cutting Width: 48 In.
Base unit includes: Steel cutting edge, steel skid shoes
Loader Compatibility: D120/H120/120R
Dimensions: 19.3"Hx21.6"Dx50.6"W
Capacity: 11.6 cu ft
Operational Weight: 142 lbs.

Shipping Weight: lbs.

Code	Attachment Identifier	Description	List Price Suggested USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
2411XF		AS10F - 48 in. Snow Push	805.00
		DESTINATION AND LANGUAGE	
0202		United States	In Base Price
0184		Canada	No Added Cost
		OPERATOR'S MANUAL AND DECAL KIT	
0409		English Operator's Manual and Decal Kit	In Base Price
0437		Spanish Operator's Manual and Decal Kit	No Added Cost
0413		French Operator's Manual and Decal Kit	No Added Cost
		BACK DRAG ATTACHMENT	
9205		Back Drag Kit with Steel Edge - 48 in.	178.00
9206		Back Drag Kit with Rubber Edge - 48 in.	215.00
		RUBBER EDGE KIT	
9843		Rubber Edge Kit - 48 in.	148.00
		SKID SHOES	
9863		Poly Skid Shoes Kit (2 included)	230.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous	
	5FP110414804	AS10F (48 in.) Back Drag Kit with Rubber Edge	223.31
	5FP110404804	AS10F (48 in.) Back Drag Kit with Steel Edge	184.80
	5FP110434804	AS10F (48 in.) Rubber Edge Kit	154.00
	5FP281104204	AS10F Poly Skid Shoe Kit	238.71

AS10F - 48 in. Snow Push

Continued

Code	Attachment Identifier	Description	List Price Suggested USD ($)
		ATTACHMENTS FOR FIELD CONVERSION ...Continued...	
	5MP43052	FRENCH OM/DECAL-LDR ATTACHMENTS	0.00
	5MP76312XES	French Operator's Manual and Decal Kit	See Parts

AS10F - 60 in. Snow Push

Equipment for Base Machine

Cutting Width: 60 In.
Base unit includes: Steel cutting edge, steel skid shoes
Loader Series:
200X/200CX/H130/220R/D160/305/H160/H165
Dimensions: 19.3"Hx21.6"Dx62.6"W
Capacity: 14.5 cu ft
Operational Weight: 160 lbs.

Shipping Weight: lbs.

Code	Attachment Identifier	Description	List Price Suggested USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
2412XF		AS10F - 60 in. Snow Push	858.00
		DESTINATION AND LANGUAGE	
0202		United States	In Base Price
0184		Canada	No Added Cost
		OPERATOR'S MANUAL AND DECAL KIT	
0409		English Operator's Manual and Decal Kit	In Base Price
0437		Spanish Operator's Manual and Decal Kit	No Added Cost
0413		French Operator's Manual and Decal Kit	No Added Cost
		BACK DRAG ATTACHMENT	
9207		Back Drag Kit with Steel Edge - 60 in.	186.00
9208		Back Drag Kit with Rubber Edge - 60 in.	234.00
		RUBBER EDGE KIT	
9844		Rubber Edge Kit - 60 in.	167.00
		SKID SHOES	
9863		Poly Skid Shoes Kit (2 included)	230.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous	
	5FP110416004	AS10F (60 in.) Back Drag Kit with Rubber Edge	243.11
	5FP110406004	AS10F (60 in.) Back Drag Kit with Steel Edge	192.51
	5FP110436004	AS10F (60 in.) Rubber Edge Kit	173.80
	5FP281104204	AS10F Poly Skid Shoe Kit	238.71

AS10F - 60 in. Snow Push

Continued

Code	Attachment Identifier	Description	List Price Suggested USD ($)
		ATTACHMENTS FOR FIELD CONVERSION ...Continued...	
	5MP43052	FRENCH OM/DECAL-LDR ATTACHMENTS	0.00
	5MP76312XES	French Operator's Manual and Decal Kit	See Parts

SB1148 - 48 In. 3-Point Medium Snowblower - U.S.

Equipment for Base Machine

Function: Snow Removal
Working Width: 48 In.
Transport Width: 48.5 In.
Working Height: 24 5/8 In.
Length: 38.5 In.
Single/Dual Auger: Single
Auger Diameter: 15 In.
Auger Flighting Thickness: 1/4 In.
Impeller Diameter: 20 In.
Impeller Width: 6 In.
Impeller Shaft Diameter: 1 In.
Number of Impeller Blades: 4
Roller Chain: 50
Drive Sprocket: 17 Teeth
Driven Sprocket: 36 Teeth
Chain Idler: Manual Adjustment
Gear Box Manufacturer: Comer
Gear Box Description: Model L-25J
Gear Box HP (Through Gears): 11
Gear Box HP (Straight Through): 30
Tractor RPM: 540 RPM
Impeller RPM: 540 RPM
Auger RPM: 170 RPM
PTO Manufacturer: Comer
PTO Description: 20
PTO Clutch Setting (Number): 900
Shearbolt Bolt Size and Grade (PTO):
M6 8.8 Metric
Shearbolt Bolt Size and Grade (Auger):
1/4 In. 5 SAE
Skid Shoe: Adjustable
Skid Shoe Material: Steel
End Plate Thickness: 3/16 In.
Back Plate Thickness: 12 Gauge
Impeller Housing Thickness: 12 Gauge
Impeller Blade Thickness: 3/16 In.
Side Panel Bottom Thickness: 3/16 In.
Cutting Edge: Welded
Cutting Edge Dimension: 3/8 In. x 2 In.
Chute Diameter: 8 In.
Chute Base: Standard
Chute Rotation: 215 Degrees
Parking Stand: Standard
Hitch Category: Category I
Quick Hitch Compatibility:
iMatch Compatible
HP Requirements (Minimum-Maximum HP):
16-35 HP
Operating Weight: 375 lbs.
Shipping Weight: 415 lbs.
Approximate Set-up Time: 60 Minutes
Chute Deflector Adjustment (Standard):
Manual
Chute Deflector Adjustment Options:
Hydraulic Cylinder (2 In. x 5 In.)
Including Brackets, Hoses, and Tips
Electric Actuator (5 In.)
Including Hardware, Switch, and Electric Cable
Chute Rotation (Standard): Must Choose
an Option, Manual or Hydraulic
Chute Rotation Options:
Manual, Worm Gear with Crank
Hydraulic: Motor,
Including Flow Restrictors, Hoses, and Tips
Chute: Two Part ONLY
Dual Auger: N/A
Rotating Drum (Including Hoses and Tips):
N/A

Code	Attachment Identifier	Description	List Price Suggested USD ($)

Select One Code From Each Required Category

BASE MACHINE

3801XF	SB1148 - 48 In. 3-Point Medium Snowblower - U.S.	3,077.00

CHUTES

1000	Manual Chute Rotation Kit	In Base Price
1010	Hydraulic Cylinder Kit for Chute Rotation	441.00

HYDRAULIC CYLINDER KIT

9000	Hydraulic Cylinder Kit for Chute Deflector	355.00
9010	Electric Kit for Chute Deflector *Includes 5 In. actuator.*	1,030.00

ATTACHMENTS FOR FIELD CONVERSION

SB1148 - 48 In. 3-Point Medium Snowblower - U.S.

Continued

Code	Attachment Identifier	Description	List Price Suggested USD ($)
		ATTACHMENTS FOR FIELD CONVERSION ...Continued...	
		Miscellaneous	
	5RDF0049A	Electric Kit for Chute Deflector - Includes 5 In. Actuator *For snowblowers with serial number 1XFSB11XB0111288 and above.*	1,069.20
	5RDF0048A	Hydraulic Cylinder Kit for Chute Deflector *For snowblowers with serial number 1XFSB11XB0111288 and above.*	368.51
	5RDF0019	Hydraulic Cylinder Kit for Chute Deflector *For snowblowers with serial number 1XFSB11XB0111287 and below.*	327.80
	5RDF0017	Hydraulic Cylinder Kit for Chute Rotation *For snowblowers with serial number 1XFSB11XB0111287 and below.*	589.60
	5RDF0047	Hydraulic Cylinder Kit for Chute Rotation *For snowblowers with serial number 1XFSB11XB0111288 and above.*	685.31
	BLV11199	John Deere Quik-Knect Driveline Yoke Bundle *Tractor Receiver Part number: BLV10953At least one tractor receiver bundle is needed per tractor. This bundle is removable and can be used on various tractors within the compatibility.One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).*	275.00
	5RDF0016	Manual Chute Rotation Kit (SB11) *For snowblowers with serial numbers 1XFSB11XB0111287 and below.*	182.60
	5RDF0046	Manual Chute Rotation Kit (SB11) *For snowblowers with serial number 1XFSB11XB0111288 and above.*	182.60

SB1154 - 54 In. 3-Point Medium Snowblower - U.S.

Equipment for Base Machine

Function: Snow Removal
Working Width: 54 In.
Transport Width: 54.5 In.
Working Height: 26 In.
Length: 41 In.
Single/Dual Auger: Single
Auger Diameter: 15 In.
Auger Flighting Thickness: 5/16 In.
Impeller Diameter: 24 In.
Impeller Width: 7 In.
Impeller Shaft Diameter: 1-3/8 In.
Number of Impeller Blades: 4
Roller Chain: 60
Drive Sprocket: 10 Teeth
Driven Sprocket: 32 Teeth
Chain Idler: Manual Adjustment
Gear Box Manufacturer: Comer
Gear Box Description: Model T-281A
Gear Box HP (Through Gears): 23 HP
Gear Box HP (Straight Through): 60 HP
Tractor RPM: 540 RPM
Impeller RPM: 540 RPM
Auger RPM: 170 RPM
PTO Manufacturer: Comer
PTO Description: 40
PTO Clutch Setting (Number): 1300
Shearbolt Bolt Size and Grade (PTO):
M10 8.8 Metric
Shearbolt Bolt Size and Grade (Auger):
5/16 In. 5 SAE
Skid Shoe: Adjustable
Skid Shoe Material: Steel
End Plate Thickness: 3/16 In.
Back Plate Thickness: 12 Gauge
Impeller Housing Thickness: 12 Gauge
Impeller Blade Thickness: 3/16 In.
Side Panel Bottom Thickness: 3/16 In.
Cutting Edge: Welded
Cutting Edge Dimension: 3/8 In. x 2 In.
Chute Diameter: 8 In.
Chute Base: Standard
Chute Rotation: 215 Degrees
Parking Stand: Standard
Hitch Category: Category I
Quick Hitch Compatibility:
iMatch Compatible
HP Requirements (Minimum-Maximum HP):
16-35 HP
Operating Weight: 455 lbs.
Shipping Weight: 495 lbs.
Approximate Set-up Time: 60 Minutes
Chute Deflector Adjustment (Standard):
Manual
Chute Deflector Adjustment Options:
Hydraulic Cylinder (2 In. x 5 In.)
Including Brackets, Hoses, and Tips
Electric Actuator (5 In.)
Including Hardware, Switch, and Electric Cable
Chute Rotation (Standard): Must Choose an
Option - Manual or Hydraulic
Chute Rotation Options:
Manual, Worm Gear with Crank
Hydraulic: Motor
Including Flow Restrictors, Hoses, and Tips
Chute: Two Part ONLY
Dual Auger: MN/A
Rotating Drum (Including Hoses and Tips):
N/A

Code	Attachment Identifier	Description	List Price Suggested USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
3802XF		SB1154 - 54 In. 3-Point Medium Snowblower - U.S.	3,419.00
		CHUTES	
1000		Manual Chute Rotation Kit	In Base Price
1010		Hydraulic Cylinder Kit for Chute Rotation	441.00
		HYDRAULIC CYLINDER KIT	
9000		Hydraulic Cylinder Kit for Chute Deflector	355.00
9010		Electric Kit for Chute Deflector *Includes 5 In. actuator.*	1,030.00
		ATTACHMENTS FOR FIELD CONVERSION	

SB1154 - 54 In. 3-Point Medium Snowblower - U.S.

Continued

Code	Attachment Identifier	Description	List Price Suggested USD ($)
		ATTACHMENTS FOR FIELD CONVERSION ...Continued...	
		Miscellaneous	
	5RDF0020	Electric Kit for Chute Deflector - Includes 4 In. Actuator *For snowblowers with serial number 1XFSB11XAB0111287 and below.*	1,085.71
	5RDF0049A	Electric Kit for Chute Deflector - Includes 5 In. Actuator *For snowblowers with serial number 1XFSB11XB0111288 and above.*	1,069.20
	5RDF0048A	Hydraulic Cylinder Kit for Chute Deflector *For snowblowers with serial number 1XFSB11XB0111288 and above.*	368.51
	5RDF0019	Hydraulic Cylinder Kit for Chute Deflector *For snowblowers with serial number 1XFSB11XB0111287 and below.*	327.80
	5RDF0017	Hydraulic Cylinder Kit for Chute Rotation *For snowblowers with serial number 1XFSB11XB0111287 and below.*	589.60
	5RDF0047	Hydraulic Cylinder Kit for Chute Rotation *For snowblowers with serial number 1XFSB11XB0111288 and above.*	685.31
	BLV11178	John Deere Quik-Knect Driveline Yoke Bundle *Tractor Receiver Part number: BLV10953At least one tractor receiver bundle is needed per tractor. This bundle is removable and can be used on various tractors within the compatibility.One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).*	275.00
	5RDF0016	Manual Chute Rotation Kit (SB11) *For snowblowers with serial numbers 1XFSB11XB0111287 and below.*	182.60
	5RDF0046	Manual Chute Rotation Kit (SB11) *For snowblowers with serial number 1XFSB11XB0111288 and above.*	182.60

SB1164 - 64 In. 3-Point Medium Snowblower - U.S.

Equipment for Base Machine

Function: Snow Removal
Working Width: 64 In.
Transport Width: 64.5 In.
Working Height: 26 In.
Length: 41 In.
Single/Dual Auger: Single
Auger Diameter: 15 In.
Auger Flighting Thickness: 5/16 In.
Impeller Diameter: 24 In.
Impeller Width: 7 In.
Impeller Shaft Diameter: 1-3/8 In.
Number of Impeller Blades: 4
Roller Chain: 60
Drive Sprocket: 10 Teeth
Driven Sprocket: 32 Teeth
Chain Idler: Manual Adjustment
Gear Box Manufacturer: Comer
Gear Box Description: Model T-281A
Gear Box HP (Through Gears): 23 HP
Gear Box HP (Straight Through): 60 HP
Tractor RPM: 540 RPM
Impeller RPM: 540 RPM
Auger RPM: 170 RPM
PTO Manufacturer: Comer
PTO Description: 40
PTO Clutch Setting (Number): 1300
Shearbolt Bolt Size and Grade (PTO):
M10 8.8 Metric
Shearbolt Bolt Size and Grade (Auger):
5/16 In. 5 SAE
Skid Shoe: Adjustable
Skid Shoe Material: Steel
End Plate Thickness: 3/16 In.
Back Plate Thickness: 12 Gauge
Impeller Housing Thickness: 12 Gauge
Impeller Blade Thickness: 3/16 In.
Side Panel Bottom Thickness: 3/16 In.
Cutting Edge: Welded
Cutting Edge Dimension: 3/8 In. x 2 In.
Chute Diameter: 8 In.
Chute Base: Standard
Chute Rotation: 215 Degrees
Parking Stand: Standard
Hitch Category: Category I
Quick Hitch Compatibility:
iMatch Compatible
HP Requirements (Minimum-Maximum HP):
20-50 HP
Operating Weight: 479 lbs.
Shipping Weight: 519 lbs.
Approximate Set-Up Time: 60 Minutes
Chute Deflector Adjustment (Standard):
Manual
Chute Deflector Adjustment Options:
Hydraulic Cylinder (2 In. x 5 In.)
Including Brackets, Hoses, and Tips
Electric Actuator (5 In.)
Including Hardware, Switch, and Electric Cable
Chute Rotation (Standard): Must Choose an
Option - Manual or Hydraulic
Chute Rotation Options:
Manual, Worm Gear with Crank
Hydraulic: Motor
Including Flow Restrictors, Hoses, and Tips
Chute: Two Part ONLY
Dual Auger: N/A
Rotating Drum (Including Hoses and Tips):
N/A

Code	Attachment Identifier	Description	List Price Suggested USD ($)

Select One Code From Each Required Category

BASE MACHINE

3803XF	SB1164 - 64 In. 3-Point Medium Snowblower - U.S.	3,521.00

CHUTES

1000	Manual Chute Rotation Kit	In Base Price
1010	Hydraulic Cylinder Kit for Chute Rotation	441.00

HYDRAULIC CYLINDER KIT

9000	Hydraulic Cylinder Kit for Chute Deflector	355.00
9010	Electric Kit for Chute Deflector *Includes 5 In. actuator.*	1,030.00

ATTACHMENTS FOR FIELD CONVERSION

SB1164 - 64 In. 3-Point Medium Snowblower - U.S.

Continued

Code	Attachment Identifier	Description	List Price Suggested USD ($)
		ATTACHMENTS FOR FIELD CONVERSION ...Continued...	
		Miscellaneous	
	5RDF0020	Electric Kit for Chute Deflector - Includes 4 In. Actuator *For snowblowers with serial number 1XFSB11XAB0111287 and below.*	1,085.71
	5RDF0049A	Electric Kit for Chute Deflector - Includes 5 In. Actuator *For snowblowers with serial number 1XFSB11XB0111288 and above.*	1,069.20
	5RDF0048A	Hydraulic Cylinder Kit for Chute Deflector *For snowblowers with serial number 1XFSB11XB0111288 and above.*	368.51
	5RDF0019	Hydraulic Cylinder Kit for Chute Deflector *For snowblowers with serial number 1XFSB11XB0111287 and below.*	327.80
	5RDF0017	Hydraulic Cylinder Kit for Chute Rotation *For snowblowers with serial number 1XFSB11XB0111287 and below.*	589.60
	5RDF0047	Hydraulic Cylinder Kit for Chute Rotation *For snowblowers with serial number 1XFSB11XB0111288 and above.*	685.31
	BLV11178	John Deere Quik-Knect Driveline Yoke Bundle *Tractor Receiver Part number: BLV10953At least one tractor receiver bundle is needed per tractor. This bundle is removable and can be used on various tractors within the compatibility.One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).*	275.00
	5RDF0016	Manual Chute Rotation Kit (SB11) *For snowblowers with serial numbers 1XFSB11XB0111287 and below.*	182.60
	5RDF0046	Manual Chute Rotation Kit (SB11) *For snowblowers with serial number 1XFSB11XB0111288 and above.*	182.60

SB1174 - 74 In. 3-Point Medium Snowblower - U.S.

Equipment for Base Machine

Function: Snow Removal
Working Width: 74 In.
Transport Width: 74.5 In.
Working Height: 26 In.
Length: 47.5 In.
Single/Dual Auger: Single
Auger Diameter: 15 In.
Auger Flighting Thickness: 5/16 In.
Impeller Diameter: 24 In.
Impeller Width: 9 In.
Impeller Shaft Diameter: 1-3/8 In.
Number of Impeller Blades: 4
Roller Chain: 60
Drive Sprocket: 10 Teeth
Driven Sprocket: 32 Teeth
Chain Idler: Manual Adjustment
Gear Box Manufacturer: Comer
Gear Box Description: Model T-281A
Gear Box HP (Through Gears): 23 HP
Gear Box HP (Straight Through): 60 HP
Tractor RPM: 540 RPM
Impeller RPM: 540 RPM
Auger RPM: 170 RPM
PTO Manufacturer: Comer
PTO Description: 50
PTO Clutch Setting (Number): 1700
Shearbolt Bolt Size and Grade (PTO):
M10 8.8 Metric
Shearbolt Bolt Size and Grade (Auger):
5/16 In. 5 SAE
Skid Shoe: Adjustable
Skid Shoe Material: Steel
End Plate Thickness: 3/16 In.
Back Plate Thickness: 11 Gauge
Impeller Housing Thickness: 11 Gauge
Impeller Blade Thickness: 1/4 In.
Side Panel Bottom Thickness: 3/16 In.
Cutting Edge: Welded
Cutting Edge Dimension: 3/8 In. x 2 In.
Chute Diameter: 12 In.
Chute Base: Standard
Chute Rotation: 215 Degrees
Parking Stand: Standard
Hitch Category: Category I
Quick Hitch Compatibility:
iMatch Compatible
HP Requirements (Minimum-Maximum HP):
20-50 HP
Operating Weight: 590 lbs.
Shipping Weight: 635 lbs.
Approximate Set-Up Time: 60 Minutes
Chute Deflector Adjustment (Standard):
Manual
Chute Deflector Adjustment Options:
Hydraulic Cylinder (2 In. x 5 In.)
Including Brackets, Hoses and Tips
Electric Actuator (8 In.)
Including Hardware, Switch, and Electric Cable
Chute Rotation (Standard): Must Choose an
Option - Manual or Hydraulic
Manual, Worm Gear with Crank
Hydraulic: Motor
Including Flow Restrictor, Hoses, and Tips
Chute: Two Part ONLY
Dual Auger: N/A
Rotating Drum (Including Hoses and Tips):
N/A

Code	Attachment Identifier	Description	List Price Suggested USD ($)

Select One Code From Each Required Category

BASE MACHINE

3804XF	SB1174 - 74 In. 3-Point Medium Snowblower - U.S.	4,436.00

CHUTES

1000	Manual Chute Rotation Kit	In Base Price
1010	Hydraulic Cylinder Kit for Chute Rotation	441.00

HYDRAULIC CYLINDER KIT

9000	Hydraulic Cylinder Kit for Chute Deflector	355.00
9010	Electric Kit for Chute Deflector *Includes 8 In. actuator.*	1,030.00

ATTACHMENTS FOR FIELD CONVERSION

SB1174 - 74 In. 3-Point Medium Snowblower - U.S.

Continued

Code	Attachment Identifier	Description	List Price Suggested USD ($)
		ATTACHMENTS FOR FIELD CONVERSION ...Continued...	
		Miscellaneous	
	5RDF0021	Electric Kit for Chute Deflector - Includes 8 In. Actuator	1,069.20
	5RDF0048A	Hydraulic Cylinder Kit for Chute Deflector *For snowblowers with serial number 1XFSB11XB0111288 and above.*	368.51
	5RDF0071	Hydraulic Cylinder Kit for Chute Deflector	359.89
	5RDF0018	Hydraulic Cylinder Kit for Chute Rotation *For snowblowers with serial numbers 1XFSB11XB0111287 and below.*	767.80
	5RDF0047	Hydraulic Cylinder Kit for Chute Rotation *For snowblowers with serial number 1XFSB11XB0111288 and above.*	685.31
	BLV11178	John Deere Quik-Knect Driveline Yoke Bundle *Tractor Receiver Part number: BLV10953At least one tractor receiver bundle is needed per tractor. This bundle is removable and can be used on various tractors within the compatibility.One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).*	275.00
	5RDF0016	Manual Chute Rotation Kit (SB11) *For snowblowers with serial numbers 1XFSB11XB0111287 and below.*	182.60
	5RDF0046	Manual Chute Rotation Kit (SB11) *For snowblowers with serial number 1XFSB11XB0111288 and above.*	182.60

SB1184 - 84 In. 3-Point Medium Snowblower - U.S.

Equipment for Base Machine

Function: Snow Removal
Working Width: 84 In.
Transport Width: 85.5 In.
Working Height: 34 In.
Length: 55.5 In.
Single/Dual Auger: Single
Auger Diameter: 20 In.
Auger Flighting Thickness: 3/8 In.
Impeller Diameter: 27-1/2 In.
Impeller Width: 10.5 In.
Impeller Shaft Diameter: 1-9/16 In.
Number of Impeller Blades: 4
Roller Chain: 60
Drive Sprocket: 12 Teeth
Driven Sprocket: 38 Teeth
Chain Idler: Manual Adjustment
Gear Box Manufacturer: Comer
Gear Box Description: Model T-27D
Gear Box HP (Through Gears): 55 HP
Gear Box HP (Straight Through): 105 HP
Tractor RPM: 540 RPM
Impeller RPM: 540 RPM
Auger RPM: 170 RPM
PTO Manufacturer: Comer
PTO Description: 60
PTO Clutch Setting (Number): 1900
Shearbolt Bolt Size and Grade (PTO):
M10 6.8 Metric
Shearbolt Bolt Size and Grade (Auger):
5/16 In. 5 SAE
Skid Shoe: Adjustable
Skid Shoe Material: Steel
End Plate Thickness: 3/16 In.
Back Plate Thickness: 11 Gauge
Impeller Housing Thickness: 11 Gauge
Impeller Blade Thickness: 3/8 In.
Side Panel Bottom Thickness: 3/16 In.
Cutting Edge: Welded
Cutting Edge Dimension: 1/2 In. x 3 In.
Chute Diameter: 12 In.
Chute Base: Standard
Chute Rotation: 215 Degrees
Parking Stand: Standard
Hitch Category: Category I/II
Quick Hitch Compatibility:
iMatch Compatible and
Quick Coupler Compatible
HP Requirements (Minimum-Maximum HP):
35-90 HP
Operating Weight: 958 lbs.
Shipping Weight: 1003 lbs.
Approximate Set-Up Time: 60 Minutes
Chute Deflector Adjustment (Standard):
Manual
Chute Deflector Adjustment Options:
Hydraulic Cylinder (2 In. x 8 In.)
Including Hoses and Tips
Electric Actuator (8 In.)
Including Hardware, Switch, and Electric Cable
Chute Rotation (Standard): Must choose an
Option - Manual or Hydraulic
Chute Rotation Options:
Manual, Worm Gear with Crank
Hydraulic: Cylinder (2 In. x 8 In.),
Including Bracket, Hoses, and Tips
Chute: Two Part ONLY
Dual Auger: N/A
Rotating Drum (Including Hoses and Tips):
N/A

Code	Attachment Identifier	Description	List Price Suggested USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
3805XF		SB1184 - 84 In. 3-Point Medium Snowblower - U.S.	6,130.00
		CHUTES	
1000		Manual Chute Rotation Kit	In Base Price
1010		Hydraulic Cylinder Kit for Chute Rotation	553.00
		HYDRAULIC CYLINDER KIT	
9000		Hydraulic Cylinder Kit for Chute Deflector	377.00
9010		Electric Kit for Chute Deflector *Includes 8 In. actuator.*	1,030.00
		ATTACHMENTS FOR FIELD CONVERSION	

SB1184 - 84 In. 3-Point Medium Snowblower - U.S.

Continued

Code	Attachment Identifier	Description	List Price Suggested USD ($)
		ATTACHMENTS FOR FIELD CONVERSION ...Continued...	
		Miscellaneous	
	5RDF0021	Electric Kit for Chute Deflector - Includes 8 In. Actuator	1,069.20
	5RDF0071	Hydraulic Cylinder Kit for Chute Deflector	359.89
	5RDF0018	Hydraulic Cylinder Kit for Chute Rotation	767.80
	BLV11202	John Deere Quik-Knect Driveline Yoke Bundle *Tractor Receiver Part number: BLV10953At least one tractor receiver bundle is needed per tractor. This bundle is removable and can be used on various tractors within the compatibility.One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).*	275.00
	5RDF0016	Manual Chute Rotation Kit (SB11)	182.60

SB1194 - 94 In. 3-Point Medium Snowblower - U.S.

Equipment for Base Machine

Function: Snow Removal
Working Width: 94 In. (2,387.6 mm)
Transport Width: 95.5 In. (2,425.7 mm)
Working Height: 34 In. (863.6 mm)
Length: 55.5 In. (1,409.7 mm)
Single/Dual Auger: Single
Auger Diameter: 20 In. (508 mm)
Auger Flighting Thickness: 3/8 In. (9.5 mm)
Impeller Diameter: 27-1/2 In. (698.5 mm)
Impeller Width: 10.5 In. (266.7 mm)
Impeller Shaft Diameter: 1-9/16 In. (39.7 mm)
Number of Impeller Blades: 4
Roller Chain: 60
Drive Sprocket: 10 Teeth
Driven Sprocket: 32 Teeth
Chain Idler: Manual Adjustment
Gear Box Manufacturer: Comer
Gear Box Description: Model T-27D
Gear Box HP (Through Gears): 55 HP (41 kW)
Gear Box HP (Straight Through): 105 HP (78.3 kW)
Tractor RPM: 540 RPM
Impeller RPM: 540 RPM
Auger RPM: 170 RPM
PTO Manufacturer: Comer
PTO Description: 60
PTO Clutch Setting (Number): 1900 N-m
Shearbolt Bolt Size and Grade (PTO):
M10 6.8 Metric
Shearbolt Bolt Size and Grade (Auger):
5/16 In. 5 SAE
Skid Shoe: Adjustable
Skid Shoe Material: Steel
End Plate Thickness: 3/16 In. (4.8 mm)
Back Plate Thickness: 11 Gauge (3.18 mm)
Impeller Housing Thickness: 11 Gauge (3.18 mm)
Impeller Blade Thickness: 3/8 In. (9.5 mm)
Side Panel Bottom Thickness: 3/16 In. (4.8 mm)
Cutting Edge: Welded
Cutting Edge Dimension: 1/2 In. x 3 In. (12.7 x 76.2 mm)
Chute Diameter: 12 In. (304.8 mm)
Chute Base: Standard
Chute Rotation: 215 Degrees
Parking Stand: Standard
Hitch Category: Category II
Quick Hitch Compatibility:
Quick Coupler Compatible
HP Requirements (Minimum-Maximum HP):
35-90 HP (26.1 kW - 67.1 kW)
Operating Weight: 1,121 lbs. (508.5 kg)
Shipping Weight: 1,166 lbs. (528.9 kg)
Approximate Set-Up Time: 60 Minutes
Chute Deflector Adjustment (Standard):
Manual
Chute Deflector Adjustment Options:
Hydraulic Cylinder (2 In. x 8 In.)
Including Hoses and Tips
Electric Actuator (8 In.)
Including Hardware, Switch, and Electric Cable
Chute Rotation (Standard): Must choose an Option - Manual or Hydraulic
Chute Rotation Options:
Manual, Worm Gear with Crank
Hydraulic: Cylinder (2 In. x 8 In.), Including Bracket, Hoses, and Tips
Chute: Two Part ONLY
Dual Auger: N/A
Rotating Drum (Including Hoses and Tips):
N/A

Code	Attachment Identifier	Description	List Price Suggested USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
3806XF		SB1194 - 94 In. 3-Point Medium Snowblower - U.S.	6,361.00
		CHUTES	
1000		Manual Chute Rotation Kit	In Base Price
1010		Hydraulic Cylinder Kit for Chute Rotation	553.00
		HYDRAULIC CYLINDER KIT	
9000		Hydraulic Cylinder Kit for Chute Deflector	377.00
9010		Electric Kit for Chute Deflector *Includes 8 In. actuator.*	1,030.00
		ATTACHMENTS FOR FIELD CONVERSION	

SB1194 - 94 In. 3-Point Medium Snowblower - U.S.

Continued

Code	Attachment Identifier	Description	List Price Suggested USD ($)
		ATTACHMENTS FOR FIELD CONVERSION ...Continued...	
		Miscellaneous	
	5RDF0021	Electric Kit for Chute Deflector - Includes 8 In. Actuator	1,069.20
	5RDF0071	Hydraulic Cylinder Kit for Chute Deflector	359.89
	5RDF0018	Hydraulic Cylinder Kit for Chute Rotation	767.80
	5RDF0016	Manual Chute Rotation Kit (SB11)	182.60

SB1274 - 74 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.

Equipment for Base Machine

Function: Snow Removal
Working Width: 74 In. (1,879.6 mm)
Transport Width: 74.5 In. (1892.3 mm)
Working Height: 30 In. (762 mm)
Single/Dual Auger: Single
Auger Diameter: 20 In. (508 mm)
Auger Flighting Thickness: 3/8 In. (9.53 mm)
Impeller Diameter: 26 In. (660.4 mm)
Impeller Width: 10.5 In. (266.7 mm)
Impeller Shaft Diameter: 1 9/16 In. (39.69 mm)
Number of Impeller Blades: 4
Roller Chain: 60
Drive Sprocket: 10 Teeth
Driven Sprocket: 32 Teeth
Chain Idler: Automatic Adjustment
Gear Box Manufacturer: Comer
Gear Box Description: Model T-27D
Gear Box HP (Through Gears): 55 HP (41 kW)
Gear Box HP (Straight Through): 105 HP (78.3 kW)
Tractor RPM: 540 RPM
Impeller RPM: 540 RPM
Auger RPM: 170 RPM
PTO Manufacturer: Comer
PTO Description: 50
PTO Clutch Setting: 1,700 Nm (1,253.9 lbf-ft)
Shearbolt Bolt Size and Grade (PTO):
M10 8.8 Metric
Shearbolt Bolt Size and Grade (Auger):
5/16 In. 5 SAE
Skid Shoe: Adjustable
Skid Shoe Material: Steel
End Plate Thickness: 3/16 In. (4.8mm)
Back Plate Thickness: 11 Gauge
Impeller Housing Thickness: 3/16 In. (4.8mm)
Impeller Blade Thickness: 5/16 In. (7.9mm)
Side Panel Bottom Thickness: 1/2 In. (12.7 mm)
Cutting Edge: Replacable
Cutting Edge Dimension: 1/2 In. x 3 In. (12.7mm x 76.2 mm) Chute Diameter: 10.5 In. (266.7 mm)
Chute Base: Standard
Chute Rotation: 270 Degrees
Parking Stand: Standard
Hitch Category: Category I & II
Quick Hitch Compatibility:
iMatch & Cat. II Quick Coupler Compatible
HP Requirements (Minimum-Maximum HP):
30-80 HP (22.4-59.7kW)
Operating Weight: 835 lbs. (378.7 kg)
Shipping Weight: 875 lbs. (396.9 kg)
Approximate Set-up Time: 60 Minutes
Chute Deflector Adjustment (Standard): Hydraulic Cylinder Chute Rotation (Standard): Hydraulic Motor Chute: Three Part ONLY w/ 2" x 4" cylinder, hoses, and tips Rotating Drum (Including Hoses and Tips):
N/A

Code	Attachment Identifier	Description	List Price Suggested USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
3831XF		SB1274 - 74 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S. *Includes 2" x 4" cylinder, hoses, and tips for chute deflection.*	7,455.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous	
	5RDF0028	Cutting Edge - CHT400 Steel	340.10
	BLV11202	John Deere Quik-Knect Driveline Yoke Bundle *Tractor Receiver Part number: BLV10953At least one tractor receiver bundle is needed per tractor. This bundle is removable and can be used on various tractors within the compatibility.One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).*	275.00

SB1274 - 74 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.

Continued

THIS PAGE INTENTIONALLY LEFT BLANK

SB1280 - 80 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.

Equipment for Base Machine

Function: Snow Removal
Working Width: 80 In. (2,032 mm)
Transport Width: 80.5 In. (2,044.7 mm)
Working Height: 30 In. (762 mm)
Single/Dual Auger: Single
Auger Diameter: 20 In. (508 mm)
Auger Flighting Thickness: 3/8 In. (9.53 mm)
Impeller Diameter: 26 In. (660.4 mm)
Impeller Width: 10.5 In. (266.7 mm)
Impeller Shaft Diameter: 1 9/16 In. (39.69 mm)
Number of Impeller Blades: 4
Roller Chain: 60
Drive Sprocket: 10 Teeth
Driven Sprocket: 32 Teeth
Chain Idler: Automatic Adjustment
Gear Box Manufacturer: Comer
Gear Box Description: Model T-27D
Gear Box HP (Through Gears): 55 HP (41 kW)
Gear Box HP (Straight Through): 105 HP (78.3 kW)
Tractor RPM: 540 RPM
Impeller RPM: 540 RPM
Auger RPM: 170 RPM
PTO Manufacturer: Comer
PTO Description: 50
PTO Clutch Setting: 1,700 Nm (1,253.9 lbf-ft)
Shearbolt Bolt Size and Grade (PTO):
M10 8.8 Metric
Shearbolt Bolt Size and Grade (Auger):
5/16 In. 5 SAE
Skid Shoe: Adjustable
Skid Shoe Material: Steel
End Plate Thickness: 3/16 In. (4.8mm)
Back Plate Thickness: 11 Gauge
Impeller Housing Thickness: 3/16 In. (4.8mm)
Impeller Blade Thickness: 5/16 In. (7.9mm)
Side Panel Bottom Thickness: 1/2 In. (12.7 mm)
Cutting Edge: Replacable
Cutting Edge Dimension: 1/2 In. x 3 In. (12.7mm x 76.2 mm) Chute Diameter: 10.5 In. (266.7 mm)
Chute Base: Standard
Chute Rotation: 270 Degrees
Parking Stand: Standard
Hitch Category: Category I & II
Quick Hitch Compatibility:
iMatch & Cat. II Quick Coupler Compatible
HP Requirements (Minimum-Maximum HP):
30-80 HP (22.4-59.7kW)
Operating Weight: 895 lbs. (406 kg)
Shipping Weight: 935 lbs. (424.1 kg)
Approximate Set-up Time: 60 Minutes
Chute Deflector Adjustment (Standard): Hydraulic Cylinder Chute Rotation (Standard): Hydraulic Motor
Chute: Three Part ONLY w/ 2" x 4" cylinder, hoses, and tips Rotating Drum (Including Hoses and Tips):
N/A

Code	Attachment Identifier	Description	List Price Suggested USD ($)

Select One Code From Each Required Category

BASE MACHINE

3832XF		SB1280 - 80 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S. *Includes 2" x 4" cylinder, hoses, and tips for chute deflection.*	7,674.00

ATTACHMENTS FOR FIELD CONVERSION

Miscellaneous

	5RDF0029	Cutting Edge - CHT400 Steel	375.09
	BLV11202	John Deere Quik-Knect Driveline Yoke Bundle *Tractor Receiver Part number: BLV10953At least one tractor receiver bundle is needed per tractor. This bundle is removable and can be used on various tractors within the compatibility.One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).*	275.00

SB1280 - 80 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.

Continued

THIS PAGE INTENTIONALLY LEFT BLANK

SB1308R - 8 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.

Equipment for Base Machine

Function: Snow Removal
Working Width: 98 In.
Transport Width: 99 In.
Working Height: 44 In.
Length: 67 In.
Single/Dual Auger: Single/Dual
Auger Diameter: 24 In.
Auger Flighting Thickness: 7/16 In.
Impeller Diameter: 31-1/2 In.
Impeller Width: 14 In.
Impeller Shaft Diameter: 2 In.
Number of Impeller Blades: 6
Roller Chain: 80
Drive Sprocket: 12 Teeth
Driven Sprocket: 34 Teeth
Chain Idler: Automatic Adjustment
Gear Box Manufacturer: Comer
Gear Box Description: Model T-279A
Gear Box HP (Through Gears): 100 HP
Gear Box HP (Straight Through): 185 HP
Tractor RPM: 540/1000 RPM Optional
Impeller RPM: 540 RPM
Auger RPM: 190 RPM
PTO Manufacturer: Comer
PTO Description: 80
PTO Clutch Setting (Number): 3000
Shearbolt Bolt Size and Grade (PTO):
M10 6.8 Metric
Shearbolt Bolt Size and Grade (Auger):
5/16 In. 5 SAE
Skid Shoe: Adjustable
Skid Shoe Material: Steel
End Plate Thickness: 5/16 In.
Back Plate Thickness: 10 Gauge
Impeller Housing Thickness: 3/16 In.
Impeller Blade Thickness: 1/2 In.
Side Panel Bottom Thickness: 5/8 In.
Cutting Edge: Bolt-on/Reversible
Cutting Edge Dimension: 1/2 In. x 4 In.
Chute Diameter: 14-7/8 In.
Chute Base: Heavy Duty
Chute Rotation: 270 Degrees
Parking Stand: Standard
Hitch Category: Category II/III
Quick Hitch Compatibility:
Quick Hitch Compatible
HP Requirements (Minimum-Maximum HP):
90-180 HP
Operating Weight: 2233 lbs.
Shipping Weight: 2280 lbs.
Approximate Set-Up Time: 100 Minutes
Chute Deflector Adjustment (Standard):
Manual - Must Choose a Chute Option
Chute Deflector Adjustment Options:
Hydraulic Cylinder (2 In. x 8 In.)
Including Hoses and Tips
Chute Rotation (Standard):
Hydraulic Motor Chute Rotation
Including Hoses and Tips
Chute Rotation Options: N/A
Chute:
Two Part, Includes Manual Deflector
Three Part, Includes Cylinder
(2 In. x 8 In.), Hoses, and Tips
Dual Auger: 15 In. Diameter Auger
Rotating Drum (Including Hoses and Tips):
Standard

Code	Attachment Identifier	Description	List Price Suggested USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
3812XF		SB1308R - 8 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.	14,025.00
		CHUTES	
1000		2 Part Chute *Includes manual deflector.*	In Base Price
1010		3 Part Chute *Includes cylinders, hoses, and tips for hydraulic chute deflection. (Not available with option 9030).*	646.00
		HYDRAULIC CYLINDER KIT	
9030		Hydraulic Cylinder Kit for Chute Deflector *(Not available with option 1010).*	348.00

SB1308R - 8 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.

Continued

Code	Attachment Identifier	Description	List Price Suggested USD ($)
		HYDRAULIC ELECTRIC KIT	
9040		Reducer 1000 RPM Tractor PTO to 540 RPM for 13 Series Snowblowers, Models (SB1392, SB1308, SB1309) *Bundle Number 5RDF0023 is needed to complete kit.*	3,566.00
9050		Quick Disconnect Yoke Series 08, 1-3/4 In., 20 Splines for Series 13 Snowblowers, Models (SB1392, SB1308, SB1309) *Bundle Number 5RDF0022 is needed to complete kit.*	295.00
9060		Quick Hitch Kit *Required for Cat 2 and Cat 3 Quick-Hitch.* *For SB1388 and SB1388R Snowblower.*	860.00
		AUGER KIT	
9010		2nd Auger Kit *15 In. diameter.*	1,628.00
		MAIN AUGER	
9012		Serrated Main Auger	3,119.00
		CUTTING EDGE	
9000		Cutting Edge - CHT400 Steel	342.00
9002		Cutting Edge - Tivar *Fully Plastic - Wear & Rust Resistant.*	731.00
9003		Cutting Edge - Stainless Steel	710.00
		DRIFT CUTTERS	
9020		Drift Cutters	404.00
		SKID SHOES	
9070		Stainless Steel Pivoting Skid Shoes (13-Series Snowblower)	591.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous	
	5RDF0065	2nd Auger Kit - 15 In. Diameter	1,943.45
	5RDF0052	Cutting Edge - CHT400 Steel	417.40
	5RDF0074	Drift Cutters	419.11
	5RDF0071	Hydraulic Cylinder Kit for Chute Deflector	359.89
	5RDF0075	Quick Hitch Kit for SB13 Series Snowblowers except SB1388 & SB1388R *Required for Cat 2 & Cat 3 Quick-Hitch*	892.11

SB1308R - 8 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.

Continued

Code	Attachment Identifier	Description	List Price Suggested USD ($)
		ATTACHMENTS FOR FIELD CONVERSION ...Continued...	
	5RDF0023	Quick disconnect Yoke series 08, 1-3/4'', 20 splines for series 13 snowblowers, models (SB1392, SB1308, and SB1309) *Bundle Number 5RDF0022 is needed to complete kit.*	305.80
	5RDF0076	Reducer 1000 RPM Tractor PTO to 540 RPM for 13 series snowblowers, models (SB1392, SB1308, and SB1309)	3,741.14
	5RDF0069	Serrated Main Auger for SB1308 & SB1308R	3,454.04
	5RDF0062	Stainless Steel Pivoting Skid Shoes	741.87

SB1308R - 8 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.

Continued

THIS PAGE INTENTIONALLY LEFT BLANK

SB1309R - 9 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.

Equipment for Base Machine

Function: Snow Removal
Working Width: 104 In.
Transport Width: 105 In.
Working Height: 44 In.
Length: 67 In.
Single/Dual Auger: Single/Dual
Auger Diameter: 24 In.
Auger Flighting Thickness: 7/16 In.
Impeller Diameter: 31-1/2 In.
Impeller Width: 14 In.
Impeller Shaft Diameter: 2 In.
Number of Impeller Blades: 6
Roller Chain: 80
Drive Sprocket: 12 Teeth
Driven Sprocket: 34 Teeth
Chain Idler: Automatic Adjustment
Gear Box Manufacturer: Comer
Gear Box Description: Model T-279A
Gear Box HP (Through Gears): 100 HP
Gear Box HP (Straight Through): 185 HP
Tractor RPM: 540/1000 RPM
Impeller RPM: 540 RPM
Auger RPM: 190 RPM
PTO Manufacturer: Comer
PTO Description: 80
PTO Clutch Setting (Number): 3000
Shearbolt Bolt Size and Grade (PTO):
M10 6.8 Metric
Shearbolt Bolt Size and Grade (Auger):
5/16 In. 5 SAE
Skid Shoe: Adjustable
Skid Shoe Material: Steel
End Plate Thickness: 5/16 In.
Back Plate Thickness: 10 Gauge
Impeller Housing Thickness: 3/16 In.
Impeller Blade Thickness: 1/2 In.
Side Panel Bottom Thickness: 5/8 In.
Cutting Edge: Bolt-on/Reversible
Cutting Edge Dimension: 1/2 In. x 4 In.
Chute Diameter: 14-7/8 In.
Chute Base: Heavy Duty
Chute Rotation: 270 Degrees
Parking Stand: Standard
Hitch Category: Category II/III
Quick Hitch Compatibility:
Quick Hitch Compatible
HP Requirements (Minimum-Maximum HP):
90-180 HP
Operating Weight: 2336 lbs.
Shipping Weight: 2385 lbs.
Approximate Set-Up Time: 100 Minutes
Chute Deflector Adjustment (Standard):
Manual - Must Choose a Chute Option
Chute Deflector Adjustment Options:
Hydraulic Cylinder (2 In. x 8 In.)
Including Hoses and Tips
Chute Rotation (Standard):
Hydraulic Motor Chute Rotation
Including Hoses and Tips
Chute Rotation Options: N/A
Chute:
Two Part, Includes Manual Deflector
Three Part, Includes Cylinder
(2 In. x 8 In.), Hoses and Tips
Dual Auger: 15 In. Diameter Auger
Rotating Drum (Including Hoses and Tips):
Standard

Code	Attachment Identifier	Description	List Price Suggested USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
3813XF		SB1309R - 9 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.	14,361.00
		CHUTES	
1000		2 Part Chute *Includes manual deflector.*	In Base Price
1010		3 Part Chute *Includes cylinders, hoses, and tips for hydraulic chute deflection. (Not available with option 9030).*	646.00
		HYDRAULIC CYLINDER KIT	
9030		Hydraulic Cylinder Kit for Chute Deflector *(Not available with option 1010).*	348.00

SB1309R - 9 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.

Continued

Code	Attachment Identifier	Description	List Price Suggested USD ($)
		HYDRAULIC ELECTRIC KIT	
9040		Reducer 1000 RPM Tractor PTO to 540 RPM for 13 Series Snowblowers, Models (SB1392, SB1308, SB1309) *Bundle Number 5RDF0023 is needed to complete kit.*	3,566.00
9050		Quick Disconnect Yoke Series 08, 1-3/4 In., 20 Splines for Series 13 Snowblowers, Models (SB1392, SB1308, SB1309) *Bundle Number 5RDF0022 is needed to complete kit.*	295.00
9060		Quick Hitch Kit *Required for Cat 2 and Cat 3 Quick-Hitch.* *For SB1388 and SB1388R Snowblower.*	860.00
		AUGER KIT	
9010		2nd Auger Kit *15 In. diameter.*	1,646.00
		MAIN AUGER	
9012		Serrated Main Auger	3,226.00
		CUTTING EDGE	
9000		Cutting Edge - CHT400 Steel	368.00
9002		Cutting Edge - Tivar *Fully Plastic - Wear & Rust Resistant.*	763.00
9003		Cutting Edge - Stainless Steel	720.00
		DRIFT CUTTERS	
9020		Drift Cutters	404.00
		SKID SHOES	
9070		Stainless Steel Pivoting Skid Shoes (13-Series Snowblower)	591.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous	
	5RDF0066	2nd Auger Kit - 15 In. Diameter	1,780.20
	5RDF0053	Cutting Edge - CHT400 Steel	390.63
	5RDF0061	Cutting Edge for SB1309R - Stainless Steel	798.49
	5RDF0057	Cutting Edge for SB1309R - Tivar *Fully Plastic - Wear and Rust Resistant*	792.00
	5RDF0074	Drift Cutters	419.11
	5RDF0071	Hydraulic Cylinder Kit for Chute Deflector	359.89

SB1309R - 9 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.

Continued

Code	Attachment Identifier	Description	List Price Suggested USD ($)
		ATTACHMENTS FOR FIELD CONVERSION ...Continued...	
	5RDF0075	Quick Hitch Kit for SB13 Series Snowblowers except SB1388 & SB1388R *Required for Cat 2 & Cat 3 Quick-Hitch*	892.11
	5RDF0023	Quick disconnect Yoke series 08, 1-3/4'', 20 splines for series 13 snowblowers, models (SB1392, SB1308, and SB1309) *Bundle Number 5RDF0022 is needed to complete kit.*	305.80
	5RDF0076	Reducer 1000 RPM Tractor PTO to 540 RPM for 13 series snowblowers, models (SB1392, SB1308, and SB1309)	3,741.14
	5RDF0070	Serrated Main Auger for SB1309R	3,575.94
	5RDF0062	Stainless Steel Pivoting Skid Shoes	741.87

SB1309R - 9 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.

Continued

THIS PAGE INTENTIONALLY LEFT BLANK

SB1388R - 88 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.

Equipment for Base Machine

Function: Snow Removal
Working Width: 88 In.
Transport Width: 88.5 In.
Working Height: 40 In.
Length: 62.5 In.
Single/Dual Auger: Single/Dual
Auger Diameter: 22 In.
Auger Flighting Thickness: 7/16 In.
Impeller Diameter: 28-1/2 In.
Impeller Width: 12 In.
Impeller Shaft Diameter: 1-9/16 In.
Number of Impeller Blades: 4
Roller Chain: 80
Drive Sprocket: 11 Teeth
Driven Sprocket: 34 Teeth
Chain Idler: Automatic Adjustment
Gear Box Manufacturer: Comer
Gear Box Description: Model T-27D
Gear Box HP (Through Gears): 55 HP
Gear Box HP (Straight Through): 105 HP
Tractor RPM: 540 RPM
Impeller RPM: 540 RPM
Auger RPM: 175 RPM
PTO Manufacturer: Comer
PTO Description: 60
PTO Clutch Setting (Number): 1900
Shearbolt Bolt Size and Grade (PTO):
M10 6.8 Metric
Shearbolt Bolt Size and Grade (Auger):
5/16 In. 5 SAE
Skid Shoe: Adjustable
Skid Shoe Material: Steel
End Plate Thickness: 1/4 In.
Back Plate Thickness: 11 Gauge
Impeller Housing Thickness: 3/16 In.
Impeller Blade Thickness: 3/8 In.
Side Panel Bottom Thickness: 5/8 In.
Cutting Edge: Bolt-on/Reversible
Cutting Edge Dimension: 1/2 In. x 4 In.
Chute Diameter: 12 3/4 In.
Chute Base: Heavy Duty
Chute Rotation: 270 Degrees
Parking Stand: Standard
Hitch Category: Category II
Quick Hitch Compatibility:
Quick Coupler Compatible
HP Requirements (Minimum-Maximum HP):
45-95 HP
Operating Weight: 1670 lbs.
Shipping Weight: 1715 lbs.
Approximate Set-Up Time: 90 Minutes
Chute Deflector Adjustment (Standard):
Manual - Must Choose a Chute Option
Chute Deflector Adjustment Options:
Hydraulic Cylinder (2 In. x 8 In.)
Including Hoses and Tips
Chute Rotation (Standard):
Hydraulic Motor Chute Rotation
Including Hoses and Tips
Chute Rotation Options: N/A
Chute:
Two Part, Includes Manual Deflector
Three Part, Includes Cylinder
(2 In. x 8 In.), Hoses and Tips
Dual Auger: 14 In. Diameter Auger
Rotating Drum (Including Hoses and Tips):
Standard

Code	Attachment Identifier	Description	List Price Suggested USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
3815XF		SB1388R - 88 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.	11,255.00
		CHUTES	
1000		2 Part Chute *Includes manual deflector.*	In Base Price
1010		3 Part Chute *Includes cylinders, hoses, and tips for hydraulic chute deflection. (Not available with option 9030).*	704.00
		HYDRAULIC CYLINDER KIT	
9030		Hydraulic Cylinder Kit for Chute Deflector *(Not available with option 1010).*	348.00

SB1388R - 88 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.

Continued

Code	Attachment Identifier	Description	List Price Suggested USD ($)
		HYDRAULIC ELECTRIC KIT	
9060		Quick Hitch Kit *Required for Cat 2 and Cat 3 Quick-Hitch.* *For 13-Series Snowblower except SB1388 and SB1388R.*	753.00
		AUGER KIT	
9010		2nd Auger Kit *14 In. diameter.*	1,520.00
		MAIN AUGER	
9012		Serrated Main Auger	2,956.00
		CUTTING EDGE	
9000		Cutting Edge - CHT400 Steel	297.00
9002		Cutting Edge - Tivar *Fully Plastic - Wear & Rust Resistant.*	677.00
9003		Cutting Edge - Stainless Steel	688.00
		DRIFT CUTTERS	
9020		Drift Cutters	404.00
		SKID SHOES	
9070		Stainless Steel Pivoting Skid Shoes (13-Series Snowblower)	591.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous	
	5RDF0063	2nd Auger Kit - 14 In. Diameter	1,813.15
	5RDF0050	Cutting Edge - CHT400 Steel	324.55
	5RDF0058	Cutting Edge for SB1388 & SB1388R - Stainless Steel	730.73
	5RDF0054	Cutting Edge for SB1388 & SB1388R - Tivar *Fully Plastic - Wear and Rust Resistant.*	717.13
	5RDF0074	Drift Cutters	419.11
	5RDF0071	Hydraulic Cylinder Kit for Chute Deflector	359.89
	5RDF0077	Quick Hitch Kit for SB1388 and SB1388R Snowblower *Required for Cat 2 & Cat 3 Quick-Hitch*	781.00
	5RDF0067	Serrated Main Auger for SB1388 & SB1388R	3,277.28
	5RDF0062	Stainless Steel Pivoting Skid Shoes	741.87

SB1388R - 88 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.

Continued

SB1388R - 88 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.

Continued

THIS PAGE INTENTIONALLY LEFT BLANK

SB1388 - 88 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.

Equipment for Base Machine

Function: Snow Removal
Working Width: 88 In.
Transport Width: 88.5 In.
Working Height: 40 In.
Length: 61 In.
Single/Dual Auger: Single/Dual
Auger Diameter: 22 In.
Auger Flighting Thickness: 7/16 In.
Impeller Diameter: 28-1/2 In.
Impeller Width: 12 In.
Impeller Shaft Diameter: 1-9/16 In.
Number of Impeller Blades: 4
Roller Chain: 80
Drive Sprocket: 11 Teeth
Driven Sprocket: 34 Teeth
Chain Idler: Automatic Adjustment
Gear Box Manufacturer: Comer
Gear Box Description: Model T-27D
Gear Box HP (Through Gears): 55 HP
Gear Box HP (Straight Through): 105 HP
Tractor RPM: 540 RPM
Impeller RPM: 540 RPM
Auger RPM: 175 RPM
PTO Manufacturer: Comer
PTO Description: 60
PTO Clutch Setting (Number): 1900
Shearbolt Bolt Size and Grade (PTO):
M10 6.8 Metric
Shearbolt Bolt Size and Grade (Auger):
5/16 In. 5 SAE
Skid Shoe: Adjustable
Skid Shoe Material: Steel
End Plate Thickness: 1/4 In.
Back Plate Thickness: 11 Gauge
Impeller Housing Thickness: 1/4 In.
Impeller Blade Thickness: 3/8 In.
Side Panel Bottom Thickness: 5/8 In.
Cutting Edge: Bolt-on/Reversible
Cutting Edge Dimension: 1/2 In. x 4 In.
Chute Diameter: 12-3/4 In.
Chute Base: Heavy Duty
Chute Rotation: 270 Degrees
Parking Stand: Standard
Hitch Category: Category II
Quick Hitch Compatibility:
Quick Coupler Compatible
HP Requirements (Minimum-Maximum HP):
45-95 HP
Operating Weight: 1552 lbs.
Shipping Weight: 1597 lbs.
Approximate Set-Up Time: 90 Minutes
Chute Deflector Adjustment (Standard):
Manual - Must Choose a Chute Option
Chute Deflector Adjustment Options:
Hydraulic Cylinder (2 In. x 8 In.)
Including Hoses and Tips
Chute Rotation (Standard):
Hydraulic Motor Chute Rotation
Including Hoses and Tips
Chute Rotation Options: N/A
Chute:
Two Part, Includes Manual Deflector
Three Part, Includes Cylinder
(2 In. x 8 In.), Hoses and Tips
Dual Auger: 14 In. Diameter Auger
Rotating Drum (Including Hoses and Tips):
N/A

Code	Attachment Identifier	Description	List Price Suggested USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
3814XF		SB1388 - 88 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.	9,558.00
		CHUTES	
1000		2 Part Chute *Includes manual deflector.*	In Base Price
1010		3 Part Chute *Includes cylinders, hoses, and tips for hydraulic chute deflection. (Not available with option 9030).*	704.00
		HYDRAULIC CYLINDER KIT	
9030		Hydraulic Cylinder Kit for Chute Deflector *(Not available with option 1010).*	348.00

SB1388 - 88 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.

Continued

Code	Attachment Identifier	Description	List Price Suggested USD ($)
		HYDRAULIC ELECTRIC KIT	
9060		Quick Hitch Kit *Required for Cat 2 and Cat 3 Quick-Hitch.* *For 13-Series Snowblower except SB1388 and SB1388R.*	753.00
		AUGER KIT	
9010		2nd Auger Kit *14 In. diameter.*	1,520.00
		MAIN AUGER	
9012		Serrated Main Auger	2,956.00
		CUTTING EDGE	
9000		Cutting Edge - CHT400 Steel	297.00
9002		Cutting Edge - Tivar *Fully Plastic - Wear & Rust Resistant.*	677.00
9003		Cutting Edge - Stainless Steel	688.00
		DRIFT CUTTERS	
9020		Drift Cutters	404.00
		SKID SHOES	
9070		Stainless Steel Pivoting Skid Shoes (13-Series Snowblower)	591.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous	
	5RDF0063	2nd Auger Kit - 14 In. Diameter	1,813.15
	5RDF0050	Cutting Edge - CHT400 Steel	324.55
	5RDF0058	Cutting Edge for SB1388 & SB1388R - Stainless Steel	730.73
	5RDF0054	Cutting Edge for SB1388 & SB1388R - Tivar *Fully Plastic - Wear and Rust Resistant.*	717.13
	5RDF0074	Drift Cutters	419.11
	5RDF0071	Hydraulic Cylinder Kit for Chute Deflector	359.89
	5RDF0077	Quick Hitch Kit for SB1388 and SB1388R Snowblower *Required for Cat 2 & Cat 3 Quick-Hitch*	781.00
	5RDF0067	Serrated Main Auger for SB1388 & SB1388R	3,277.28
	5RDF0062	Stainless Steel Pivoting Skid Shoes	741.87

SB1388 - 88 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.

Continued

SB1388 - 88 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.

Continued

THIS PAGE INTENTIONALLY LEFT BLANK

SB1392R - 92 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.

Equipment for Base Machine

Function: Snow Removal
Working Width: 92 In.
Transport Width: 93 In.
Working Height: 44 In.
Length: 67 In.
Single/Dual Auger: Single/Dual
Auger Diameter: 24 In.
Auger Flighting Thickness: 7/16 In.
Impeller Diameter: 31-1/2 In.
Impeller Width: 14 In.
Impeller Shaft Diameter: 2 In.
Number of Impeller Blades: 6
Roller Chain: 80
Drive Sprocket: 12 Teeth
Driven Sprocket: 34 Teeth
Chain Idler: Automatic Adjustment
Gear Box Manufacturer: Comer
Gear Box Description: Model T-279A
Gear Box HP (Through Gears): 100 HP
Gear Box HP (Straight Through): 185 HP
Tractor RPM: 540/1000 RPM
Impeller RPM: 540 RPM
Auger RPM: 190 RPM
PTO Manufacturer: Comer
PTO Description: 80
PTO Clutch Setting (Number): 3000
Shearbolt Bolt Size and Grade (PTO):
M10 6.8 Metric
Shearbolt Bolt Size and Grade (Auger):
5/16 In. 5 SAE
Skid Shoe: Adjustable
Skid Shoe Material: Steel
End Plate Thickness: 5/16 In.
Back Plate Thickness: 10 Gauge
Impeller Housing Thickness: 3/16 In.
Impeller Blade Thickness: 1/2 In.
Side Panel Bottom Thickness: 5/8 In.
Cutting Edge: Bolt-on/Reversible
Cutting Edge Dimension: 1/2 In. x 4 In.
Chute Diameter: 14-7/8 In.
Chute Base: Heavy Duty
Chute Rotation: 270 Degrees
Parking Stand: Standard
Hitch Category: Category II
Quick Hitch Compatibility:
Quick Coupler Compatible
HP Requirements (Minimum-Maximum HP):
75-125 HP
Operating Weight: 2183 lbs.
Shipping Weight: 2230 lbs.
Approximate Set-Up Time: 100 Minutes
Chute Deflector Adjustment (Standard):
Manual - Must Choose a Chute Option
Chute Deflector Adjustment Options:
Hydraulic Cylinder (2 In. x 8 In.)
Including Hoses and Tips
Chute Rotation (Standard):
Hydraulic Motor Chute Rotation
Including Hoses and Tips
Chute Rotation Options: N/A
Chute:
Two Part, Includes Manual Deflector
Three Part, Includes Cylinder
(2 In. x 8 In.), Hoses, and Tips
Dual Auger: 15 In. Diameter Auger
Rotating Drum (Including Hoses and Tips):
Standard

Code	Attachment Identifier	Description	List Price Suggested USD ($)
		Select One Code From Each Required Category	
		BASE MACHINE	
3817XF		SB1392R - 92 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.	13,416.00
		CHUTES	
1000		2 Part Chute *Includes manual deflector.*	In Base Price
1010		3 Part Chute *Includes cylinders, hoses, and tips for hydraulic chute deflection. (Not available with option 9030).*	646.00
		HYDRAULIC CYLINDER KIT	
9030		Hydraulic Cylinder Kit for Chute Deflector *(Not available with option 1010).*	348.00

SB1392R - 92 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.

Continued

Code	Attachment Identifier	Description	List Price Suggested USD ($)
		HYDRAULIC ELECTRIC KIT	
9040		Reducer 1000 RPM Tractor PTO to 540 RPM for 13 Series Snowblowers, Models (SB1392, SB1308, SB1309) *Bundle Number 5RDF0023 is needed to complete kit.*	3,566.00
9050		Quick Disconnect Yoke Series 08, 1-3/4 In., 20 Splines for Series 13 Snowblowers, Models (SB1392, SB1308, SB1309) *Bundle Number 5RDF0022 is needed to complete kit.*	295.00
9060		Quick Hitch Kit *Required for Cat 2 and Cat 3 Quick-Hitch.* *For SB1388 and SB1388R Snowblower.*	860.00
		AUGER KIT	
9010		2nd Auger Kit *15 In. diameter.*	1,540.00
		MAIN AUGER	
9012		Serrated Main Auger	3,009.00
		CUTTING EDGE	
9000		Cutting Edge - CHT400 Steel	313.00
9002		Cutting Edge - Tivar *Fully Plastic - Wear & Rust Resistant.*	699.00
9003		Cutting Edge - Stainless Steel	699.00
		DRIFT CUTTERS	
9020		Drift Cutters	404.00
		SKID SHOES	
9070		Stainless Steel Pivoting Skid Shoes (13-Series Snowblower)	591.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous	
	5RDF0064	2nd Auger Kit - 15 In. Diameter	1,866.16
	5RDF0051	Cutting Edge - CHT400 Steel	342.04
	5RDF0059	Cutting Edge for SB1392 & SB1392R - Stainless Steel	724.91
	5RDF0055	Cutting Edge for SB1392 & SB1392R - Tivar *Fully Plastic - Wear and Rust Resistant.*	724.91
	5RDF0074	Drift Cutters	419.11
	5RDF0071	Hydraulic Cylinder Kit for Chute Deflector	359.89

SB1392R - 92 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.

Continued

Code	Attachment Identifier	Description	List Price Suggested USD ($)
		ATTACHMENTS FOR FIELD CONVERSION ...Continued...	
	5RDF0075	Quick Hitch Kit for SB13 Series Snowblowers except SB1388 & SB1388R *Required for Cat 2 & Cat 3 Quick-Hitch*	892.11
	5RDF0023	Quick disconnect Yoke series 08, 1-3/4'', 20 splines for series 13 snowblowers, models (SB1392, SB1308, and SB1309) *Bundle Number 5RDF0022 is needed to complete kit.*	305.80
	5RDF0076	Reducer 1000 RPM Tractor PTO to 540 RPM for 13 series snowblowers, models (SB1392, SB1308, and SB1309)	3,741.14
	5RDF0068	Serrated Main Auger for SB1392 & SB1392R	3,336.19
	5RDF0062	Stainless Steel Pivoting Skid Shoes	741.87

SB1392R - 92 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.

Continued

THIS PAGE INTENTIONALLY LEFT BLANK

SB2164 - 64 In Hydraulic, 300 Series Carrier Loader Mount Snowblower

Equipment for Base Machine

Function: Snow Removal
Working Width: 64 In. (1,625.6 mm)
Transport Width: 64 In. (1,625.6 mm)
Working Height: 27 In. (685.8 mm)
Single/Dual Auger: Single
Auger Diameter: 15 In.
Auger Flighting Thickness: 5/16 In. (8 mm)
Impeller Diameter: 24 In. (609.6 mm)
Impeller Width: 7 In. (177.8 mm)
Impeller Shaft Diameter: 1.25 In. (31.75 mm)
Number of Impeller Blades: 4
Auger Drive: Hydraulic
Impeller Drive: Hydraulic
Impeller RPM: 680 RPM
Auger RPM: 200 RPM
Skid Shoe: Adjustable
Skid Shoe Material: Steel
End Plate Thickness: 3/16 In. (4.8 mm)
Back Plate Thickness: 11 Gauge (3.18 mm)
Impeller Housing Thickness: 3/16 In. (4.8 mm)
Impeller Blade Thickness: 1/4 In. (6.4 mm)
Side Panel Bottom Thickness: 1/2 In. (12.7 mm)
Cutting Edge: Replaceable
Cutting Edge Dimension: 3/8 In. x 2 In. (9.5 mm x 50.8 mm)
Chute Diameter: 8.25 In. (209.6 mm)
Chute Base: Standard
Chute Rotation: 270 Degrees
Operating Weight: 760 lbs. (344.7 kg)
Shipping Weight: 840 lbs. (381 kg)
Approximate Set-Up Time: 120 Minutes
Chute Deflector Adjustment (Standard): Must Choose an option Manual Tie Rod or Hydraulic Cylinder
Chute Deflector Adjustment Options: Electric Solenoid Valve, Switch, and Hydraulic Cylinder
Chute: Two Part ONLY
Dual Auger: N/A
Rotating Drum (Including Hoses and Tips): N/A
Function: Hydraulic Power Unit
Pressure: 2700 psi
Flow: 16 gpm
Reservoir Capacity: 15 gal.
System Capacity: 17 gal.
System Features: Pressure relieve valve, filter, temperature and oil level gauge, and thermal protection switch
Hoses, Tips, and Brackets included
Tractor RPM: 540 RPM
PTO Manufacturer: Comer
Parking Stand: Standard
Hitch Category: Category I
Quick Hitch Compatibility: iMatch Compatible
Approximate Set-Up Time: 120 Minutes

Code	Attachment Identifier	Description	List Price Suggested USD ($)

Select One Code From Each Required Category

BASE MACHINE

3822XF	SB2164 - 64 In Hydraulic, 300 Series Carrier Loader Mount Snowblower *With Hydraulic Chute Rotation and HP2025 Hydraulic Power Unit - U.S.* *Must only be used with HP2025 Hydraulic Power Unit.*	15,615.00

HYDRAULIC POWER UNITS

1000	HP2025 - Hydraulic Power Unit, 25 HP *Includes wiring harness 5RDF0078 to control the loader mounted implement.*	In Base Price
1095	Less Hydraulic Power Unit *HP2025*	-7,785.00

OIL COOLER

2000	Oil Cooler for HP2025 and HP2134 Hydraulic Power Units *Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.* *Not available with option Code 1095.*	In Base Price
2095	Less Oil Cooler	-1,989.00

SB2164 - 64 In Hydraulic, 300 Series Carrier Loader Mount Snowblower

Continued

Code	Attachment Identifier	Description	List Price Suggested USD ($)
		CHUTES	
3000		SB21 Manual Chute Deflection *Includes manual deflector.*	In Base Price
3010		Hydraulic Chute Deflection *Includes cylinders, hoses and fittings.*	681.00
		HYDRAULIC ELECTRIC KIT	
9040		Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors *Not available with option Code 1095.*	110.00
		DRIFT CUTTERS	
9020		Drift Cutters (SB21)	162.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous	
	5RDF0026	Drift Cutters (SB21)	168.31
	5RDF0027	Kit for Hydraulic Chute Deflector (SB2164)	754.06
	5RDF0036	Oil Cooler for HP2025 and HP2134 Hydraulic Power Units *Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.*	2,063.60
	5RDF0038	Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors *Includes complete wiring harness from battery to switch in the console.*	114.40
	5RDF0078	Wiring Harness for HP2025 and HP2134 Hydraulic Power Units to control Loader Mounted Attachment *Includes complete wiring harness from switch in the console to 3 cavities connectors for front implements.*	159.51

SB2176 - 76 In. Hydraulic, 400 Series Carrier Loader Mount Snowblower

Equipment for Base Machine

Function: Snow Removal
Working Width: 76 In. (1,931.4 mm)
Transport Width: 76 In. (1,931.4 mm)
Working Height: 27 In. (685.8 mm)
Single/Dual Auger: Single
Auger Diameter: 15 In.
Auger Flighting Thickness: 5/16 In. (8 mm)
Impeller Diameter: 24 In. (609.6 mm)
Impeller Width: 8.5 In. (215.9 mm)
Impeller Shaft Diameter: 1.25 In. (31.75 mm)
Number of Impeller Blades: 4
Auger Drive: Hydraulic
Impeller Drive: Hydraulic
Impeller RPM: 580 RPM
Auger RPM: 180 RPM
Skid Shoe: Adjustable
Skid Shoe Material: Steel
End Plate Thickness: 3/16 In. (4.8 mm)
Back Plate Thickness: 11 Gauge (3.18 mm)
Impeller Housing Thickness: 3/16 In. (4.8 mm)
Impeller Blade Thickness: 5/16 In. (8 mm)
Side Panel Bottom Thickness: 1/2 In. (12.7 mm)
Cutting Edge: Replaceable
Cutting Edge Dimension: 1/2 In. x 3 In. (12.7 mm x 76.2 mm)
Chute Diameter: 12 In. (0.3m)
Chute Base: Standard
Chute Rotation: 270 Degrees
Operating Weight: 760 lbs. (344.7 kg)
Shipping Weight: 840 lbs. (381 kg)
Approximate Set-Up Time: 120 Minutes
Chute Deflector Adjustment (Standard): Must Choose an option Manual or Hydraulic Adjustable Tie Rod or Hydraulic
Chute Deflector Adjustment Options: Electric Solenoid Valve, Switch, Wiring Harness and Hydraulic Cylinder
Chute: Two Part ONLY
Dual Auger: N/A
Rotating Drum (Including Hoses and Tips): N/A
Function: Hydraulic Power Unit
Pressure: 2700 psi
Flow: 16 gpm
Reservoir Capacity: 15 gal.
System Capacity: 17 gal.
System Features: Pressure relieve valve, filter, temperature and oil level gauge, and thermal protection switch
Hoses, Tips, and Brackets included
Tractor RPM: 540 RPM
PTO Manufacturer: Comer
Parking Stand: Standard
Hitch Category: Category I
Quick Hitch Compatibility: iMatch Compatible
Approximate Set-Up Time: 120 Minutes

Code	Attachment Identifier	Description	List Price Suggested USD ($)

Select One Code From Each Required Category

BASE MACHINE

3821XF	SB2176 - 76 In. Hydraulic, 400 Series Carrier Loader Mount Snowblower *With Hydraulic Chute Rotation and HP2134 Hydraulic Power Unit - U.S.* *Must only be used with HP2134 Hydraulic Power Unit.*	16,061.00

HYDRAULIC POWER UNITS

1095	Less Hydraulic Power Unit *HP2134*	-7,919.00
1010	HP2134 - Hydraulic Power Unit, 34 HP *Includes wiring harness 5RDF0078 to control the loader mounted implement.*	In Base Price

OIL COOLER

2000	Oil Cooler for HP2025 and HP2134 Hydraulic Power Units *Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.* *Not available with option Code 1095.*	In Base Price
2095	Less Oil Cooler	-1,989.00

SB2176 - 76 In. Hydraulic, 400 Series Carrier Loader Mount Snowblower

Continued

Code	Attachment Identifier	Description	List Price Suggested USD ($)
		CHUTES	
3000		SB21 Manual Chute Deflection *Includes manual deflector.*	In Base Price
3010		Hydraulic Chute Deflection *Includes cylinders, hoses and fittings.*	681.00
		HYDRAULIC ELECTRIC KIT	
9040		Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors *Not available with option Code 1095.*	110.00
		DRIFT CUTTERS	
9020		Drift Cutters (SB21)	162.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous	
	5RDF0026	Drift Cutters (SB21)	168.31
	5RDF0025	Kit for Hydraulic Chute Deflector (SB2176)	706.07
	5RDF0036	Oil Cooler for HP2025 and HP2134 Hydraulic Power Units *Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.*	2,063.60
	5RDF0038	Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors *Includes complete wiring harness from battery to switch in the console.*	114.40
	5RDF0078	Wiring Harness for HP2025 and HP2134 Hydraulic Power Units to control Loader Mounted Attachment *Includes complete wiring harness from switch in the console to 3 cavities connectors for front implements.*	159.51