



FL1053 - 53" FLAIL MOWER (FIXED)

Code	Description	List price
04A1XF	<p>FL1053 - 53" FLAIL MOWER (FIXED)</p> <p>Dimensions Capacity, Cutting (in.): 0.75" Height, Cutting (in.): .78" /1.57" /2.36" Height, Overall (in.): 31.2" Length, Overall (in.): 32" Width, Cutting (in.): 53" Width, Overall (in.): 60.02" Weight (lbs.): 467 lbs.</p> <p>Compatibility Tractor HP Required (min. - max.): 20 - 45HP Tractor Weight MINIMUM (lbs.): 1400 lbs. COG (in): 15"</p> <p>Hitch Hitch Type: 3-point iMatch Compatible: No Hitch Category: 1 Hitch Position: Fixed Centered Offset Range: No Hydraulic Offset: No</p> <p>Blades Blade Type: Hammers (std); Y-Blade (service) Number of Hammers: 28 Type of Blades/ Hammers: 19 / 21 Blade Tip Speed (ft/min): 8622</p> <p>Rotor Rotor Diameter (in.): 5" Rotor Speed (rpm): 2600 rpm Rotor Thickness (mm.): 8 mm. Rotor Work Diameter (in.): 12.63" Rotor Bearing Type: SPHERICAL ROLLER 22207</p> <p>Drives Gear Box Speed (rpm): 540 rpm Drive Belts: 2 - SPB Lp=1160 Gauge Roller Diameter (in.): 5.5"</p> <p>Other Hydraulic Quick Coupler Size (in.): 1/2" Frame Thickness (mm.): 3 mm.</p>	



FL1053 - 53" FLAIL MOWER (FIXED)

Code	Description	List price
	Side Frame Thickness (mm.): 4 mm. Roller Bearing Diameter (in.): 2.4" Rear Roller Bearing Type: D30 D62 B20 2206E 2RS1 Belt adjustment: Screw adjustment Primary Pulley Diameter (mm.): 225 mm. Secondary Pulley Diameter (mm.): 140 mm. Hood Height (in.): 15.35" Side Case Height (in.): 25.2" PTO Yoke Height (in.): 18.66"	
	BASE MACHINE	
04A1XF	FL1053 - 53" FLAIL MOWER (FIXED)	USD \$4,323.00
	DESTINATION AND LANGUAGE Basic Factory Options DESTINATION	
0202	United States	No Added Cost
	OPERATOR'S MANUAL AND DECALS	
0409	English	No Added Cost
0413	French	No Added Cost
0437	Spanish	No Added Cost



FL1061 - 61" FLAIL MOWER (FIXED)

Code	Description	List price
04B1XF	<p>FL1061 - 61" FLAIL MOWER (FIXED)</p> <p>Dimensions Capacity, Cutting (in.): 0.75" Height, Cutting (in.): .78" /1.57" /2.36" Height, Overall (in.): 31.2" Length, Overall (in.): 32" Width, Cutting (in): 61" Width, Overall (in.): 68.16" Weight (lbs.): 505 lbs.</p> <p>Compatibility Tractor HP Required (min. - max.): 25 - 45HP Tractor Weight MINIMUM (lbs.): 1550 lbs. COG (in): 15"</p> <p>Hitch Hitch Type: 3-point iMatch Compatible: No Hitch Category: 1 Hitch Position: Fixed Centered Offset Range: No Hydraulic Offset: No</p> <p>Blades Blade Type: Hammers (std); Y-Blade (service) Number of Hammers: 32 Type of Blades/ Hammers: 19 / 21 Blade Tip Speed (ft/min): 8622</p> <p>Rotor Rotor Diameter (in.): 5" Rotor Speed (rpm): 2600 rpm Rotor Thickness (mm.): 8 mm. Rotor Work Diameter (in.): 12.63" Rotor Bearing Type: SPHERICAL ROLLER 22207</p> <p>Drives Gear Box Speed (rpm): 540 rpm Drive Belts: 2 - SPB Lp=1160 Gauge Roller Diameter (in.): 5.5"</p> <p>Other Hydraulic Quick Coupler Size (in.): 1/2"</p>	



FL1061 - 61" FLAIL MOWER (FIXED)

Code	Description	List price
	Frame Thickness (mm.): 3 mm. Side Frame Thickness (mm.): 4 mm. Roller Bearing Diameter (in.): 2.4" Rear Roller Bearing Type: D30 D62 B20 2206E 2RS1 Belt adjustment: Screw adjustment Primary Pulley Diameter (mm.): 225 mm. Secondary Pulley Diameter (mm.): 140 mm. Hood Height (in.): 15.35" Side Case Height (in.): 25.2" PTO Yoke Height (in.): 18.66"	
	BASE MACHINE	
04B1XF	FL1061 - 61" FLAIL MOWER (FIXED)	USD \$4,550.00
	DESTINATION AND LANGUAGE Basic Factory Options DESTINATION	
0202	United States	No Added Cost
	OPERATOR'S MANUAL AND DECALS	
0409	English	No Added Cost
0413	French	No Added Cost
0437	Spanish	No Added Cost



FL1163 - 63" FLAIL MOWER (SIDE SHIFT)

Code	Description	List price
04D1XF	FL1163 - 63" FLAIL MOWER (SIDE SHIFT)	
	Dimensions	
	Capacity, Cutting (in.): 1.5"	
	Height, Cutting (in.): 0.98" /1.96" /2.99"	
	Height, Overall (in.): 36.5"	
	Length, Overall (in.): 44.3"	
	Width, Cutting (in): 63"	
	Width, Overall (in.): 68.88"	
	Weight (lbs.): 718 lbs.	
	Compatibility	
	Tractor HP Required (min. - max.): 30 - 55HP	
	Tractor Weight MINIMUM (lbs.): 2600 lbs.	
	COG (in): 25"	
	Hitch	
	Hitch Type: 3-point	
	iMatch Compatible: No	
	Hitch Category: 1	
	Hitch Position: Centered	
	Offset Range: Left of Center (11"-33"), Right of Center (30"-46")	
	Hydraulic Offset: No	
	Blades	
	Blade Type: Hammers (std); Y-Blade (service)	
	Number of Hammers: 22	
	Type of Blades/ Hammers: 18 / 20	
	Blade Tip Speed (ft/min): 8937	
	Rotor	
	Rotor Diameter (in.): 5"	
	Rotor Speed (rpm): 2278 rpm	
	Rotor Thickness (mm.): 8 mm.	
	Rotor Work Diameter (in.): 15"	
	Rotor Bearing Type: SPHERICAL ROLLER 22207	
	Drives	
	Gear Box Speed (rpm): 540 rpm	
	Drive Belts: 3 - SPB Lp=1320	
	Gauge Roller Diameter (in.): 5.5"	
	Other	
	Hydraulic Quick Coupler Size (in.): 1/2"	
	Frame Thickness (mm.): 3 mm.	



FL1163 - 63" FLAIL MOWER (SIDE SHIFT)

Code	Description	List price
	Side Frame Thickness (mm.): 5 mm. Roller Bearing Diameter (in): 2.835" Rear Roller Bearing Type: YAR 207-2FW/VA201 Belt adjustment: Screw adjustment Primary Pulley Diameter (mm.): 225 mm. Secondary Pulley Diameter (mm.): 160 mm. Hood Height (in.): 18.89" Side Case Height (in.): 24.01" PTO Yoke Height (in.): 18.18"	
	BASE MACHINE	
04D1XF	FL1163 - 63" FLAIL MOWER (SIDE SHIFT)	USD \$6,000.00
	DESTINATION AND LANGUAGE	
	Basic Factory Options	
	DESTINATION	
0202	United States	No Added Cost
	OPERATOR'S MANUAL AND DECALS	
0409	English	No Added Cost
0413	French	No Added Cost
0437	Spanish	No Added Cost
	HYDRAULICS	
	Field Installed Options	
	HYDRAULICS	
9800	Hydraulic Adjustment Kit	USD \$455.00



FL1169 - 69" FLAIL MOWER (SIDE SHIFT)

Code	Description	List price
04E1XF	FL1169 - 69" FLAIL MOWER (SIDE SHIFT)	
	<p>Dimensions</p> <p>Capacity, Cutting (in.): 1.5"</p> <p>Height, Cutting (in.): 0.98" /1.96" /2.99"</p> <p>Height, Overall (in.): 36.5"</p> <p>Length, Overall (in.): 44.3"</p> <p>Width, Cutting (in): 69"</p> <p>Width, Overall (in.): 74.76"</p> <p>Weight (lbs.): 749 lbs.</p> <p>Compatibility</p> <p>Tractor HP Required (min. - max.): 35 - 55HP</p> <p>Tractor Weight MINIMUM (lbs.): 2600 lbs.</p> <p>COG (in): 25"</p> <p>Hitch</p> <p>Hitch Type: 3-point</p> <p>iMatch Compatible: No</p> <p>Hitch Category: 1</p> <p>Hitch Position: Centered</p> <p>Offset Range: Left of Center (11"-33"), Right of Center (36"-52")</p> <p>Hydraulic Offset: No</p> <p>Blades</p> <p>Blade Type: Hammers (std); Y-Blade (service)</p> <p>Number of Hammers: 24</p> <p>Type of Blades/ Hammers: 18 / 20</p> <p>Blade Tip Speed (ft/min): 8937</p> <p>Rotor</p> <p>Rotor Diameter (in.): 5"</p> <p>Rotor Speed (rpm): 2278 rpm</p> <p>Rotor Thickness (mm.): 8 mm.</p> <p>Rotor Work Diameter (in.): 15"</p> <p>Rotor Bearing Type: SPHERICAL ROLLER 22207</p> <p>Drives</p> <p>Gear Box Speed (rpm): 540 rpm</p> <p>Drive Belts: 3 - SPB Lp=1320</p> <p>Gauge Roller Diameter (in.): 5.5"</p> <p>Other</p> <p>Hydraulic Quick Coupler Size (in.): 1/2"</p> <p>Frame Thickness (mm.): 3 mm.</p> <p>Side Frame Thickness (mm.): 5 mm.</p>	



FL1169 - 69" FLAIL MOWER (SIDE SHIFT)

Code	Description	List price
	Roller Bearing Diameter (in): 2.835" Rear Roller Bearing Type: YAR 207-2FW/VA201 Belt adjustment: Screw adjustment Primary Pulley Diameter (mm.): 225 mm. Secondary Pulley Diameter (mm.): 160 mm. Hood Height (in.): 18.89" Side Case Height (in.): 24.01" PTO Yoke Height (in.): 18.18"	
	BASE MACHINE	
04E1XF	FL1169 - 69" FLAIL MOWER (SIDE SHIFT)	USD \$6,250.00
	DESTINATION AND LANGUAGE Basic Factory Options DESTINATION	
0202	United States	No Added Cost
	OPERATOR'S MANUAL AND DECALS	
0409	English	No Added Cost
0413	French	No Added Cost
0437	Spanish	No Added Cost
	HYDRAULICS Field Installed Options HYDRAULICS	
9800	Hydraulic Adjustment Kit	USD \$455.00



FL1045S - 45" FLAIL MOWER (SIDE OFFSET)

Code	Description	List price
04F1XF	<p>FL1045S - 45" FLAIL MOWER (SIDE OFFSET)</p> <p>Dimensions Capacity, Cutting (in.): 0.79" Height, Cutting (in.): .78" /1.57" /2.36" Height, Overall (in.): 38.7" Length, Overall (in.): 71.2" Width, Cutting (in): 45" Width, Overall (in.): 52.32" Weight (lbs.): 592 lbs.</p> <p>Compatibility Tractor HP Required (min. - max.): 15 - 45HP Tractor Weight MINIMUM (lbs.): 2600 lbs. COG (in): 45.6"</p> <p>Hitch Hitch Type: 3-point iMatch Compatible: No Hitch Category: 1 Hitch Position: Offset Offset Range: Left of Center (21.5"), Fully Extended (68") Hydraulic Offset: Standard</p> <p>Blades Blade Type: Hammers (std); Y-Blade (service) Number of Hammers: 24 Type of Blades/ Hammers: 19 / 21 Blade Tip Speed (ft/min): 8622</p> <p>Rotor Rotor Diameter (in.): 5" Rotor Speed (rpm): 2600 rpm Rotor Thickness (mm.): 8 mm. Rotor Work Diameter (in.): 12.63" Rotor Bearing Type: SPHERICAL ROLLER 22207</p> <p>Drives Gear Box Speed (rpm): 540 rpm Drive Belts: 2 - SPB Lp=1160 Gauge Roller Diameter (in.): 5.5"</p> <p>Other Hydraulic Quick Coupler Size (in.): 1/2" Frame Thickness (mm.): 3 mm.</p>	



FL1045S - 45" FLAIL MOWER (SIDE OFFSET)

Code	Description	List price
	Side Frame Thickness (mm.): 4 mm. Roller Bearing Diameter (in.): 2.4" Rear Roller Bearing Type: D30 D62 B20 2206E 2RS1 Belt adjustment: Screw adjustment Primary Pulley Diameter (mm.): 225 mm. Secondary Pulley Diameter (mm.): 140 mm. Hood Height (in.): 15.35" Side Case Height (in.): 25.2" PTO Yoke Height (in.): 19.29"	
	BASE MACHINE	
04F1XF	FL1045S - 45" FLAIL MOWER (SIDE OFFSET)	USD \$6,750.00
	DESTINATION AND LANGUAGE Basic Factory Options DESTINATION	
0202	United States	No Added Cost
	OPERATOR'S MANUAL AND DECALS	
0409	English	No Added Cost
0413	French	No Added Cost
0437	Spanish	No Added Cost



FL1061S - 61" FLAIL MOWER (SIDE OFFSET)

Code	Description	List price
04K1XF	FL1061S - 61" FLAIL MOWER (SIDE OFFSET)	
	<p>Dimensions</p> <p>Capacity, Cutting (in.): 0.79"</p> <p>Height, Cutting (in.): .78" /1.57" /2.36"</p> <p>Height, Overall (in.): 38.7"</p> <p>Length, Overall (in.): 71.2"</p> <p>Width, Cutting (in): 61"</p> <p>Width, Overall (in.): 68.88"</p> <p>Weight (lbs.): 663 lbs.</p> <p>Compatibility</p> <p>Tractor HP Required (min. - max.): 25 - 45HP</p> <p>Tractor Weight MINIMUM (lbs.): 2600 lbs.</p> <p>COG (in): 45.6"</p> <p>Hitch</p> <p>Hitch Type: 3-point</p> <p>iMatch Compatible: No</p> <p>Hitch Category: 1</p> <p>Hitch Position: Offset</p> <p>Offset Range: Left of Center (21.5"), Fully Extended - (83")</p> <p>Hydraulic Offset: Standard</p> <p>Blades</p> <p>Blade Type: Hammers (std); Y-Blade (service)</p> <p>Number of Hammers: 32</p> <p>Type of Blades/ Hammers: 19 / 21</p> <p>Blade Tip Speed (ft/min): 8622</p> <p>Rotor</p> <p>Rotor Diameter (in.): 5"</p> <p>Rotor Speed (rpm): 2600 rpm</p> <p>Rotor Thickness (mm.): 8 mm.</p> <p>Rotor Work Diameter (in.): 12.63"</p> <p>Rotor Bearing Type: SPHERICAL ROLLER 22207</p> <p>Drives</p> <p>Gear Box Speed (rpm): 540 rpm</p> <p>Drive Belts: 2 - SPB Lp=1160</p> <p>Gauge Roller Diameter (in.): 5.5"</p> <p>Other</p> <p>Hydraulic Quick Coupler Size (in.): 1/2"</p> <p>Frame Thickness (mm.): 3 mm.</p> <p>Side Frame Thickness (mm.): 4 mm.</p>	



FL1061S - 61" FLAIL MOWER (SIDE OFFSET)

Code	Description	List price
	Roller Bearing Diameter (in): 2.4" Rear Roller Bearing Type: D30 D62 B20 2206E 2RS1 Belt adjustment: Screw adjustment Primary Pulley Diameter (mm.): 225 mm. Secondary Pulley Diameter (mm.): 140 mm. Hood Height (in.): 15.35" Side Case Height (in.): 25.2" PTO Yoke Height (in.): 19.29"	
	BASE MACHINE	
04K1XF	FL1061S - 61" FLAIL MOWER (SIDE OFFSET)	USD \$7,180.00
	DESTINATION AND LANGUAGE Basic Factory Options DESTINATION	
0202	United States	No Added Cost
	OPERATOR'S MANUAL AND DECALS	
0409	English	No Added Cost
0413	French	No Added Cost
0437	Spanish	No Added Cost



FL1163S - 63" FLAIL MOWER (SIDE OFFSET)

Code	Description	List price
04M1XF	FL1163S - 63" FLAIL MOWER (SIDE OFFSET)	
	<p>Dimensions</p> <p>Capacity, Cutting (in.): 1.18"</p> <p>Height, Cutting (in.): 0.98" /1.96" /2.99"</p> <p>Height, Overall (in.): 39"</p> <p>Length, Overall (in.): 79.5"</p> <p>Width, Cutting (in): 63"</p> <p>Width, Overall (in.): 77.16"</p> <p>Weight (lbs.): 936 lbs.</p> <p>Compatibility</p> <p>Tractor HP Required (min. - max.): 45 - 75HP</p> <p>Tractor Weight MINIMUM (lbs.): 3700 lbs.</p> <p>COG (in): 45.6"</p> <p>Hitch</p> <p>Hitch Type: 3-point</p> <p>iMatch Compatible: No</p> <p>Hitch Category: 1</p> <p>Hitch Position: Offset</p> <p>Offset Range: Left of Center (12"), Fully Extended - (94.5")</p> <p>Hydraulic Offset: Standard</p> <p>Blades</p> <p>Blade Type: Hammers (std); Y-Blade (service)</p> <p>Number of Hammers: 22</p> <p>Type of Blades/ Hammers: 18 / 20</p> <p>Blade Tip Speed (ft/min): 8937</p> <p>Rotor</p> <p>Rotor Diameter (in.): 5"</p> <p>Rotor Speed (rpm): 2278 rpm</p> <p>Rotor Thickness (mm.): 8 mm.</p> <p>Rotor Work Diameter (in.): 15"</p> <p>Rotor Bearing Type: SPHERICAL ROLLER 22207</p> <p>Drives</p> <p>Gear Box Speed (rpm): 540 rpm</p> <p>Drive Belts: 3 - SPB Lp=1320</p> <p>Gauge Roller Diameter (in.): 5.5"</p> <p>Other</p> <p>Hydraulic Quick Coupler Size (in.): 1/2"</p> <p>Frame Thickness (mm.): 3 mm.</p> <p>Side Frame Thickness (mm.): 5 mm.</p>	



FL1163S - 63" FLAIL MOWER (SIDE OFFSET)

Code	Description	List price
	Roller Bearing Diameter (in): 2.835" Rear Roller Bearing Type: YAR 207-2FW/VA201 Belt adjustment: Screw adjustment Primary Pulley Diameter (mm.): 225 mm. Secondary Pulley Diameter (mm.): 160 mm. Hood Height (in.): 18.89" Side Case Height (in.): 24.01" PTO Yoke Height (in.): 23.62"	
	BASE MACHINE	
04M1XF	FL1163S - 63" FLAIL MOWER (SIDE OFFSET)	USD \$8,310.00
	DESTINATION AND LANGUAGE Basic Factory Options DESTINATION	
0202	United States	No Added Cost
	OPERATOR'S MANUAL AND DECALS	
0409	English	No Added Cost
0413	French	No Added Cost
0437	Spanish	No Added Cost



FL1169S - 69" FLAIL MOWER (SIDE OFFSET)

Code	Description	List price
04N1XF	<p>FL1169S - 69" FLAIL MOWER (SIDE OFFSET)</p> <p>Dimensions Capacity, Cutting (in.): 1.18" Height, Cutting (in.): 0.98" /1.96" /2.99" Height, Overall (in.): 39" Length, Overall (in.): 79.5" Width, Cutting (in): 69" Width, Overall (in.): 83.04" Weight (lbs.): 981 lbs.</p> <p>Compatibility Tractor HP Required (min. - max.): 50 - 75HP Tractor Weight MINIMUM (lbs.): 3700 lbs. COG (in): 45.6"</p> <p>Hitch Hitch Type: 3-point iMatch Compatible: No Hitch Category: 1 Hitch Position: Offset Offset Range: Left of Center (12"), Fully Extended (100") Hydraulic Offset: Standard</p> <p>Blades Blade Type: Hammers (std); Y-Blade (service) Number of Hammers: 24 Type of Blades/ Hammers: 18 / 20 Blade Tip Speed (ft/min): 8937</p> <p>Rotor Rotor Diameter (in.): 5" Rotor Speed (rpm): 2278 rpm Rotor Thickness (mm.): 8 mm. Rotor Work Diameter (in.): 15" Rotor Bearing Type: SPHERICAL ROLLER 22207</p> <p>Drives Gear Box Speed (rpm): 540 rpm Drive Belts: 3 - SPB Lp=1320 Gauge Roller Diameter (in.): 5.5"</p> <p>Other Hydraulic Quick Coupler Size (in.): 1/2" Frame Thickness (mm.): 3 mm.</p>	



FL1169S - 69" FLAIL MOWER (SIDE OFFSET)

Code	Description	List price
	Side Frame Thickness (mm.): 5 mm. Roller Bearing Diameter (in.): 2.835" Rear Roller Bearing Type: YAR 207-2FW/VA201 Belt adjustment: Screw adjustment Primary Pulley Diameter (mm.): 225 mm. Secondary Pulley Diameter (mm.): 160 mm. Hood Height (in.): 18.89" Side Case Height (in.): 24.01" PTO Yoke Height (in.): 23.62"	
	BASE MACHINE	
04N1XF	FL1169S - 69" FLAIL MOWER (SIDE OFFSET)	USD \$8,585.00
	DESTINATION AND LANGUAGE Basic Factory Options DESTINATION	
0202	United States	No Added Cost
	OPERATOR'S MANUAL AND DECALS	
0409	English	No Added Cost
0413	French	No Added Cost
0437	Spanish	No Added Cost



FL1272S - 72" FLAIL MOWER (SIDE OFFSET)

Code	Description	List price
04R1XF	FL1272S - 72" FLAIL MOWER (SIDE OFFSET)	
	<p>Dimensions</p> <p>Capacity, Cutting (in.): 1.57"</p> <p>Height, Cutting (in.): 1.18" /1.96" /3.14"</p> <p>Height, Overall (in.): 45"</p> <p>Length, Overall (in.): 91.4"</p> <p>Width, Cutting (in.): 72"</p> <p>Width, Overall (in.): 94.92"</p> <p>Weight (lbs.): 1484 lbs.</p> <p>Compatibility</p> <p>Tractor HP Required (min. - max.): 40 - 105HP</p> <p>Tractor Weight MINIMUM (lbs.): 5300 lbs.</p> <p>COG (in): 54.7"</p> <p>Hitch</p> <p>Hitch Type: 3-point</p> <p>iMatch Compatible: No</p> <p>Hitch Category: 2</p> <p>Hitch Position: Offset</p> <p>Offset Range: Left of Center (13.5"), Fully Extended (115")</p> <p>Hydraulic Offset: Standard</p> <p>Blades</p> <p>Blade Type: Hammers (std); Y-Blade (service)</p> <p>Number of Hammers: 22</p> <p>Type of Blades/ Hammers: 8 / 10</p> <p>Blade Tip Speed (ft/min): 10039</p> <p>Rotor</p> <p>Rotor Diameter (in.): 5.5"</p> <p>Rotor Speed (rpm): 2354 rpm</p> <p>Rotor Thickness (mm.): 10 mm.</p> <p>Rotor Work Diameter (in.): 16.29"</p> <p>Rotor Bearing Type: SPHERICAL ROLLER 21309</p> <p>Drives</p> <p>Gear Box Speed (rpm): 540 rpm</p> <p>Drive Belts: 3 - SPB Lp=1320</p> <p>Gauge Roller Diameter (in.): 6.62"</p> <p>Other</p> <p>Hydraulic Quick Coupler Size (in.): 1/2"</p>	



FL1272S - 72" FLAIL MOWER (SIDE OFFSET)

Code	Description	List price
	Frame Thickness (mm.): 4 mm. Side Frame Thickness (mm.): 8 mm. Roller Bearing Diameter (in.): 3.15" Rear Roller Bearing Type: D40 D80 B23 62208 2RS2 Belt adjustment: Screw adjustment Primary Pulley Diameter (mm.): 225 mm. Secondary Pulley Diameter (mm.): 160 mm. Hood Height (in.): 19.68" Side Case Height (in.): 24.4" PTO Yoke Height (in.): 23.62"	
	BASE MACHINE	
04R1XF	FL1272S - 72" FLAIL MOWER (SIDE OFFSET)	USD \$11,460.00
	DESTINATION AND LANGUAGE Basic Factory Options DESTINATION	
0202	United States	No Added Cost
	OPERATOR'S MANUAL AND DECALS	
0409	English	No Added Cost
0413	French	No Added Cost
0437	Spanish	No Added Cost



GM1048E Economy Rear Discharge Grooming Mower

Code	Description	List price
0461XF	<p>GM1048E Economy Rear Discharge Grooming Mower</p> <ul style="list-style-type: none"> 4 Rubber Swivel Tires 11 Gauge Reinforced Deck Spindle Shafts Greased from the Top for Easy Service Single Belt Drive with Automatic Belt Idler Rugged 30-HP Gearbox One Piece Balanced Steel Pulleys High Blade Speed Floating Top Hitch iMatch Compatible (Quick-Attach System) Working Width: 48 In. Overall Machine Width: 51 In. Machine Weight: 340 lbs. HP Requirements: 16 - 30 HP Deck Thickness: 11 Gauge Cutting Height from 1 In. to 4 In. Category I Hitch Blade Tip Speed: 13,188 Ft./Minute Type: Rear Discharge Front Antiscalping Roller: Optional Mulching Kit: Optional Rotor RPM: 3,037 RPM Driveline: 1-3/8 In. ASAE Category II Shipping Weight: 398 lbs. Set-up Time: 30 Minute 1 Year Warranty 	
	BASE MACHINE	
0461XF	<p><i>iMatch and iMatch conversion kit ordered separately.</i></p> <p>GM1048E Economy Rear Discharge Grooming Mower</p>	USD \$3,617.00
	DESTINATION AND LANGUAGE	
	Field Installed Options	
	OPERATOR'S MANUAL AND DECALS	
9200	French Operators Manual and Decal Kit (GM10E Series)	No Added Cost
	FRAME	
	Field Installed Options	



GM1048E Economy Rear Discharge Grooming Mower

Code	Description	List price
	ROLLERS	
9450	Front Anti-Scalping Roller	USD \$164.00
	CONVERSION KIT	
9630	I-Match Conversion Kit	USD \$522.00
	CUTTING UNITS	
	Field Installed Options	
	MULCH KITS	
9690	Mulching Kit <i>For GM1048E.</i>	USD \$414.00
	MISCELLANEOUS	
	ATTACHMENTS FOR FIELD CONVERSION	
	MISCELLANEOUS	
BLV11199	John Deere Quik-Knect Driveline Yoke Bundle <i>Tractor Receiver Part number: BLV10953</i>	USD \$300.30
	<i>At least one tractor receiver bundle is needed per tractor. This bundle is removable and can be used on various tractors within the compatibility.</i>	
	<i>One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).</i>	
5BP004600	Mulching Kit (GM1048E)	USD \$500.51
5BP950959B	French Manual Decal (GM10E Series)	USD \$0.00
5BP001600	Front Antiscalping Roller	USD \$180.40
5BP006750	iMatch Conversion Kit <i>Fits GM1048E, GM1060E, and GM1072E. Must also order longer 5BP0500404 driveline from parts for GM1048E or GM1060E.</i>	USD \$662.20



GM1060E Economy Rear Discharge Grooming Mower

Code	Description	List price
0462XF	<p>GM1060E Economy Rear Discharge Grooming Mower</p> <ul style="list-style-type: none"> 4 Rubber Swivel Tires 11 Gauge Reinforced Deck Spindle Shafts Greased from the Top for Easy Service Single Belt Drive with Automatic Belt Idler Rugged 30-HP Gearbox One Piece Balanced Steel Pulleys High Blade Speed Floating Top Hitch iMatch Compatible (Quick-Attach System) Working Width: 60 In. Overall Machine Width: 63 In. Machine Weight: 375 lbs. HP Requirements: 18 - 30 HP Deck Thickness: 11 Gauge Cutting Height from 1 In. to 4 In. Category I Hitch Blade Tip Speed: 14,763 Ft./Minute Type: Rear Discharge Front Antiscalping Roller: Optional Mulching Kit: Optional Rotor RPM: 2,803 RPM Driveline: 1-3/8 In. ASAE Category II Shipping Weight: 470 lbs. Set-up Time: 30 Minute 1 Year Warranty 	
	<p>BASE MACHINE</p>	
	<p><i>iMatch and iMatchconversion kit ordered separately.</i></p>	
0462XF	<p>GM1060E Economy Rear Discharge Grooming Mower</p>	USD \$3,731.00
	<p>DESTINATION AND LANGUAGE</p>	
	<p>Field Installed Options</p>	
	<p>OPERATOR'S MANUAL AND DECALS</p>	
9200	<p>French Operators Manual and Decal Kit (GM10E Series)</p>	No Added Cost
	<p>FRAME</p>	
	<p>Field Installed Options</p>	



GM1060E Economy Rear Discharge Grooming Mower

Code	Description	List price
	ROLLERS	
9450	Front Anti-Scalping Roller	USD \$164.00
	CONVERSION KIT	
9630	I-Match Conversion Kit	USD \$522.00
	CUTTING UNITS	
	Field Installed Options	
	MULCH KITS	
9690	Mulching Kit For GM1060E.	USD \$474.00
	MISCELLANEOUS	
	ATTACHMENTS FOR FIELD CONVERSION	
	MISCELLANEOUS	
BLV11199	John Deere Quik-Knect Driveline Yoke Bundle Tractor Receiver Part number: BLV10953 <i>At least one tractor receiver bundle is needed per tractor. This bundle is removable and can be used on various tractors within the compatibility.</i> <i>One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).</i>	USD \$300.30
5BP005600	Mulching Kit (GM1060E)	USD \$572.00
5BP950959B	French Manual Decal (GM10E Series)	USD \$0.00
5BP001600	Front Antiscalping Roller	USD \$180.40
5BP006750	iMatch Conversion Kit Fits GM1048E, GM1060E, and GM1072E. Must also order longer 5BP0500404 driveline from parts for GM1048E or GM1060E.	USD \$662.20



GM1072E Economy Rear Discharge Grooming Mower

Code	Description	List price
0463XF	<p>GM1072E Economy Rear Discharge Grooming Mower</p> <ul style="list-style-type: none"> 4 Rubber Swivel Tires 11 Gauge Reinforced Deck Spindle Shafts Greased from the Top for Easy Service Single Belt Drive with Automatic Belt Idler Rugged 30-HP Gearbox One Piece Balanced Steel Pulleys High Blade Speed Floating Top Hitch iMatch Compatible (Quick-Attach System) Working Width: 72 In. Overall Machine Width: 74 In. Machine Weight: 440 lbs. HP Requirements: 22 - 30 HP Deck Thickness: 11 Gauge Cutting Height from 1 In. to 4 In. Category I Hitch Blade Tip Speed: 14,566 Ft./Minute Type: Rear Discharge Front Antiscalping Roller: Optional Mulching Kit: Optional Rotor RPM: 2,278 RPM Driveline: 1-3/8 In. ASAE Category II Shipping Weight: 540 lbs. Set-up Time: 30 Minute 1 Year Warranty 	
	BASE MACHINE	
0463XF	<p><i>iMatch and iMatchconversion kit ordered separately.</i></p> <p>GM1072E Economy Rear Discharge Grooming Mower</p>	USD \$4,108.00
	DESTINATION AND LANGUAGE	
	Field Installed Options	
	OPERATOR'S MANUAL AND DECALS	
9200	French Operators Manual and Decal Kit (GM10E Series)	No Added Cost
	FRAME	
	Field Installed Options	



GM1072E Economy Rear Discharge Grooming Mower

Code	Description	List price
	ROLLERS	
9450	Front Anti-Scalping Roller	USD \$164.00
	CONVERSION KIT	
9630	I-Match Conversion Kit	USD \$522.00
	CUTTING UNITS	
	Field Installed Options	
	MULCH KITS	
9690	Mulching Kit <i>For GM1072E.</i>	USD \$514.00
	MISCELLANEOUS	
	ATTACHMENTS FOR FIELD CONVERSION	
	MISCELLANEOUS	
BLV11199	John Deere Quik-Knect Driveline Yoke Bundle <i>Tractor Receiver Part number: BLV10953</i>	USD \$300.30
	<i>At least one tractor receiver bundle is needed per tractor. This bundle is removable and can be used on various tractors within the compatibility.</i>	
	<i>One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).</i>	
5BP006600	Mulching Kit (GM1072E)	USD \$623.71
5BP950959B	French Manual Decal (GM10E Series)	USD \$0.00
5BP001600	Front Antiscalping Roller	USD \$180.40
5BP006750	iMatch Conversion Kit <i>Fits GM1048E, GM1060E, and GM1072E. Must also order longer 5BP0500404 driveline from parts for GM1048E or GM1060E.</i>	USD \$662.20



GM4060E Rear Discharge Grooming Mower

Code	Description	List price
0591XF	<p>GM4060E Rear Discharge Grooming Mower Tractor PTO Horsepower: 15 to 35 HP Type: Rear Discharge Tractor PTO Speed: 540 RPM Operating Weight: 481 lbs. Hitch: Category I Driveline: Category 2 Drive Type: Gearbox Over V-Belt Deck Thickness: 8 Gauge Steel Plate Cutting Width: 60 In. Cutting Height Range: 1 In. to 4.5 In. Cutting Height Adjustment: Spacer On Caster Caster Wheels: (4) 10 In. x 3-1/4 In. Solid Caster Wheel Bearings: Roller Bearings Blade Tip Speed: 18,030 FPM Blade Spindles: 3 Cast Iron Blade Spindle Bearings: Ball Bearings Blade Overlap: 1-1/2 In. Blade Dimensions: (3) 1/4 In. x 2-1/2 In. Blade Composition: Heat-Treated Alloy Steel Belts: B Section, Aramid/Kevlar Belt Adjustment: Spring-Loaded Idler Assembly/Set-Up Time: 15 Minutes (Approximate) Approximate Operating Weight: 503 lbs. Front Roller Kit: Optional</p>	
	BASE MACHINE	
0591XF	GM4060E Rear Discharge Grooming Mower	USD \$3,927.00
	DESTINATION AND LANGUAGE	
	Basic Factory Options	
	DESTINATION	
0202	United States	In Base Price
	OPERATOR'S MANUAL AND DECALS	



GM4060E Rear Discharge Grooming Mower

Code	Description	List price
0409	English OM	In Base Price
0413	French OM & Decal Kit	No Added Cost
0437	Spanish OM & Decal Kit	No Added Cost
MISCELLANEOUS		
Field Installed Options		
MISCELLANEOUS		
9640	Front anti-scalp roller kit	USD \$130.00
9641	Rear anti-scalp roller kit	USD \$80.00
9642	Rear chain shield (60)	USD \$149.00
ATTACHMENTS FOR FIELD CONVERSION		
MISCELLANEOUS		
BLV11178	John Deere Quik-Knect Driveline Yoke Bundle <i>Tractor Receiver Part number: BLV10953</i>	USD \$300.30
<p><i>At least one tractor receiver bundle is needed per tractor. This bundle is removable and can be used on various tractors within the compatibility.</i></p> <p><i>One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).</i></p>		
5WD616079	Front Anti-Scalp Roller Kit	USD \$103.40
5WD616090	SPANISH OM and DECAL KIT	USD \$537.91
5WD618210	Rear Anti-Scalp Roller Kit	USD \$138.60
5WD616076	REAR CHAIN SHIELD - 72" Deck	USD \$205.71
5WD613747	FRENCH OM and DECAL KIT	USD \$525.80
5WD616077	Rear Chain Shield - 60" Deck	USD \$182.60
BLV10953	John Deere Quik Knect™ PTO receiver	USD \$225.50



GM4072E Rear Discharge Grooming Mower

Code	Description	List price
0611XF	<p>GM4072E Rear Discharge Grooming Mower</p> <p>Tractor Horsepower: 20 to 35 HP Type: Rear Discharge Tractor PTO Speed: 540 RPM Shipping Weight: 689 lbs. Mower Deck Gearbox HP: 35 HP Hitch: Category I Gearbox Ratio: 1:1.92 Driveline: Category III Drive Type: Gearbox Over V-Belt Deck Thickness: 8 Gauge Steel Plate Cutting Width: 72 In. Cutting Height Range: 1 In. to 4.5 In. Cutting Height Adjustment: Spacer On Caster Caster Wheels: (4) 10 In. x 3-1/4 In. Solid Caster Wheel Bearings: Roller Bearings Blade Tip Speed: 18,000 FPM Blade Spindles: 3 Cast Iron Blade Spindle Bearings: Ball Bearings Blade Overlap: 1 1/2 In. Blade Dimensions: (3) 1/4 In. x 2-1/2 In. Blade Composition: Heat-Treated Alloy Steel Belts: B Section, Aramid/Kevlar Belt Adjustment: Spring-Loaded Idler Assembly/Set-Up Time: 15 Minutes (Approximate) Approximate Operating Weight: 603 lbs. Front Roller Kit: Optional</p>	
	BASE MACHINE	
0611XF	GM4072E Rear Discharge Grooming Mower	USD \$4,233.00
	<p>DESTINATION AND LANGUAGE</p> <p>Basic Factory Options</p> <p>DESTINATION</p>	



GM4072E Rear Discharge Grooming Mower

Code	Description	List price
0202	United States	In Base Price
OPERATOR'S MANUAL AND DECALS		
0409	English OM	In Base Price
0413	French OM & Decal Kit	No Added Cost
0437	Spanish OM & Decal Kit	No Added Cost
MISCELLANEOUS		
Field Installed Options		
MISCELLANEOUS		
9640	Front anti-scalp roller kit	USD \$130.00
9641	Rear anti-scalp roller kit	USD \$80.00
9643	Rear chain shield (72)	USD \$169.00
ATTACHMENTS FOR FIELD CONVERSION		
MISCELLANEOUS		
BLV11178	John Deere Quik-Knect Driveline Yoke Bundle <i>Tractor Receiver Part number: BLV10953</i>	USD \$300.30
<p><i>At least one tractor receiver bundle is needed per tractor. This bundle is removable and can be used on various tractors within the compatibility.</i></p> <p><i>One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).</i></p>		
5WD616090	SPANISH OM and DECAL KIT	USD \$537.91
5WD618210	Rear Anti-Scalp Roller Kit	USD \$138.60
5WD616076	REAR CHAIN SHIELD - 72" Deck	USD \$205.71
5WD616077	Rear Chain Shield - 60" Deck	USD \$182.60
5WD613747	FRENCH OM and DECAL KIT	USD \$525.80
5WD616079	Front Anti-Scalp Roller Kit	USD \$103.40
BLV10953	John Deere Quik Knect™ PTO receiver	USD \$225.50



FM4012 Flex Wing Grooming Mower

Code	Description	List price
0901XF	<p>FM4012 Flex Wing Grooming Mower</p> <p>Dimensions Working Width (in.) (Max): 12 ft. Working Length (in.) (Max): 11' 8" Transport Dimensions (LxWxH): 11'3" x 7'7" x 10'x3"</p> <p>Weight Operating Weight: 1,999 lbs. Shipping Weight: 2,005 lbs. Operating tongue: 218 lbs. Transport tongue: 384 lbs.</p> <p>Tractor requirements Engine HP Requirements: 540 RPM PTO hp Range: 25-60 PTO HP</p> <p>Gearbox Ratio: 1:2.5 (wing), 1:1.92 (center) Splitter Gearbox: 1:1 Mower Deck Gearbox: 25 hp (wing) 30 hp (center)</p> <p>Drive Type: Gear Box over V-Belt Wing driveline: ASAE Category III Input driveline: ASAE Category III CV</p> <p>Hitch Type: Adjustable Clevis Category (Drawbar): 1 Adjustment: 4 positions iMatch / Quick hitch: Not Applicable</p> <p>Belts Type: B-Section, Kevlar</p> <p>Cutting Cutting Width: 12 ft. Cutting Width, Center deck: 60 in. Cutting Width, Wing deck: 48 in. Cutting Height, Range, in. (cm): 1.5" to 4.5" Cutting Height, Adjustment: .5" increments (spacer)</p> <p>Deck Thickness, gauge: 10 Gauge Overlap: 6" Lift cylinders: 3 x 10" Wing travel, degrees: 20 degrees up and down</p>	



FM4012 Flex Wing Grooming Mower

Code	Description	List price
	Discharge type: Rear Discharge Blades Blade Tip Speed: 17, 900 ft./min (Center Deck) / 18,200 ft./min (Wing Decks) Number of Blades: 9 Blade Spindles: Ductile Iron, lubed for life; Sealed, ball bearing Spindle type: steel Spindle bearings: ball Overlap: Minimum 1.25 in. Dimensions, type 1: (9) .25 x 2.5 In. Tires Transport Tires: 2 ea. 20.5 x 8.8 in. Gauge Wheels Size: 8x3.5 in. Quantity: 10 Type: Solid Rubber Rollers Front and Rear Anti-Scalping Roller: Option (field installed) Lighting and safety Transport Lights: Option (field installed) Auto-Engage Transport Latch: Yes Markings: SMV Rear Chain Shields: Option (field installed) Warranty Warranty Machine Warranty: 1 Year Machine Warranty Spindle Warranty: 1 Year Spindle Warranty Gearbox Warranty: 6 Year Gearbox Warranty	
BASE MACHINE		
0901XF	FM4012 Flex Wing Grooming Mower	USD \$19,125.00
DESTINATION AND LANGUAGE		
Basic Factory Options		
DESTINATION		
0202	United States	In Base Price
OPERATOR'S MANUAL AND DECALS		
0409	English	In Base Price
0413	French	No Added Cost



FM4012 Flex Wing Grooming Mower

Code	Description	List price
0437	Spanish	No Added Cost
	FRAME	
	Field Installed Options	
	CHAIN ENCLOSURES	
9645	Rear Chain Shield	USD \$412.00
	ATTACHMENTS FOR FIELD CONVERSION	
	CHAIN ENCLOSURES	
5WD616077	Rear Chain Shield - 60" Deck <i>Note: Each deck requires (1) - 5WD616077 for center deck and (2) - 5WD626442 for the wing decks.</i>	USD \$182.60
	HYDRAULICS	
	Field Installed Options	
	HYDRAULIC KITS	
9000	Hydraulic Wing Latch Release Kit	USD \$706.00
	ATTACHMENTS FOR FIELD CONVERSION	
	HYDRAULIC KITS	
5WD1029535	Hydraulic Wing Latch Release Kit	USD \$910.80
	LIGHTS	
	Field Installed Options	
	LIGHTING KITS	
9705	Light Bar	USD \$595.00
	MISCELLANEOUS	
	Field Installed Options	
	ROLLERS	
9640	Front Anti-Scalp Roller Kit	USD \$130.00
9641	Rear Anti-Scalp Roller Kit	USD \$80.00
	ATTACHMENTS FOR FIELD CONVERSION	
	ROLLERS	
5WD618210	Rear Anti-Scalp Roller Kit <i>Note: Need to order Qty. 3 if ordering for all decks</i>	USD \$138.60
5WD616079	Front Anti-Scalp Roller Kit <i>Note: Need to order Qty. 3 if ordering for all decks</i>	USD \$103.40



FM4112 Flex Wing Grooming Mower

Code	Description	List price
0911XF	<p>FM4112 Flex Wing Grooming Mower</p> <p>Dimensions Working Width (in.) (Max): 12.1ft (3.7m) Working Length (in.) (Max): 171.3” Transport Dimensions (LxWxH): 166.6 x 87.8 x 74 in</p> <p>Weight Operating Weight: 2811 lbs. Shipping Weight: Shipping Weight: 2819 lbs. Operating tongue: 336 lbs. Transport tongue: 688 lbs.</p> <p>Tractor requirements Engine HP Requirements: Tractor PTO Speed: 540 rpm PTO hp Range: HP Requirements (Min.): 30 hp</p> <p>Gearbox Ratio: 1:1.9 Splitter Gearbox: 100 HP (74.6 kW) Mower Deck Gearbox: 40 HP (29.8 kW)</p> <p>Drive Type: Gearbox over belt Wing driveline: Category 3 Input driveline: Category 4 CV</p> <p>Hitch Type: Drawbar, Swivel Category (Drawbar): 1 or 2 Adjustment: Self-leveling, multi-position iMatch / Quick hitch: Not compatible</p> <p>Belts Type: V-belt Adjustments: Spring Loaded Idler w/ Pivot</p> <p>Cutting Cutting Width: Cutting Width: 12' Cutting Width, Center deck: 60" Cutting Width, Wing deck: 48" Cutting Height, Range, in. (cm): Cutting Height Range (in.) 1.5-5" Cutting Height, Adjustment: 1/2" Spacers on casters</p> <p>Deck Thickness, gauge: 7 gauge Overlap: 6 or 8.75"</p>	



FM4112 Flex Wing Grooming Mower

Code	Description	List price
	<p>Lift cylinders: 3.5 x 10 in. (8.9 x 25.4 cm) Wing travel, degrees: Up 25 and down 15 degrees Discharge type: Rear Blades Blade Tip Speed: Blade Speed: 18,000 (ft./per minute) Number of Blades: Number of Blades: 9 Blade Spindles: Blade Spindles: 9 Spindle type: Cast Iron Spindle bearings: Triple Ball Overlap: 1.5" Dimensions, type 1: 0.25 x 2.5 in (0.6 x 6.4 cm) Composition: Heat Treated - Alloy Steel Tires Transport Wheels: (2) 20.5" x 8.0" - 10 ply Caster Wheels Size: 15" x 6.00" - 6 ply Quantity: 8 Type: Pneumatic Bearings: Powder metal bushing</p> <p>Rollers Front and Rear Anti-Scalping Roller: Option (Field Installed) Lighting and safety Transport Lights: Standard Auto-Engage Transport Latch: Standard Markings: SMV Rear Chain Shields: Optional Warranty Warranty Machine Warranty: 1 Year Machine Warranty Spindle Warranty: 3 Year Spindle Warranty Gearbox Warranty: 10 Year Gearbox Warranty Front and Rear Anti-Scalping Roller: Option (Field Installed) Rear Chain Shield Option: Option (Field Installed) Hydraulic Wing Latch Release Kit: Option (Field Installed)</p>	
	BASE MACHINE	
0911XF	FM4112 Flex Wing Grooming Mower	USD \$25,716.00
	DESTINATION AND LANGUAGE	



FM4112 Flex Wing Grooming Mower

Code	Description	List price
Basic Factory Options		
DESTINATION		
0202	United States	In Base Price
OPERATOR'S MANUAL AND DECALS		
0409	English	In Base Price
0413	French	No Added Cost
0437	Spanish	No Added Cost
FRAME		
Field Installed Options		
CHAIN ENCLOSURES		
9645	Rear Chain Shield	USD \$411.00
ATTACHMENTS FOR FIELD CONVERSION		
CHAIN ENCLOSURES		
5WD616077	Rear Chain Shield - 60" Deck <i>Note: FM4112 requires: (1) 5WD616007 for center deck AND (2) 5WD626442 for the wing decks</i>	USD \$182.60
5WD626442	Rear Chain Shield - 48" <i>FM4112 requires: (2) - 5WD626442 for the wing decks AND (1) - 5WD616077 for the center deck</i>	USD \$225.51
HYDRAULICS		
Field Installed Options		
HYDRAULIC KITS		
9000	Hydraulic Wing Latch Release Kit	USD \$697.00
ATTACHMENTS FOR FIELD CONVERSION		
HYDRAULICS		
5WD1032454	Hydraulic Wing Latch Release Kit	USD \$766.71
MISCELLANEOUS		
Field Installed Options		
ROLLERS		
9640	Front Anti-Scalp Roller Kit	USD \$390.00
9641	Rear Anti-Scalp Roller Kit	USD \$240.00
ATTACHMENTS FOR FIELD CONVERSION		
MISCELLANEOUS		



FM4112 Flex Wing Grooming Mower

Code	Description	List price
5WD618210	Rear Anti-Scalp Roller Kit	USD \$138.60
5WD616079	Front Anti-Scalp Roller Kit	USD \$103.40



FM4115 Flex Wing Grooming Mower

Code	Description	List price
0921XF	<p>FM4115 Flex Wing Grooming Mower</p> <p>Dimensions Working Width (in.) (Max): 15.2ft (4.6m) Working Length (in.) (Max): 182.2” Transport Dimensions (LxWxH): 176.3 x 96.7 x 83.6 in</p> <p>Weight Operating Weight: 3446 lbs. Shipping Weight: Shipping Weight: 3454 lbs. Operating tongue: 336 lbs. Transport tongue: 754 lbs.</p> <p>Tractor requirements Engine HP Requirements: Tractor PTO Speed: 540 rpm PTO hp Range: HP Requirements (Min.): 35 hp</p> <p>Gearbox Ratio: 1:1.9 Splitter Gearbox: 100 HP (74.6 kW) Mower Deck Gearbox: 40 HP (29.8 kW)</p> <p>Drive Type: Gearbox over belt Wing driveline: Category 3 Input driveline: Category 4 CV</p> <p>Hitch Type: Drawbar, Swivel Category (Drawbar): 1 or 2 Adjustment: Self-leveling, multi-position iMatch / Quick hitch: Not compatible</p> <p>Belts Type: V-belt Adjustments: Spring Loaded Idler w/ Pivot</p> <p>Cutting Cutting Width: Cutting Width: 15' Cutting Width, Center deck: 72" Cutting Width, Wing deck: 60" Cutting Height, Range, in. (cm): Cutting Height Range (in.) 1.5-5" Cutting Height, Adjustment: 1/2" Spacers on casters</p> <p>Deck Thickness, gauge: 7 gauge Overlap: 6 or 8.75"</p>	



FM4115 Flex Wing Grooming Mower

Code	Description	List price
	<p>Lift cylinders: 3.5 x 10 in. (8.9 x 25.4 cm) Wing travel, degrees: Up 25 and down 15 degrees Discharge type: Rear Blades Blade Tip Speed: Blade Speed: 18,000 (ft./per minute) Number of Blades: Number of Blades: 9 Blade Spindles: Blade Spindles: 9 Spindle type: Cast Iron Spindle bearings: Triple Ball Overlap: 1.5" Dimensions, type 1: 0.25 x 2.5 in (0.6 x 6.4 cm) Composition: Heat Treated - Alloy Steel Tires Transport Wheels: (2) 20.5" x 8.0" - 10 ply Caster Wheels Size: 18" x 9.50" - 8 ply Quantity: 10 Type: Pneumatic Bearings: Powder metal bushing Rollers Front and Rear Anti-Scalping Roller: Option (Field Installed)</p> <p>Lighting and safety Transport Lights: Standard Auto-Engage Transport Latch: Standard Markings: SMV Rear Chain Shields: Optional Warranty Warranty Machine Warranty: 1 Year Machine Warranty Spindle Warranty: 3 Year Spindle Warranty Gearbox Warranty: 10 Year Gearbox Warranty Front and Rear Anti-Scalping Roller: Option (Field Installed) Rear Chain Shield Option: Option (Field Installed) Hydraulic Wing Latch Release Kit: Option (Field Installed)</p>	
	BASE MACHINE	
0921XF	FM4115 Flex Wing Grooming Mower	USD \$27,658.00
	DESTINATION AND LANGUAGE	



FM4115 Flex Wing Grooming Mower

Code	Description	List price
Basic Factory Options		
DESTINATION		
0202	United States	In Base Price
OPERATOR'S MANUAL AND DECALS		
0409	English	In Base Price
0413	French	No Added Cost
0437	Spanish	No Added Cost
FRAME		
Field Installed Options		
CHAIN ENCLOSURES		
9645	Rear Chain Shield	USD \$466.00
ATTACHMENTS FOR FIELD CONVERSION		
CHAIN ENCLOSURES		
5WD616077	Rear Chain Shield - 60" Deck <i>Note: FM4115 requires: (2) 5WD616077 for wing decks and (1) 5WD616076 for the center deck.</i>	USD \$182.60
5WD616076	REAR CHAIN SHIELD - 72" Deck <i>FM4115 requires: (1) 5WD616076 for the center deck and (2) 5WD616077 for the wing decks.</i>	USD \$205.71
HYDRAULICS		
Field Installed Options		
HYDRAULIC KITS		
9000	Hydraulic Wing Latch Release Kit	USD \$697.00
ATTACHMENTS FOR FIELD CONVERSION		
HYDRAULICS		
5WD1032454	Hydraulic Wing Latch Release Kit	USD \$766.71
MISCELLANEOUS		
Field Installed Options		
ROLLERS		
9640	Front Anti-Scalp Roller Kit	USD \$390.00
9641	Rear Anti-Scalp Roller Kit	USD \$240.00
ATTACHMENTS FOR FIELD CONVERSION		
MISCELLANEOUS		



FM4115 Flex Wing Grooming Mower

Code	Description	List price
5WD616079	Front Anti-Scalp Roller Kit	USD \$103.40
5WD618210	Rear Anti-Scalp Roller Kit	USD \$138.60



FM4117 Flex Wing Grooming Mower

Code	Description	List price
0931XF	<p>FM4117 Flex Wing Grooming Mower</p> <p>Dimensions Working Width (in.) (Max): 17.1ft (5.2m) Working Length (in.) (Max): 182.2” Transport Dimensions (LxWxH): 176.3 x 101.4 x 90.7 in</p> <p>Weight Operating Weight: 3561 lbs. Shipping Weight: Shipping Weight: 3569 lbs. Operating tongue: 342 lbs. Transport tongue: 794 lbs.</p> <p>Tractor requirements Engine HP Requirements: Tractor PTO Speed: 540 rpm PTO hp Range: HP Requirements (Min.): 40 hp</p> <p>Gearbox Ratio: 1:1.9 Splitter Gearbox: 100 HP (74.6 kW) Mower Deck Gearbox: 40 HP (29.8 kW)</p> <p>Drive Type: Gearbox over belt Wing driveline: Category 3 Input driveline: Category 4 CV</p> <p>Hitch Type: Drawbar, Swivel Category (Drawbar): 1 or 2 Adjustment: Self-leveling, multi-position iMatch / Quick hitch: Not compatible</p> <p>Belts Type: V-belt Adjustments: Spring Loaded Idler w/ Pivot</p> <p>Cutting Cutting Width: Cutting Width: 17' Cutting Width, Center deck: 72" Cutting Width, Wing deck: 72" Cutting Height, Range, in. (cm): Cutting Height Range (in.) 1.5-5" Cutting Height, Adjustment: 1/2" Spacers on casters</p> <p>Deck Thickness, gauge: 7 gauge Overlap: 6 or 8.75"</p>	



FM4117 Flex Wing Grooming Mower

Code	Description	List price
	Lift cylinders: 3.5 x 10 in. (8.9 x 25.4 cm) Wing travel, degrees: Up 25 and down 15 degrees Discharge type: Rear Blades Blade Tip Speed: Blade Speed: 18,000 (ft./per minute) Number of Blades: Number of Blades: 9 Blade Spindles: Blade Spindles: 9 Spindle type: Cast Iron Spindle bearings: Triple Ball Overlap: 1.5" Dimensions, type 1: 0.25 x 2.5 in (0.6 x 6.4 cm) Composition: Heat Treated - Alloy Steel Tires Transport Wheels: (2) 20.5" x 8.0" - 10 ply Caster Wheels Size: 18" x 9.50" - 8 ply Quantity: 10 Type: Pneumatic Bearings: Powder metal bushing Rollers Front and Rear Anti-Scalping Roller: Option (Field Installed) Lighting and safety Transport Lights: Standard Auto-Engage Transport Latch: Standard Markings: SMV Rear Chain Shields: Optional Warranty Warranty Machine Warranty: 1 Year Machine Warranty Spindle Warranty: 3 Year Spindle Warranty Gearbox Warranty: 10 Year Gearbox Warranty Front and Rear Anti-Scalping Roller: Option (Field Installed) Rear Chain Shield Option: Option (Field Installed) Hydraulic Wing Latch Release Kit: Option (Field Installed)	
	BASE MACHINE	
0931XF	FM4117 Flex Wing Grooming Mower	USD \$30,672.00
	DESTINATION AND LANGUAGE	
	Basic Factory Options	



FM4117 Flex Wing Grooming Mower

Code	Description	List price
	DESTINATION	
0202	United States	In Base Price
	OPERATOR'S MANUAL AND DECALS	
0409	English	In Base Price
0413	French	No Added Cost
0437	Spanish	No Added Cost
	FRAME	
	Field Installed Options	
	CHAIN ENCLOSURES	
9645	Rear Chain Shield	USD \$505.00
	ATTACHMENTS FOR FIELD CONVERSION	
	CHAIN ENCLOSURES	
5WD616076	REAR CHAIN SHIELD - 72" Deck <i>FM4117 requires: (3) 5WD616076</i>	USD \$205.71
	HYDRAULICS	
	Field Installed Options	
	HYDRAULIC KITS	
9000	Hydraulic Wing Latch Release Kit	USD \$697.00
	ATTACHMENTS FOR FIELD CONVERSION	
	HYDRAULICS	
5WD1032454	Hydraulic Wing Latch Release Kit	USD \$766.71
	MISCELLANEOUS	
	Field Installed Options	
	ROLLERS	
9640	Front Anti-Scalp Roller Kit	USD \$390.00
9641	Rear Anti-Scalp Roller Kit	USD \$240.00
	ATTACHMENTS FOR FIELD CONVERSION	
	MISCELLANEOUS	
5WD618210	Rear Anti-Scalp Roller Kit	USD \$138.60
5WD616079	Front Anti-Scalp Roller Kit	USD \$103.40



GM1190 Rear Discharge Grooming Mower with Chain Shield

Code	Description	List price
0471XF	<p>GM1190 Rear Discharge Grooming Mower with Chain Shield</p> <p>Type: Rear Discharge Tractor PTO Speed: 540 RPM Tractor Horsepower: 25 to 50 HP Shipping Weight: 1347 lbs. Mower Deck Gearbox HP: 50 HP Hitch: Category I Gearbox Ratio: 1:1.69 Driveline: Category IV Drive Type: Gearbox Over (2) V-Belts Deck Thickness: 7 Gauge Steel Plate Cutting Width: 90 In. Cutting Height Range: 1-1/2 In. to 8 In. Cutting Height Adjustment: Adjustable Arm Caster Wheels: (4) 13 In. x 5 In. Solid Caster Wheel Bearings: Tapered Roller Bearings Blade Tip Speed: 15,570 FPM Blade Spindles: 3 Cast Iron Blade Spindle Bearings: Tapered Roller Blade Overlap: 1-1/4 In. Blade Dimensions: (6) 1/4 In. x 2-1/2 In. Blade Composition: Heat-Treated Alloy Steel Belts: Power Band, B Section, Kevlar Belt Adjustment: Spring-Loaded Idler Assembly/Set-Up Time: 45 Minutes (Approximate) Approximate Operating Weight: 1,200 lbs. Front Center Roller Kit: Optional</p>	
	BASE MACHINE	
	<i>iMatch and iMatch conversion kit ordered separately.</i>	
0471XF	GM1190 Rear Discharge Grooming Mower with Chain Shield	USD \$8,195.00
	FRAME	



GM1190 Rear Discharge Grooming Mower with Chain Shield

Code	Description	List price
Field Installed Options		
CONVERSION KIT		
9000	iMatch Conversion Kit <i>Excludes economy series.</i>	USD \$245.00
ROLLERS		
9010	Front Roller Kit <i>Contains 1 roller.</i>	USD \$170.00
WHEELS AND TIRES		
Basic Factory Options		
WHEELS AND TIRES		
3000	Pneumatic Tires	No Added Cost
3010	Solid Tires	In Base Price
MISCELLANEOUS		
ATTACHMENTS FOR FIELD CONVERSION		
MISCELLANEOUS		
5WD1032828	Front Roller Kit - Contains 1 Roller (GM1190) <i>Serial Number 1XFGM11XKB0000121 and above.</i>	USD \$218.91
5WD1032830	iMatch Conversion Kit <i>For GM1190. Serial Number 1XFGM11XKB0000121 and above.</i>	USD \$317.91
5WD1005400	iMatch Conversion Kit <i>For GM1190. Serial Number 1XFGM11XKB0000120 and below.</i>	USD \$378.42



GM2109R Rear Discharge Grooming Mower with Rear Chain Shields and Front Antiscalping Roller

Code	Description	List price
0491XF	<p>GM2109R Rear Discharge Grooming Mower with Rear Chain Shields and Front Antiscalping Roller</p> <p>Free Swinging Kick Back Blades Double Belt Drive with No Idler One Piece Balanced Steel Pulleys iMatch Compatible (Quick-Attach System) 4 Swivel Tires - Solid or Pneumatic Type: Rear Discharge Tractor PTO Speed: 540 RPM Tractor Horsepower: 30 to 70 HP Shipping Weight: 1608 lbs. Mower Deck Gearbox HP: 70 HP Hitch: Category I Gearbox Ratio: 1:2:08 Driveline: 1-3/8 In. ASAE Category III Drive Type: Gearbox Over V/Belt Deck Thickness: 8 Gauge Reinforced Deck Cutting Width: 110 In. Cutting Height Range: From 1.3 In. to 5.3 In. Cutting Height Adjustment: Spacer On Caster Caster Wheels: (4) 12 In. x 4 In. Solid or 13 In. x 6.5 In. (4 Ply, with Tubes) Air Caster Wheel Bearings: Shielded Roller Bearings Blade Tip Speed: 14,998 FPM Blade Spindles: (3) Cast Iron Blade Spindle Bearings: Shielded Tapered Bearings (2) Per Spindle Blade Composition: Heat-Treated Alloy Steel Blade Overlap: 1-1/8 In. Blade Dimensions: (6) 15-7/8 In. x 2-3/4 In. x 1/4 In.</p>	



GM2109R Rear Discharge Grooming Mower with Rear Chain Shields and Front Antiscalping Roller

Code	Description	List price
	Belts: CX, Polyester/Cogged Belt Adjustment: Single Point, Slotted Track Adjustment - No Idlers Assembly/Set-Up Time: 30 Minutes (Approximate) Approximate Operating Weight: 1490 lbs. Front Center Roller Kit: Standard 1 Year Warranty	
	BASE MACHINE	
0491XF	<i>iMatch and iMatchconversion kit ordered separately.</i> GM2109R Rear Discharge Grooming Mower with Rear Chain Shields and Front Antiscalping Roller	USD \$10,773.00
	FRAME	
	Field Installed Options	
	CONVERSION KIT	
9630	I-Match Conversion Kit	USD \$471.00
	WHEELS AND TIRES	
	Basic Factory Options	
	WHEELS AND TIRES	
3050	Solid Gauge Wheel Tires	In Base Price
3040	Pneumatic Gauge Wheel Tires	USD \$230.00
	MISCELLANEOUS	
	ATTACHMENTS FOR FIELD CONVERSION	
	MISCELLANEOUS	
BLV11178	John Deere Quik-Knect Driveline Yoke Bundle <i>Tractor Receiver Part number: BLV10953</i>	USD \$300.30
	<i>At least one tractor receiver bundle is needed per tractor. This bundle is removable and can be used on various tractors within the compatibility.</i>	
	<i>One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).</i>	
5BP002800	iMatch Conversion Kit	USD \$572.00



GM2190R Rear Discharge Grooming Mower with Rear Chain Shields and Front Antiscalping Roller

Code	Description	List price
0492XF	<p>GM2190R Rear Discharge Grooming Mower with Rear Chain Shields and Front Antiscalping Roller</p> <p>Free Swinging Kick Back Blades Double Belt Drive with No Idler One Piece Balanced Steel Pulleys iMatch Compatible (Quick-Attach System) 4 Swivel Tires - Solid or Pneumatic Type: Rear Discharge Tractor PTO Speed: 540 RPM Tractor Horsepower: 30 to 70 HP Shipping Weight: 1198 lbs. Mower Deck Gearbox HP: 70 HP Hitch: Category I Gearbox Ratio: 1:2:08 Driveline: 1-3/8 In. ASAE Category III Drive Type: Gearbox Over V/Belt Deck Thickness: 8 Gauge Reinforced Deck Cutting Width: 90 In. Cutting Height Range: From 1.3 In. to 5.3 In. Cutting Height Adjustment: Spacer On Caster Caster Wheels: (4) 12 In. x 4 In. Solid or 13 In. x 6.5 In. (4 Ply, with Tubes) Air Caster Wheel Bearings: Shielded Roller Bearings Blade Tip Speed: 14,106 FPM Blade Spindles: (3) Cast Iron Blade Spindle Bearings: Shielded Tapered Bearings (2) Per Spindle Blade Composition: Heat-Treated Alloy Steel Blade Overlap: 1-3/8 In. Blade Dimensions: (6) 13 In. x 2-3/4 In. x 1/4 In.</p>	



GM2190R Rear Discharge Grooming Mower with Rear Chain Shields and Front Antiscalping Roller

Code	Description	List price
	Belts: CX, Polyester/Cogged Belt Adjustment: Single Point, Slotted Track Adjustment - No Idlers Assembly/Set-Up Time: 30 Minutes (Approximate) Approximate Operating Weight: 1102 lbs. Front Center Roller Kit: Standard 1 Year Warranty	
	BASE MACHINE	
0492XF	<i>iMatch and iMatchconversion kit ordered separately.</i> GM2190R Rear Discharge Grooming Mower with Rear Chain Shields and Front Antiscalping Roller	USD \$9,221.00
	FRAME	
	Field Installed Options	
	CONVERSION KIT	
9630	I-Match Conversion Kit	USD \$471.00
	WHEELS AND TIRES	
	Basic Factory Options	
	WHEELS AND TIRES	
3050	Solid Gauge Wheel Tires	In Base Price
3040	Pneumatic Gauge Wheel Tires	USD \$230.00
	MISCELLANEOUS	
	ATTACHMENTS FOR FIELD CONVERSION	
	MISCELLANEOUS	
BLV11178	John Deere Quik-Knect Driveline Yoke Bundle <i>Tractor Receiver Part number: BLV10953</i>	USD \$300.30
	<i>At least one tractor receiver bundle is needed per tractor. This bundle is removable and can be used on various tractors within the compatibility.</i>	
	<i>One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).</i>	
5BP002800	iMatch Conversion Kit	USD \$572.00



GM2060R Rear Discharge Grooming Mower with Rear Chain Shields

Code	Description	List price
0481XF	<p>GM2060R Rear Discharge Grooming Mower with Rear Chain Shields</p> <p>High Blade Speed iMatch Compatible (Quick-Attach System) 4 Swivel Tires - Solid or Pneumatic Spindle Shafts Greased from the Top for Easy Service 20 to 50 HP Type: Rear Discharge Tractor PTO Speed: 540 RPM Shipping Weight: 609 lbs. Mower Deck Gearbox HP: 50 HP Hitch: Category I Gearbox Ratio: 1:3:09 (Spiral Gears) Driveline: 1-3/8 In. ASAE Category III Drive Type: Gear Box over V/Belt Deck Thickness: 8 Gauge Reinforced Deck Cutting Width: 60 In. Cutting Height Range: 1 In. to 5 In. Cutting Height Adjustment: Spacer On Caster Caster Wheels: (4) 10 In. x 3.2 In. Solid or 11 In. x 4 In. (4 Ply, with Tubes) Pneumatic Caster Wheel Bearings: Shielded Roller Bearings Blade Tip Speed: 16,929 FPM Blade Spindles: 3 Cast Iron Blade Spindle Bearings: Shielded Ball Bearings (2) Per Spindle Blade Composition: Heat-Treated Alloy Steel Blade Overlap: 1-1/8 In. Blade Dimensions: (3) 20-3/16 In. x 2 In. x 1/4 In. Belts: 5VX, Polyester/Cogged</p>	



GM2060R Rear Discharge Grooming Mower with Rear Chain Shields

Code	Description	List price
	Belt Adjustment: Single Point, Slotted Track Adjustment - No Idlers Front Roller Kit: Optional Assembly/Set-Up Time: 30 Minutes (Approximate) Approximate Operating Weight: 550 lbs. Mulching Kit Available 1 Year Warranty	
	BASE MACHINE	
0481XF	<i>iMatch and iMatchconversion kit ordered separately.</i> GM2060R Rear Discharge Grooming Mower with Rear Chain Shields	USD \$4,984.00
	FRAME	
	Field Installed Options	
	ROLLERS	
9450	Front Anti-Scalping Roller	USD \$186.00
	CONVERSION KIT	
9630	I-Match Conversion Kit	USD \$471.00
	CUTTING UNITS	
	Field Installed Options	
	MULCH KITS	
9690	Mulching Kit <i>GM2060</i>	USD \$479.00
	WHEELS AND TIRES	
	Basic Factory Options	
	WHEELS AND TIRES	
3050	Solid Gauge Wheel Tires	In Base Price
3040	Pneumatic Gauge Wheel Tires	USD \$97.00
	MISCELLANEOUS	
	ATTACHMENTS FOR FIELD CONVERSION	
	MISCELLANEOUS	
BLV11200	John Deere Quik-Knect Driveline Yoke Bundle <i>Tractor Receiver Part number: BLV10953</i> <i>At least one tractor receiver bundle is needed per tractor.</i>	USD \$300.30



GM2060R Rear Discharge Grooming Mower with Rear Chain Shields

Code	Description	List price
	<i>This bundle is removable and can be used on various tractors within the compatibility.</i>	
	<i>One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).</i>	
5BP045700	Mulching Kit (GM2060)	USD \$578.60
5BP0099915	Front Antiscalping Roller	USD \$225.51
5BP002800	iMatch Conversion Kit	USD \$572.00



GM2072R Rear Discharge Grooming Mower with Rear Chain Shields

Code	Description	List price
0482XF	<p>GM2072R Rear Discharge Grooming Mower with Rear Chain Shields</p> <p>Spindle Shafts Greased from the Top for Easy Service iMatch Compatible (Quick-Attach System) 4 Swivel Tires - Solid or Pneumatic Type: Rear Discharge Tractor PTO Speed: 540 RPM Tractor Horsepower: 20 to 50 HP Shipping Weight: 676 lbs. Mower Deck Gearbox HP: 50 HP Hitch: Category I Gearbox Ratio: 1:3:09 (Spiral Gears) Driveline: Category III Drive Type: Gearbox Over V-Belt Deck Thickness: 8 Gauge Steel Plate Cutting Width: 72 In. Cutting Height Range: 1 In. to 5 In. Cutting Height Adjustment: Spacer on Caster Caster Wheels: (4) 10 In. x 3.2 In. Solid or 11 In. x 4 In. (4 Ply, with Tubes) Pneumatic Caster Wheel Bearings: Shielded Roller Bearings Blade Tip Speed: 16,732 FPM Blade Spindles: 3 Cast Iron Blade Spindle Bearings: Shielded Ball Bearings (2) Per Spindle Blade Composition: Heat-Treated Alloy Steel Blade Overlap: 1-1/8 In. Blade Dimensions: (3) 24-1/2 In. x 2-1/4 In. x 1/4 In. Belts: 5VX, Polyester/Cogged Belt Adjustment: Single Point, Slotted Track Adjustment - No Idlers Front Roller Kit: Optional</p>	



GM2072R Rear Discharge Grooming Mower with Rear Chain Shields

Code	Description	List price
	<p>Assembly/Set-Up Time: 30 Minutes (Approximate) Approximate Operating Weight: 600 lbs. Mulching Kit Available 1 Year Warranty</p>	
0482XF	<p>BASE MACHINE <i>iMatch and iMatchconversion kit ordered separately.</i> GM2072R Rear Discharge Grooming Mower with Rear Chain Shields</p>	USD \$5,384.00
9450	<p>FRAME Field Installed Options ROLLERS Front Anti-Scalping Roller</p>	USD \$186.00
9630	<p>CONVERSION KIT I-Match Conversion Kit</p>	USD \$471.00
9690	<p>CUTTING UNITS Field Installed Options MULCH KITS Mulching Kit GM2072</p>	USD \$557.00
3050	<p>WHEELS AND TIRES Basic Factory Options WHEELS AND TIRES Solid Gauge Wheel Tires</p>	In Base Price
3040	<p>Pneumatic Gauge Wheel Tires</p>	USD \$97.00
BLV11200	<p>MISCELLANEOUS ATTACHMENTS FOR FIELD CONVERSION MISCELLANEOUS John Deere Quik-Knect Driveline Yoke Bundle <i>Tractor Receiver Part number: BLV10953</i></p> <p><i>At least one tractor receiver bundle is needed per tractor. This bundle is removable and can be used on various tractors within the compatibility.</i></p>	USD \$300.30



GM2072R Rear Discharge Grooming Mower with Rear Chain Shields

Code	Description	List price
	<i>One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).</i>	
5BP046700	Mulching Kit (GM2072)	USD \$673.20
5BP0099915	Front Antiscalping Roller	USD \$225.51
5BP002800	iMatch Conversion Kit	USD \$572.00



GM2084R Rear Discharge Grooming Mower with Rear Chain Shields and Front Antiscaling Roller

Code	Description	List price
0483XF	<p>GM2084R Rear Discharge Grooming Mower with Rear Chain Shields and Front Antiscaling Roller</p> <p>Three High-Suction Blades Standard iMatch Compatible (Quick-Attach System) 4 Swivel Tires - Solid or Pneumatic Spindle Shafts Greased from the Top for Easy Service Type: Rear Discharge Tractor PTO Speed: 540 RPM Tractor Horsepower: 25 to 50 HP Shipping Weight: 769 lbs. Mower Deck HP: 50 HP Hitch: Category I Gearbox Ratio: 1:3:09 (Spiral Gears) Driveline: 1-3/8 In. ASAE Category III Drive Type: Gearbox Over V/Belt Deck Thickness: 8 Gauge Reinforced Deck Cutting Width: 84 In. Cutting Height Range: 1 In. to 5 In. Cutting Height Adjustment: Spacer On Caster Caster Wheels: (4) 10 In. x 3.2 In. Solid or 11 In. x 4 In. (4 Ply, with Tubes) Pneumatic Caster Wheel Bearings: Shielded Roller Bearings Blade Tip Speed: 16,338 FPM Blade Spindles: 3 Cast Iron Blade Spindle Bearings: Shielded Ball Bearings (2) Per Spindle Blade Composition: Heat-Treated Alloy Steel Blade Overlap: 1-1/2 In. Blade Dimensions: (3) 28-1/2 In. x 2-1/4 In. Belts: 5VX, Polyester/Cogged</p>	



GM2084R Rear Discharge Grooming Mower with Rear Chain Shields and Front Antiscalping Roller

Code	Description	List price
	Belt Adjustment: Single Point, Slotted Track Adjustment - No Idlers Front Roller Kit: Standard Assembly/Set-Up Time: 30 Minutes (Approximate) Approximate Operating Weight: 690 lbs. Mulching Kit Available 1 Year Warranty	
	BASE MACHINE	
0483XF	<i>iMatch and iMatchconversion kit ordered separately.</i> GM2084R Rear Discharge Grooming Mower with Rear Chain Shields and Front Antiscalping Roller	USD \$6,118.00
	FRAME	
	Field Installed Options	
	CONVERSION KIT	
9630	I-Match Conversion Kit	USD \$471.00
	CUTTING UNITS	
	Field Installed Options	
	MULCH KITS	
9690	Mulching Kit <i>GM2084</i>	USD \$649.00
	WHEELS AND TIRES	
	Basic Factory Options	
	WHEELS AND TIRES	
3050	Solid Gauge Wheel Tires	In Base Price
3040	Pneumatic Gauge Wheel Tires	USD \$97.00
	MISCELLANEOUS	
	ATTACHMENTS FOR FIELD CONVERSION	
	MISCELLANEOUS	
BLV11200	John Deere Quik-Knect Driveline Yoke Bundle <i>Tractor Receiver Part number: BLV10953</i> <i>At least one tractor receiver bundle is needed per tractor. This bundle is removable and can be used on various tractors within the compatibility.</i>	USD \$300.30



GM2084R Rear Discharge Grooming Mower with Rear Chain Shields and Front Antiscalping Roller

Code	Description	List price
	<i>One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).</i>	
5BP047700	Mulching Kit (GM2084)	USD \$785.40
5BP002800	iMatch Conversion Kit	USD \$572.00



GM4060 Rear Discharge Grooming Mower

Code	Description	List price
0601XF	GM4060 Rear Discharge Grooming Mower	
	Tractor PTO Horsepower: 15 to 35 HP Type: Rear Discharge Tractor PTO Speed: 540 RPM Operating Weight: 481 lbs. Hitch: Category I iMatch Quick Hitch: Factory Ready Driveline: Category 3 Drive Type: Gearbox Over V-Belt Deck Thickness: 10 Gauge Steel Plate Cutting Width: 60 In. Cutting Height Range: 1.5 in. to 5 In. Cutting Height Adjustment: Spacer On Caster Caster Wheels: (4) 8 In. x 3-1/4 In. Solid Caster Wheel Bearings: Roller Bearings Blade Tip Speed: 17,900 FPM Blade Spindles: 3 Cast Iron Blade Spindle Bearings: Greaseless Sealed Bearings Blade Overlap: 1-1/4 In. Blade Dimensions: (3) 1/4 In. x 2-1/2 In. Blade Composition: Heat-Treated Alloy Steel Belts: B Section, Aramid/Kevlar Belt Adjustment: Spring-Loaded Idler Assembly/Set-Up Time: 30 Minutes (Approximate) Front Roller Kit: Optional Rear Roller Kit: Optional Chain Guard: Optional	
	BASE MACHINE	
0601XF	GM4060 Rear Discharge Grooming Mower	USD \$5,188.00
	DESTINATION AND LANGUAGE	
	Basic Factory Options	
	DESTINATION	



GM4060 Rear Discharge Grooming Mower

Code	Description	List price
0202	United States	In Base Price
OPERATOR'S MANUAL AND DECALS		
0409	English OM	In Base Price
0413	French OM & Decal Kit	No Added Cost
0437	Spanish OM & Decal Kit	No Added Cost
ATTACHMENTS FOR FIELD CONVERSION		
OPERATOR'S MANUAL AND DECALS		
5WD616090	SPANISH OM and DECAL KIT	USD \$537.91
5WD613747	FRENCH OM and DECAL KIT	USD \$525.80
MISCELLANEOUS		
Field Installed Options		
MISCELLANEOUS		
9640	Front anti-scalp roller kit	USD \$130.00
9641	Rear anti-scalp roller kit	USD \$80.00
9642	Rear chain shield (60)	USD \$149.00
ATTACHMENTS FOR FIELD CONVERSION		
MISCELLANEOUS		
BLV11178	John Deere Quik-Knect Driveline Yoke Bundle	USD \$300.30
5WD618210	Rear Anti-Scalp Roller Kit	USD \$138.60
5WD616079	Front Anti-Scalp Roller Kit	USD \$103.40
5WD616077	Rear Chain Shield - 60" Deck	USD \$182.60
BLV10953	John Deere Quik Knect™ PTO receiver	USD \$225.50



GM4072 Rear Discharge Grooming Mower

Code	Description	List price
0621XF	GM4072 Rear Discharge Grooming Mower Tractor PTO Horsepower: 25 to 35 HP Type: Rear Discharge Tractor PTO Speed: 540 RPM Operating Weight: 538 lbs. Hitch: Category I iMatch Quick Hitch: Factory Ready Driveline: Category 3 Drive Type: Gearbox Over V-Belt Deck Thickness: 10 Gauge Steel Plate Cutting Width: 72 In. Cutting Height Range: 1.5 In. to 5 In. Cutting Height Adjustment: Spacer On Caster Caster Wheels: (4) 8 In. x 3-1/4 In. Solid Caster Wheel Bearings: Roller Bearings Blade Tip Speed: 18,000 FPM Blade Spindles: 3 Cast Iron Blade Spindle Bearings: Greaseless Sealed Bearings Blade Overlap: 1 1/4 In. Blade Dimensions: (3) 1/4 In. x 2-1/2 In. Blade Composition: Heat-Treated Alloy Steel Belts: B Section, Aramid/Kevlar Belt Adjustment: Spring-Loaded Idler Assembly/Set-Up Time: 30 Minutes (Approximate) Front Roller Kit: Optional Rear Roller Kit: Optional Chain Guard: Optional	
	BASE MACHINE	
0621XF	GM4072 Rear Discharge Grooming Mower	USD \$5,420.00
	DESTINATION AND LANGUAGE	
	Basic Factory Options	
	DESTINATION	



GM4072 Rear Discharge Grooming Mower

Code	Description	List price
0202	United States	In Base Price
OPERATOR'S MANUAL AND DECALS		
0409	English OM	In Base Price
0413	French OM & Decal Kit	No Added Cost
0437	Spanish OM & Decal Kit	No Added Cost
ATTACHMENTS FOR FIELD CONVERSION		
OPERATOR'S MANUAL AND DECALS		
5WD616090	SPANISH OM and DECAL KIT	USD \$537.91
5WD613747	FRENCH OM and DECAL KIT	USD \$525.80
MISCELLANEOUS		
Field Installed Options		
MISCELLANEOUS		
9640	Front anti-scalp roller kit	USD \$130.00
9641	Rear anti-scalp roller kit	USD \$80.00
9643	Rear chain shield (72)	USD \$169.00
ATTACHMENTS FOR FIELD CONVERSION		
MISCELLANEOUS		
BLV11178	John Deere Quik-Knect Driveline Yoke Bundle	USD \$300.30
5WD616079	Front Anti-Scalp Roller Kit	USD \$103.40
5WD616076	REAR CHAIN SHIELD - 72" Deck	USD \$205.71
5WD618210	Rear Anti-Scalp Roller Kit	USD \$138.60
BLV10953	John Deere Quik Knect™ PTO receiver	USD \$225.50



GM4084 Rear Discharge Grooming Mower

Code	Description	List price
0631XF	<p>GM4084 Rear Discharge Grooming Mower</p> <p>Tractor PTO Horsepower: 25 to 35 HP Type: Rear Discharge Tractor PTO Speed: 540 RPM Operating Weight: 538 lbs. Hitch: Category I iMatch Quick Hitch: Factory Ready Driveline: Category 3 Drive Type: Gearbox Over V-Belt Deck Thickness: 10 Gauge Steel Plate Cutting Width: 72 In. Cutting Height Range: 1.5 In. to 5 In. Cutting Height Adjustment: Spacer On Caster Caster Wheels: (4) 8 In. x 3-1/4 In. Solid Caster Wheel Bearings: Roller Bearings Blade Tip Speed: 18,000 FPM Blade Spindles: 3 Cast Iron Blade Spindle Bearings: Greaseless Sealed Bearings Blade Overlap: 1 1/4 In. Blade Dimensions: (3) 1/4 In. x 2-1/2 In. Blade Composition: Heat-Treated Alloy Steel Belts: B Section, Aramid/Kevlar Belt Adjustment: Spring-Loaded Idler Assembly/Set-Up Time: 30 Minutes (Approximate) Front Roller Kit: Optional Rear Roller Kit: Optional Chain Guard: Optional</p>	
	BASE MACHINE	
0631XF	GM4084 Rear Discharge Grooming Mower	USD \$6,196.00
	<p>DESTINATION AND LANGUAGE</p> <p>Basic Factory Options</p> <p>DESTINATION</p>	



GM4084 Rear Discharge Grooming Mower

Code	Description	List price
0202	United States	In Base Price
OPERATOR'S MANUAL AND DECALS		
0409	English OM	In Base Price
0413	French OM & Decal Kit	No Added Cost
0437	Spanish OM & Decal Kit	No Added Cost
ATTACHMENTS FOR FIELD CONVERSION		
OPERATOR'S MANUAL AND DECALS		
5WD613747	FRENCH OM and DECAL KIT	USD \$525.80
5WD616090	SPANISH OM and DECAL KIT	USD \$537.91
MISCELLANEOUS		
Field Installed Options		
MISCELLANEOUS		
9640	Front anti-scalp roller kit	USD \$130.00
9641	Rear anti-scalp roller kit	USD \$80.00
9644	Rear chain shield (84)	USD \$193.00
ATTACHMENTS FOR FIELD CONVERSION		
MISCELLANEOUS		
BLV11178	John Deere Quik-Knect Driveline Yoke Bundle	USD \$300.30
5WD616079	Front Anti-Scalp Roller Kit	USD \$103.40
5WD618210	Rear Anti-Scalp Roller Kit	USD \$138.60
BLV10953	John Deere Quik Knect™ PTO receiver	USD \$225.50
5WD616078	REAR CHAIN SHIELD (84)	USD \$235.40



Material Collection System - 14-Bu 3-Bag

Code	Description	List price
0721XF	Material Collection System - 14-Bu 3-Bag 14-BU 3-BAG Material Collection System 3-Bag Collection Hopper Capacity: 14 Bushels Hitch: CAT I 3-point Mounted iMatch Compatible Rear PTO Gearbox Driven Blower 5 Blade High Efficiency Synthetic 15" Impeller Impeller Speed: 2250 RPM Steel Impeller Housing Boot to Blower Hose Diameter: 8 inches Bag Material: Frame Material: Sight Glass Fill Indicator or Wireless Fill Alarm Sensor Option High Efficiency Blow Molded Inducer and Transition Chute Easy-To-Empty Bags Fully and Evenly Filled Bags Tool-less access to chute for easy clog removal Tool-less boot removal and installation for quick changing of implements	
	BASE MACHINE	
0721XF	Material Collection System - 14-Bu 3-Bag	USD \$3,885.00
	DESTINATION AND LANGUAGE	
	Basic Factory Options	
	DESTINATION	
0202	United States	No Added Cost
0184	Canada	No Added Cost
0205	Quebec, Canada	No Added Cost
	OPERATOR'S MANUAL	
0409	English OM	No Added Cost
0413	French OM	No Added Cost
0437	Spanish OM	No Added Cost
	DECK BOOT	
	Basic Factory Options	
	DECK BOOT	
	<i>Includes boot, hardware, and hose</i>	



Material Collection System - 14-Bu 3-Bag

Code	Description	List price
2963	54D DECK BOOT KIT (MY19 and Older) <i>Only Available with 2551 Electric DFS</i>	USD (\$41.00)
2964	54D DECK BOOT KIT (MY20+) <i>Only Available with 2551 Electric DFS</i>	USD (\$52.00)
2962	60D DECK BOOT KIT	No Added Cost
MISCELLANEOUS		
Additional Factory Options		
MISCELLANEOUS		
9702	Fill Sensor (Wireless)	USD \$146.00
9315	Caster Wheel Storage Kit	USD \$58.00
9701	Road Lighting Kit (1E, 1R, 2R) <i>Note: Includes ROPS light extension brackets and extension harnesses, SMV</i>	USD \$198.00
ATTACHMENTS FOR FIELD CONVERSION		
MISCELLANEOUS		
5CS1020	ROAD LIGHT KIT - 3R	USD \$523.60
5CS1011	60D BOOT KIT	USD \$415.80
5CS1007	SPANISH OM & DECAL KIT - MC2014	USD \$201.31
5CS1009	54D BOOT KIT (MY19 AND OLDER)	USD \$401.51
5CS1010	54D BOOT KIT (MY20+)	USD \$386.11
5CS1018	CASTER WHEEL STORAGE KIT	USD \$63.80



Material Collection System - 20-Bu Dump from Seat

Code	Description	List price
0731XF	Material Collection System - 20-Bu Dump from Seat 20-BU Dump from Seat - Material Collection System Aluminum Hopper Capacity: 20 Bushels Hitch: CAT I 3-point Mounted iMatch Compatible Mechanical Dump From Operator Seat or Electric Option Rear PTO Gearbox Driven Blower 5 Blade High Efficiency Synthetic 15" Impeller Impeller Speed: 2250-3250 RPM Steel Impeller Housing Boot to Blower Hose Diameter: 8 inches Frame Material: Sight Glass Fill Indicator or Wireless Fill Alarm Sensor Option High Efficiency Blow Molded Inducer and Transition Chute Tool-less access to chute for easy clog removal Tool-less boot removal and installation for quick changing of implements	
BASE MACHINE		
0731XF	Material Collection System - 20-Bu Dump from Seat	USD \$5,137.00
DESTINATION AND LANGUAGE		
Basic Factory Options		
DESTINATION		
0202	United States	No Added Cost
0184	Canada	No Added Cost
0205	Quebec, Canada	No Added Cost
OPERATOR'S MANUAL		
0409	English OM	No Added Cost
0413	French OM	No Added Cost
0437	Spanish OM	No Added Cost
DECK BOOT		
Basic Factory Options		
DECK BOOT		
<i>Includes boot, hardware, and hose</i>		
2963	54D DECK BOOT KIT (MY19 and Older) <i>Only Available with 2551 Electric DFS</i>	USD (\$41.00)



Material Collection System - 20-Bu Dump from Seat

Code	Description	List price
2964	54D DECK BOOT KIT (MY20+) <i>Only Available with 2551 Electric DFS</i>	USD (\$52.00)
2962	60D DECK BOOT KIT	No Added Cost
2961	72D DECK BOOT KIT (2RLC,3R)	USD (\$43.00)
UNLOAD MATERIAL		
Basic Factory Options		
DUMP FROM SEAT		
2251	ELECTRIC DUMP-FROM-SEAT (1E, 1R, 2R) <i>Includes Wiring harness and Switch for 1E, 1R, 2R Tractors and Electric Actuator</i>	No Added Cost
2252	ELECTRIC DUMP-FROM-SEAT (3R) <i>Includes Wiring harness and Switch for 3R Tractors and Electric Actuator</i>	USD (\$61.00)
MISCELLANEOUS		
Additional Factory Options		
MISCELLANEOUS		
9702	Fill Sensor (Wireless)	USD \$146.00
9315	Caster Wheel Storage Kit	USD \$58.00
9701	Road Lighting Kit (1E, 1R, 2R) <i>Note: Includes ROPS light extension brackets and extension harnesses, SMV</i>	USD \$198.00
9700	Road Lighting Kit (3R) <i>Note: Includes 7-pin connector, tail lamps, and SMV sign</i>	USD \$476.00
ATTACHMENTS FOR FIELD CONVERSION		
MISCELLANEOUS		
5CS1018	CASTER WHEEL STORAGE KIT	USD \$63.80
5CS1011	60D BOOT KIT	USD \$415.80
5CS1019	ROAD LIGHT KIT - 1E, 1R, 2R	USD \$217.80
5CS1013	72D BOOT KIT 2RLC, 3R	USD \$398.20
5CS1010	54D BOOT KIT (MY20+)	USD \$386.11
5CS1006	FRENCH OM & DECAL KIT - MC2120	USD \$255.20
5CS1020	ROAD LIGHT KIT - 3R	USD \$523.60



Material Collection System - 20-Bu Dump from Seat

Code	Description	List price
5CS1017	FILL SENSOR (Wireless)	USD \$160.60
5CS1008	SPANISH OM & DECAL KIT - MC2120	USD \$281.60
5CS1009	54D BOOT KIT (MY19 AND OLDER)	USD \$401.51



RC2048 Lift-Type Rotary Cutter

Code	Description	List price
0511XF	<p>RC2048 Lift-Type Rotary Cutter</p> <p>Cutting Width: 48 In. (1220 mm) Cutting Height: 1.5 to 9 In. (38 to 229 mm) Cutting Capacity (Diameter): 0 to 1 In. (0 to 25 mm) Cutting Chamber Depth: 7.5 In. (190 mm) Tractor PTO HP Range: 18 - 45 HP Tractor PTO: 540 RPM Implement PTO: ASABE Category III PTO Hitch: Lift-Type Category I, Adaptable to II, iMatch, and AutoHitch Compatible Overall Width: 51 In. (1,291.4 mm) Overall Length: 86.6 In. (2,199.6 mm) Deck Shape: Flat-open Round Back Deck Type: Single Deck Thickness: 11 Gauge (3 mm) Skirt Thickness: 11 Gauge (3 mm) PTO Driveline Options: Shear Bolt or Slip Clutch Drivelines Available Gear Case HP Rating: 45 HP Blade Type: Heat Treated, Suction Type Blades Blade Thickness: 0.5 In. (13 mm) Blade Width: 3 In. (76 mm) Blade Tip Speed: 13,090 fpm (66.5 m/s) Blade Pan Type: Round Pan-Type Blade Holder Blade Pan Diameter: 22.3 In. (567 mm) Solid Laminated Tire</p>	
	<p>BASE MACHINE</p> <p><i>Includes solid laminated tire kit</i></p> <p>IMPORTANT: Use front and rear enclosures in areas where thrown objects could be hazardous.</p> <p><i>iMatch Hitch required with 2305 Tractor to facilitate driveline length.</i></p>	



RC2048 Lift-Type Rotary Cutter

Code	Description	List price
0511XF	<p><i>iMatch Hitch required if going on a 4M or 4R tractor equipped with R3/R4 tires to avoid possible interference between tractor tires and cutter front shield</i></p> <p>RC2048 Lift-Type Rotary Cutter</p>	USD \$1,955.00
<p>DESTINATION AND LANGUAGE</p> <p>Field Installed Options</p> <p>OPERATOR'S MANUAL AND DECALS</p>		
904N	French OM & Decal Kit (RC20)	USD \$145.00
<p>DRIVELINES</p> <p>Basic Factory Options</p> <p>DRIVELINES</p>		
1000	Driveline with Slip Clutch <i>Recommended</i>	USD \$172.00
1010	Driveline with Shear Bolt	In Base Price
<p>FRAME AND FEATURES</p> <p>Basic Factory Options</p> <p>ENCLOSURES</p> <p><i>Use enclosures in areas where thrown objects could be hazardous.</i></p>		
2000	Front and Rear Chain Enclosure <i>Note: Recommended</i>	USD \$251.00
2010	Front Rubber with Foot Guards and Rear Metal Enclosure	In Base Price
2020	Front Chain and No Rear Enclosure	USD \$62.00
<p>MISCELLANEOUS</p> <p>ATTACHMENTS FOR FIELD CONVERSION</p> <p>MISCELLANEOUS</p>		
BLV11201	<p>John Deere Quik-Knect Driveline Yoke Bundle</p> <p><i>BLV11201 is compatible with:</i></p> <ul style="list-style-type: none"> - RC2048 w/ Slip Clutch Driveline Serial Number Range 048199 & up - RC2048 w/ Shear Pin Driveline Serial Number Range 040602 & up <p><i>Tractor Receiver Part number: BLV10953</i></p> <p><i>At least one tractor receiver bundle is needed per tractor. This bundle is removable and can be used on various tractors within the compatibility.</i></p>	USD \$373.56



RC2048 Lift-Type Rotary Cutter

Code	Description	List price
5TIFC711289	<i>One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).</i> French Operator's Manual and Decal Kit for RC20 Series Rotary Cutters	USD \$188.11



RC2060 Lift-Type Rotary Cutter

Code	Description	List price
0512XF	<p>RC2060 Lift-Type Rotary Cutter Cutting Width: 60 In. (1524 mm) Cutting Height: 1.5 to 9 In. (38 to 229 mm) Cutting Capacity (Diameter): 0 to 1 In. (0 to 25 mm) Cutting Chamber Depth: 7.5 In. (190 mm) Tractor PTO HP Range: 19 - 65 HP Tractor PTO: 540 RPM Implement PTO: ASABE Category III PTO Hitch: Lift-Type Category I, Adaptable to II, iMatch, and AutoHitch Compatible Overall Width: 63 In. (1,600.2 mm) Overall Length: 101.2 In. (2,570.5 mm) Deck Shape: Flat-open Round Back Deck Type: Single Deck Thickness: 11 Gauge (3 mm) Skirt Thickness: 11 Gauge (3 mm) PTO Driveline Options: Shear Bolt or Slip Clutch Drivelines Available Gear Case HP Rating: 65 HP Blade Type: Heat Treated, Suction Type Blades Blade Thickness: 0.5 In. (13 mm) Blade Width: 3 In. (76 mm) Blade Tip Speed: 14,355 fpm (72.8 m/s) Blade Pan Type: Round Pan-Type Blade Holder Blade Pan Diameter: 22.3 In. (567 mm) Solid Laminated Tire (Included)</p>	
0512XF	<p>BASE MACHINE <i>Includes solid laminated tire kit</i> <i>iMatch Hitch required if going on a 4M or 4R tractor equipped with R3/R4 tires to avoid possible interference between tractor tires and cutter front shield</i> RC2060 Lift-Type Rotary Cutter</p>	USD \$2,200.00
904N	<p>DESTINATION AND LANGUAGE Field Installed Options OPERATOR'S MANUAL AND DECALS French OM & Decal Kit (RC20)</p>	USD \$145.00
	<p>DRIVELINES Basic Factory Options</p>	



RC2060 Lift-Type Rotary Cutter

Code	Description	List price
DRIVELINES		
1000	Driveline with Slip Clutch <i>Recommended</i>	USD \$186.00
1010	Driveline with Shear Bolt	In Base Price
FRAME AND FEATURES		
Basic Factory Options		
ENCLOSURES		
<i>Use enclosures in areas where thrown objects could be hazardous.</i>		
2000	Front and Rear Chain Enclosure <i>Note: Recommended</i>	USD \$304.00
2010	Front Rubber with Foot Guards and Rear Metal Enclosure	In Base Price
2020	Front Chain and No Rear Enclosure	USD \$74.00
MISCELLANEOUS		
ATTACHMENTS FOR FIELD CONVERSION		
MISCELLANEOUS		
BLV11201	John Deere Quik-Knect Driveline Yoke Bundle <i>BLV11201 is compatible with:</i> - RC2060 and RC2072 w/ Slip Clutch Driveline Serial Number Range 063419 & up - RC2060 and RC2072 w/ Shear Pin Driveline Serial Number Range 048269 & up <i>Tractor Receiver Part number: BLV10953</i> <i>At least one tractor receiver bundle is needed per tractor. This bundle is removable and can be used on various tractors within the compatibility.</i> <i>One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).</i>	USD \$373.56
5TIFC711289	French Operator's Manual and Decal Kit for RC20 Series Rotary Cutters	USD \$188.11



RC2072 Lift-Type Rotary Cutter

Code	Description	List price
0513XF	<p>RC2072 Lift-Type Rotary Cutter Cutting Width: 72 In. (1,830 mm) Cutting Height: 1.5 to 9 In. (38 to 229 mm) Cutting Capacity (Diameter): 0 to 1 In. (0 to 25 mm) Cutting Chamber Depth: 7.5 In. (190 mm) Tractor PTO HP Range: 25 - 65 HP Tractor PTO: 540 RPM Implement PTO: ASABE Category III PTO Hitch: Lift-Type Category I, Adaptable to II, iMatch, and AutoHitch Compatible Overall Width: 75 In. (1,905 mm) Overall Length: 111.5 In. (2,832.1 mm) Deck Shape: Flat-open Round Back Deck Type: Single Deck Thickness: 11 Gauge (3 mm) Skirt Thickness: 11 Gauge (3 mm) PTO Driveline Options: Shear Bolt or Slip Clutch Drivelines Available Gear Case HP Rating: 65 HP Blade Type: Heat Treated, Suction Type Blades Blade Thickness: 0.5 In. (13 mm) Blade Width: 3 In. (76 mm) Blade Tip Speed: 14,955 fpm (76 m/s) Blade Pan Type: Round Pan-Type Blade Holder Blade Pan Diameter: 28.5 In. (723.9 mm) Solid Laminated Tire (Included)</p>	
0513XF	<p>BASE MACHINE <i>Includes solid laminated tire kit</i> <i>iMatch Hitch required if going on a 4M or 4R tractor equipped with R3/R4 tires to avoid possible interference between tractor tires and cutter front shield</i> RC2072 Lift-Type Rotary Cutter</p>	USD \$2,524.00
904N	<p>DESTINATION AND LANGUAGE Field Installed Options OPERATOR'S MANUAL AND DECALS French OM & Decal Kit (RC20)</p>	USD \$145.00
	DRIVELINES	



RC2072 Lift-Type Rotary Cutter

Code	Description	List price
Basic Factory Options DRIVELINES		
1000	Driveline with Slip Clutch <i>Recommended</i>	USD \$186.00
1010	Driveline with Shear Bolt	In Base Price
FRAME AND FEATURES Basic Factory Options ENCLOSURES <i>Use enclosures in areas where thrown objects could be hazardous.</i>		
2000	Front and Rear Chain Enclosure <i>Note: Recommended</i>	USD \$422.00
2010	Front Rubber with Foot Guards and Rear Metal Enclosure	In Base Price
2020	Front Chain and No Rear Enclosure	USD \$113.00
MISCELLANEOUS ATTACHMENTS FOR FIELD CONVERSION MISCELLANEOUS		
BLV11201	John Deere Quik-Knect Driveline Yoke Bundle <i>BLV11201 is compatible with:</i> <ul style="list-style-type: none"> - RC2060 and RC2072 w/ Slip Clutch Driveline Serial Number Range 063419 & up - RC2060 and RC2072 w/ Shear Pin Driveline Serial Number Range 048269 & up <i>Tractor Receiver Part number: BLV10953</i> <i>At least one tractor receiver bundle is needed per tractor. This bundle is removable and can be used on various tractors within the compatibility.</i> <i>One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).</i>	USD \$373.56
5TIFC711289	French Operator's Manual and Decal Kit for RC20 Series Rotary Cutters	USD \$188.11



RC2084 Lift-Type Rotary Cutter

Code	Description	List price
0514XF	<p>RC2084 Lift-Type Rotary Cutter Cutting Width: 84 In. (2,134 mm) Cutting Height: 1.75 to 11 In. (44.45 to 279.4 mm) Cutting Capacity (Diameter): 0 to 1 In. (0 to 25 mm) Cutting Chamber Depth: 9.75 In. (248 mm) Tractor PTO HP Range: 45 - 90 HP Tractor PTO: 540 RPM Implement PTO: ASABE Category III PTO Hitch: Lift-Type Category II, Category II Quick Hitch Compatible Overall Width: 88 In. (2,235 mm) Overall Length: 124 In. (3,150 mm) Deck Shape: Flat-open Round Back Deck Type: Single Deck Thickness: 10 Gauge (3.4 mm) Skirt Thickness: 10 Gauge (3.4 mm) PTO Driveline Options: Slip Clutch Standard Gear Case HP Rating: 90 HP Blade Type: Heat Treated, Suction Type Blades Blade Thickness: 0.5 In. (13 mm) Blade Width: 3 In. (76 mm) Blade Tip Speed: 14,380 fpm (73 m/s) Blade Pan Type: Round Pan-Type Blade Holder Blade Pan Diameter: 32.5 In. (825.5 mm) Tire Options: Single or Dual Laminated Tire</p>	
0514XF	<p>BASE MACHINE <i>Includes Driveline with Slip Clutch</i> <i>iMatch Hitch required if going on a 4M or 4R tractor equipped with R3/R4 tires to avoid possible interference between tractor tires and cutter front shield</i></p>	USD \$4,686.00
904N	<p>DESTINATION AND LANGUAGE Field Installed Options OPERATOR'S MANUAL AND DECALS</p> <p>French OM & Decal Kit (RC20)</p>	USD \$145.00
	<p>FRAME AND FEATURES Basic Factory Options ENCLOSURES <i>Use enclosures in areas where thrown objects could be hazardous.</i></p>	



RC2084 Lift-Type Rotary Cutter

Code	Description	List price
2000	Front and Rear Chain Enclosure	In Base Price
	WHEELS AND TIRES	
	Basic Factory Options	
	WHEELS AND TIRES	
3000	Laminated Tire	In Base Price
3010	Dual Tire Laminated	USD \$133.00
	MISCELLANEOUS	
	ATTACHMENTS FOR FIELD CONVERSION	
	MISCELLANEOUS	
BLV11203	John Deere Quik-Knect Driveline Yoke Bundle <i>BLV11203 is compatible with RC2084 w/ Slip Clutch Driveline Serial Number Range 105933 & up</i> <i>Tractor Receiver Part number: BLV10953</i> <i>At least one tractor receiver bundle is needed per tractor.</i> <i>This bundle is removable and can be used on various tractors within the compatibility.</i> <i>One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).</i>	USD \$376.37
5TIFC711289	French Operator's Manual and Decal Kit for RC20 Series Rotary Cutters	USD \$188.11



RC4048 Rotary Cutter

Code	Description	List price
2701XF	<p>RC4048 Rotary Cutter</p> <p>Overall Width: 52.3 in. Overall Length: 90.3 in. Overall Weight: 410 lbs.</p> <p>CAPACITY</p> <p>Cutting Width: 48 In. (1220 mm) Cutting Height: 2 to 9 In. Cutting Capacity (Diameter): 0 to 1 In. (0 to 25 mm) Cutting Chamber Depth: 7 In. (178 mm)</p> <p>TRACTOR COMPATIBILITY</p> <p>Tractor PTO HP Range: 15-40 HP Tractor PTO: 540 RPM Implement PTO: ASABE Category III PTO Gear Case HP Rating: 40 HP</p> <p>HITCH</p> <p>Type: Lift-Type Category: I iMatch Compatible: Yes AutoHitch Compatible: no</p> <p>DECK</p> <p>Deck Shape: Flat-open Round Back Deck Type: Single Deck Thickness: 12 Gauge (2.79 mm) Skirt Thickness: 12 Gauge (2.79mm)</p> <p>DRIVELINE</p> <p>PTO Driveline Options: Slip Clutch Drivelines Quick-Knect™ compatible: Yes</p> <p>BLADES</p> <p>Blade Tip Speed: 13,100 Blade Type: Heat Treated, Suction Type Blades Blade Thickness: 0.5 In. (13 mm) Blade Width: 3 In. (76 mm) Blade Pan Type: Oval Pan-Type Blade Holder Blade Pan Diameter: 9.25 x 20.5 in. (235 x 622 cm)</p> <p>WHEELS</p> <p>Quantity: 1 Tire: Laminated Tire Diameter laminated: 16 in. (406 mm) Width laminated: 4 in. (101.6 mm)</p>	



RC4048 Rotary Cutter

Code	Description	List price
	<p>SAFETY</p> <p>Markings: Standard</p> <p>Front deflector: Front Chain Shield</p> <p>Rear deflector: Rear Chain Shield</p> <p>Warranty: 1 year, Gear Box - 3 years</p> <p>Chain Shields: Front & Rear Standard</p>	
	BASE MACHINE	
	<p><i>Rotary Cutters come in multiples of 2 per order</i></p> <p><i>IMPORTANT: Use front and rear enclosures in areas where thrown objects could be hazardous.</i></p>	
2701XF	RC4048 Rotary Cutter	USD \$2,608.00
	DESTINATION AND LANGUAGE	
	Basic Factory Options	
	DESTINATION	
0202	United States	No Added Cost
	OPERATOR'S MANUAL AND DECALS	
	<i>OM & Decal Kits come in a quantity of 2 per order</i>	
0409	English OM and Decals Kit	No Added Cost
0413	French OM and Decals Kit	No Added Cost
0437	Spanish Om and Decals Kit	No Added Cost
	MISCELLANEOUS	
	Field Installed Options	
	MISCELLANEOUS	
	<i>Miscellaneous Options come in a quantity of 2 per order</i>	
9864	Skid Shoes (Replaceable)	USD \$82.00
	ATTACHMENTS FOR FIELD CONVERSION	
	MISCELLANEOUS	
BLV11178	John Deere Quik-Knect Driveline Yoke Bundle	USD \$300.30
BLV10953	John Deere Quik Knect™ PTO receiver	USD \$225.50
5WD1038335	Skid Shoes (Replaceable)	USD \$100.11



RC4060 Rotary Cutter

Code	Description	List price
2711XF	<p>RC4060 Rotary Cutter</p> <p>Overall Width: 61.3 in. Overall Length: 98.3 in. Overall Weight: 494 lbs.</p> <p>CAPACITY Cutting Width: 60 In. (1524 mm) Cutting Height: 2 to 9 In. Cutting Capacity (Diameter): 0 to 1 In. (0 to 25 mm) Cutting Chamber Depth: 7 In. (178 mm)</p> <p>TRACTOR COMPATIBILITY Tractor PTO HP Range: 20-55 HP Tractor PTO: 540 RPM Implement PTO: ASABE Category III PTO Gear Case HP Rating: 55 HP</p> <p>HITCH Type: Lift-Type Category: I iMatch Compatible: Yes AutoHitch Compatible: no</p> <p>DECK Deck Shape: Flat-open Round Back Deck Type: Single Deck Thickness: 12 Gauge (2.79 mm) Skirt Thickness: 12 Gauge (2.79mm)</p> <p>DRIVELINE PTO Driveline Options: Slip Clutch Drivelines Quick-Knect™ compatible: Yes</p> <p>BLADES Blade Tip Speed: 13,620 Blade Type: Heat Treated, Suction Type Blades Blade Thickness: 0.5 In. (13 mm) Blade Width: 3 In. (76 mm) Blade Pan Type: Oval Pan-Type Blade Holder Blade Pan Diameter: 235 x 521 mm 20.5 x 9.25 in.</p> <p>WHEELS Quantity: 1 Tire: Laminated Tire</p>	



RC4060 Rotary Cutter

Code	Description	List price
	Diameter laminated: 16 in. (406 mm) Width laminated: 4 in. (101.6 mm) SAFETY Markings: Standard Front deflector: Front Chain Shield Rear deflector: Rear Chain Shield Warranty: 1 year, Gear Box - 3 years Chain Shields: Front & Rear Standard	
	BASE MACHINE	
2711XF	<i>Rotary Cutters come in multiples of 2 per order</i> RC4060 Rotary Cutter	USD \$2,842.00
	DESTINATION AND LANGUAGE	
	Basic Factory Options	
	DESTINATION	
0202	United States	No Added Cost
	OPERATOR'S MANUAL AND DECALS	
	<i>OM & Decal Kits come in a quantity of 2 per order</i>	
0409	English OM and Decals Kit	No Added Cost
0413	French OM and Decals Kit	No Added Cost
0437	Spanish Om and Decals Kit	No Added Cost
	MISCELLANEOUS	
	Field Installed Options	
	MISCELLANEOUS	
	<i>Miscellaneous Options come in a quantity of 2 per order</i>	
9864	Skid Shoes (Replaceable)	USD \$82.00
	ATTACHMENTS FOR FIELD CONVERSION	
	MISCELLANEOUS	
BLV11178	John Deere Quik-Knect Driveline Yoke Bundle	USD \$300.30
BLV10953	John Deere Quik Knect™ PTO receiver	USD \$225.50
5WD1038335	Skid Shoes (Replaceable)	USD \$100.11



RC4072 Rotary Cutter

Code	Description	List price
2721XF	<p>RC4072 Rotary Cutter</p> <p>Overall Width: 73.3 in. Overall Length: 111 In Overall Weight: 575 lbs.</p> <p>CAPACITY Cutting Width: 72 In. (1,830 mm) Cutting Height: 2 to 9 In. Cutting Capacity (Diameter): 0 to 1 In. (0 to 25 mm) Cutting Chamber Depth: 7 In. (178 mm)</p> <p>TRACTOR COMPATIBILITY Tractor PTO HP Range: 25 - 55 HP Tractor PTO: 540 RPM Implement PTO: ASABE Category III PTO Gear Case HP Rating: 55 HP</p> <p>HITCH Type: Lift-Type Category: I iMatch Compatible: Yes AutoHitch Compatible: no</p> <p>DECK Deck Shape: Flat-open Round Back Deck Type: Single Deck Thickness: 12 Gauge (2.79 mm) Skirt Thickness: 12 Gauge (2.79mm)</p> <p>DRIVELINE PTO Driveline Options: Slip Clutch Drivelines Quick-Knect™ compatible: Yes</p> <p>BLADES Blade Tip Speed: 14,340 Blade Type: Heat Treated, Suction Type Blades Blade Thickness: 0.5 In. (13 mm) Blade Width: 3 In. (76 mm) Blade Pan Type: Oval Pan-Type Blade Holder Blade Pan Diameter: 235 x 521 mm 20.5 x 9.25 in.</p> <p>WHEELS Quantity: 1 Tire: Laminated Tire Diameter laminated: 16 in. (406 mm) Width laminated: 4 in. (101.6 mm)</p>	



RC4072 Rotary Cutter

Code	Description	List price
	<p>SAFETY</p> <p>Markings: Standard</p> <p>Front deflector: Front Chain Shield</p> <p>Rear deflector: Rear Chain Shield</p> <p>Warranty: 1 year, Gear Box - 3 years</p> <p>Chain Shields: Front & Rear Standard</p>	
	BASE MACHINE	
2721XF	<p><i>Rotary Cutters come in multiples of 2 per order</i></p> <p>RC4072 Rotary Cutter</p>	USD \$3,311.00
	DESTINATION AND LANGUAGE	
	Basic Factory Options	
	DESTINATION	
0202	United States	No Added Cost
	OPERATOR'S MANUAL AND DECALS	
	<i>OM & Decal Kits come in a quantity of 2 per order</i>	
0409	English OM and Decals Kit	No Added Cost
0413	French OM and Decals Kit	No Added Cost
0437	Spanish Om and Decals Kit	No Added Cost
	MISCELLANEOUS	
	Field Installed Options	
	MISCELLANEOUS	
	<i>Miscellaneous Options come in a quantity of 2 per order</i>	
9864	Skid Shoes (Replaceable)	USD \$82.00
	ATTACHMENTS FOR FIELD CONVERSION	
	MISCELLANEOUS	
BLV11178	John Deere Quik-Knect Driveline Yoke Bundle	USD \$300.30
BLV10953	John Deere Quik Knect™ PTO receiver	USD \$225.50
5WD1038335	Skid Shoes (Replaceable)	USD \$100.11