FL1053 - 53" FLAIL MOWER (FIXED)

Code	Description	List price
04A1XF	**FL1053 - 53" FLAIL MOWER (FIXED)**	
	Dimensions	
	Capacity, Cutting (in.): 0.75"	
	Height, Cutting (in.): .78" /1.57" /2.36"	
	Height, Overall (in.): 31.2"	
	Length, Overall (in.): 32"	
	Width, Cutting (in): 53"	
	Width, Overall (in.): 60.02"	
	Weight (lbs.): 467 lbs.	
	Compatibility	
	Tractor HP Required (min. - max.): 20 - 45HP	
	Tractor Weight MINIMUM (lbs.): 1400 lbs.	
	COG (in): 15"	
	Hitch	
	Hitch Type: 3-point	
	iMatch Compatible: No	
	Hitch Category: 1	
	Hitch Position: Fixed Centered	
	Offset Range: No	
	Hydraulic Offset: No	
	Blades	
	Blade Type: Hammers (std); Y-Blade (service)	
	Number of Hammers: 28	
	Type of Blades/ Hammers: 19 / 21	
	Blade Tip Speed (ft/min): 8622	
	Rotor	
	Rotor Diameter (in.): 5"	
	Rotor Speed (rpm): 2600 rpm	
	Rotor Thickness (mm.): 8 mm.	
	Rotor Work Diameter (in.): 12.63"	
	Rotor Bearing Type: SPHERICAL ROLLER 22207	
	Drives	
	Gear Box Speed (rpm): 540 rpm	
	Drive Belts: 2 - SPB Lp=1160	
	Gauge Roller Diameter (in.): 5.5"	
	Other	
	Hydraulic Quick Coupler Size (in.): 1/2"	
	Frame Thickness (mm.): 3 mm.	

Copyright © Deere & Company. All Rights Reserved.

FL1053 - 53" FLAIL MOWER (FIXED)

Code	Description	List price
	Side Frame Thickness (mm.): 4 mm. Roller Bearing Diameter (in): 2.4" Rear Roller Bearing Type: D30 D62 B20 2206E 2RS1 Belt adjustment: Screw adjustment Primary Pulley Diameter (mm.): 225 mm. Secondary Pulley Diameter (mm.): 140 mm. Hood Height (in.): 15.35" Side Case Height (in.): 25.2" PTO Yoke Height (in.): 18.66"	
	BASE MACHINE	
04A1XF	FL1053 - 53" FLAIL MOWER (FIXED)	USD $4,323.00
	DESTINATION AND LANGUAGE **Basic Factory Options** **DESTINATION**	
0202	United States	No Added Cost
	OPERATOR'S MANUAL AND DECALS	
0409	English	No Added Cost
0413	French	No Added Cost
0437	Spanish	No Added Cost

Copyright © Deere & Company. All Rights Reserved.

FL1061 - 61" FLAIL MOWER (FIXED)

Code	Description	List price
04B1XF	**FL1061 - 61" FLAIL MOWER (FIXED)**	
	Dimensions	
	Capacity, Cutting (in.): 0.75"	
	Height, Cutting (in.): .78" /1.57" /2.36"	
	Height, Overall (in.): 31.2"	
	Length, Overall (in.): 32"	
	Width, Cutting (in): 61"	
	Width, Overall (in.): 68.16"	
	Weight (lbs.): 505 lbs.	
	Compatibility	
	Tractor HP Required (min. - max.): 25 - 45HP	
	Tractor Weight MINIMUM (lbs.): 1550 lbs.	
	COG (in): 15"	
	Hitch	
	Hitch Type: 3-point	
	iMatch Compatible: No	
	Hitch Category: 1	
	Hitch Position: Fixed Centered	
	Offset Range: No	
	Hydraulic Offset: No	
	Blades	
	Blade Type: Hammers (std); Y-Blade (service)	
	Number of Hammers: 32	
	Type of Blades/ Hammers: 19 / 21	
	Blade Tip Speed (ft/min): 8622	
	Rotor	
	Rotor Diameter (in.): 5"	
	Rotor Speed (rpm): 2600 rpm	
	Rotor Thickness (mm.): 8 mm.	
	Rotor Work Diameter (in.): 12.63"	
	Rotor Bearing Type: SPHERICAL ROLLER 22207	
	Drives	
	Gear Box Speed (rpm): 540 rpm	
	Drive Belts: 2 - SPB Lp=1160	
	Gauge Roller Diameter (in.): 5.5"	
	Other	
	Hydraulic Quick Coupler Size (in.): 1/2"	

Copyright © Deere & Company. All Rights Reserved.

FL1061 - 61" FLAIL MOWER (FIXED)

Code	Description	List price
	Frame Thickness (mm.): 3 mm. Side Frame Thickness (mm.): 4 mm. Roller Bearing Diameter (in): 2.4" Rear Roller Bearing Type: D30 D62 B20 2206E 2RS1 Belt adjustment: Screw adjustment Primary Pulley Diameter (mm.): 225 mm. Secondary Pulley Diameter (mm.): 140 mm. Hood Height (in.): 15.35" Side Case Height (in.): 25.2" PTO Yoke Height (in.): 18.66"	
	BASE MACHINE	
04B1XF	FL1061 - 61" FLAIL MOWER (FIXED)	USD $4,550.00
	DESTINATION AND LANGUAGE **Basic Factory Options** **DESTINATION**	
0202	United States	No Added Cost
	OPERATOR'S MANUAL AND DECALS	
0409	English	No Added Cost
0413	French	No Added Cost
0437	Spanish	No Added Cost

Copyright © Deere & Company. All Rights Reserved.

FL1163 - 63" FLAIL MOWER (SIDE SHIFT)

Code	Description	List price
04D1XF	**FL1163 - 63" FLAIL MOWER (SIDE SHIFT)**	
	Dimensions Capacity, Cutting (in.): 1.5" Height, Cutting (in.): 0.98" /1.96" /2.99" Height, Overall (in.): 36.5" Length, Overall (in.): 44.3" Width, Cutting (in): 63" Width, Overall (in.): 68.88" Weight (lbs.): 718 lbs. Compatibility Tractor HP Required (min. - max.): 30 - 55HP Tractor Weight MINIMUM (lbs.): 2600 lbs. COG (in): 25" Hitch Hitch Type: 3-point iMatch Compatible: No Hitch Category: 1 Hitch Position: Centered Offset Range: Left of Center (11"-33"), Right of Center (30"-46") Hydraulic Offset: No Blades Blade Type: Hammers (std); Y-Blade (service) Number of Hammers: 22 Type of Blades/ Hammers: 18 / 20 Blade Tip Speed (ft/min): 8937 Rotor Rotor Diameter (in.): 5" Rotor Speed (rpm): 2278 rpm Rotor Thickness (mm.): 8 mm. Rotor Work Diameter (in.): 15" Rotor Bearing Type: SPHERICAL ROLLER 22207 Drives Gear Box Speed (rpm): 540 rpm Drive Belts: 3 - SPB Lp=1320 Gauge Roller Diameter (in.): 5.5" Other Hydraulic Quick Coupler Size (in.): 1/2" Frame Thickness (mm.): 3 mm.	

Copyright © Deere & Company. All Rights Reserved.

FL1163 - 63" FLAIL MOWER (SIDE SHIFT)

Code	Description	List price
	Side Frame Thickness (mm.): 5 mm. Roller Bearing Diameter (in): 2.835" Rear Roller Bearing Type: YAR 207-2FW/VA201 Belt adjustment: Screw adjustment Primary Pulley Diameter (mm.): 225 mm. Secondary Pulley Diameter (mm.): 160 mm. Hood Height (in.): 18.89" Side Case Height (in.): 24.01" PTO Yoke Height (in.): 18.18"	
	BASE MACHINE	
04D1XF	FL1163 - 63" FLAIL MOWER (SIDE SHIFT)	USD $6,000.00
	DESTINATION AND LANGUAGE **Basic Factory Options** **DESTINATION**	
0202	United States	No Added Cost
	OPERATOR'S MANUAL AND DECALS	
0409	English	No Added Cost
0413	French	No Added Cost
0437	Spanish	No Added Cost
	HYDRAULICS **Field Installed Options** **HYDRAULICS**	
9800	Hydraulic Adjustment Kit	USD $455.00

Copyright © Deere & Company. All Rights Reserved.

FL1169 - 69" FLAIL MOWER (SIDE SHIFT)

Code	Description	List price
04E1XF	**FL1169 - 69" FLAIL MOWER (SIDE SHIFT)**	
	Dimensions	
	Capacity, Cutting (in.): 1.5"	
	Height, Cutting (in.): 0.98" /1.96" /2.99"	
	Height, Overall (in.): 36.5"	
	Length, Overall (in.): 44.3"	
	Width, Cutting (in): 69"	
	Width, Overall (in.): 74.76"	
	Weight (lbs.): 749 lbs.	
	Compatibility	
	Tractor HP Required (min. - max.): 35 - 55HP	
	Tractor Weight MINIMUM (lbs.): 2600 lbs.	
	COG (in): 25"	
	Hitch	
	Hitch Type: 3-point	
	iMatch Compatible: No	
	Hitch Category: 1	
	Hitch Position: Centered	
	Offset Range: Left of Center (11"-33"), Right of Center (36"-52")	
	Hydraulic Offset: No	
	Blades	
	Blade Type: Hammers (std); Y-Blade (service)	
	Number of Hammers: 24	
	Type of Blades/ Hammers: 18 / 20	
	Blade Tip Speed (ft/min): 8937	
	Rotor	
	Rotor Diameter (in.): 5"	
	Rotor Speed (rpm): 2278 rpm	
	Rotor Thickness (mm.): 8 mm.	
	Rotor Work Diameter (in.): 15"	
	Rotor Bearing Type: SPHERICAL ROLLER 22207	
	Drives	
	Gear Box Speed (rpm): 540 rpm	
	Drive Belts: 3 - SPB Lp=1320	
	Gauge Roller Diameter (in.): 5.5"	
	Other	
	Hydraulic Quick Coupler Size (in.): 1/2"	
	Frame Thickness (mm.): 3 mm.	
	Side Frame Thickness (mm.): 5 mm.	

Copyright © Deere & Company. All Rights Reserved.

FL1169 - 69" FLAIL MOWER (SIDE SHIFT)

Code	Description	List price
	Roller Bearing Diameter (in): 2.835" Rear Roller Bearing Type: YAR 207-2FW/VA201 Belt adjustment: Screw adjustment Primary Pulley Diameter (mm.): 225 mm. Secondary Pulley Diameter (mm.): 160 mm. Hood Height (in.): 18.89" Side Case Height (in.): 24.01" PTO Yoke Height (in.): 18.18"	
	BASE MACHINE	
04E1XF	FL1169 - 69" FLAIL MOWER (SIDE SHIFT)	USD $6,250.00
	DESTINATION AND LANGUAGE **Basic Factory Options** **DESTINATION**	
0202	United States	No Added Cost
	OPERATOR'S MANUAL AND DECALS	
0409	English	No Added Cost
0413	French	No Added Cost
0437	Spanish	No Added Cost
	HYDRAULICS **Field Installed Options** **HYDRAULICS**	
9800	Hydraulic Adjustment Kit	USD $455.00

Copyright © Deere & Company. All Rights Reserved.

FL1045S - 45" FLAIL MOWER (SIDE OFFSET)

Code	Description	List price
04F1XF	**FL1045S - 45" FLAIL MOWER (SIDE OFFSET)**	
	Dimensions	
	Capacity, Cutting (in.): 0.79"	
	Height, Cutting (in.): .78" /1.57" /2.36"	
	Height, Overall (in.): 38.7"	
	Length, Overall (in.): 71.2"	
	Width, Cutting (in): 45"	
	Width, Overall (in.): 52.32"	
	Weight (lbs.): 592 lbs.	
	Compatibility	
	Tractor HP Required (min. - max.): 15 - 45HP	
	Tractor Weight MINIMUM (lbs.): 2600 lbs.	
	COG (in): 45.6"	
	Hitch	
	Hitch Type: 3-point	
	iMatch Compatible: No	
	Hitch Category: 1	
	Hitch Position: Offset	
	Offset Range: Left of Center (21.5"), Fully Extended (68")	
	Hydraulic Offset: Standard	
	Blades	
	Blade Type: Hammers (std); Y-Blade (service)	
	Number of Hammers: 24	
	Type of Blades/ Hammers: 19 / 21	
	Blade Tip Speed (ft/min): 8622	
	Rotor	
	Rotor Diameter (in.): 5"	
	Rotor Speed (rpm): 2600 rpm	
	Rotor Thickness (mm.): 8 mm.	
	Rotor Work Diameter (in.): 12.63"	
	Rotor Bearing Type: SPHERICAL ROLLER 22207	
	Drives	
	Gear Box Speed (rpm): 540 rpm	
	Drive Belts: 2 - SPB Lp=1160	
	Gauge Roller Diameter (in.): 5.5"	
	Other	
	Hydraulic Quick Coupler Size (in.): 1/2"	
	Frame Thickness (mm.): 3 mm.	

Copyright © Deere & Company. All Rights Reserved.

FL1045S - 45" FLAIL MOWER (SIDE OFFSET)

Code	Description	List price
	Side Frame Thickness (mm.): 4 mm. Roller Bearing Diameter (in): 2.4" Rear Roller Bearing Type: D30 D62 B20 2206E 2RS1 Belt adjustment: Screw adjustment Primary Pulley Diameter (mm.): 225 mm. Secondary Pulley Diameter (mm.): 140 mm. Hood Height (in.): 15.35" Side Case Height (in.): 25.2" PTO Yoke Height (in.): 19.29"	
	BASE MACHINE	
04F1XF	FL1045S - 45" FLAIL MOWER (SIDE OFFSET)	USD $6,750.00
	DESTINATION AND LANGUAGE **Basic Factory Options** **DESTINATION**	
0202	United States	No Added Cost
	OPERATOR'S MANUAL AND DECALS	
0409	English	No Added Cost
0413	French	No Added Cost
0437	Spanish	No Added Cost

Copyright © Deere & Company. All Rights Reserved.

FL1061S - 61" FLAIL MOWER (SIDE OFFSET)

Code	Description	List price
04K1XF	**FL1061S - 61" FLAIL MOWER (SIDE OFFSET)**	
	Dimensions	
	Capacity, Cutting (in.): 0.79"	
	Height, Cutting (in.): .78" /1.57" /2.36"	
	Height, Overall (in.): 38.7"	
	Length, Overall (in.): 71.2"	
	Width, Cutting (in): 61"	
	Width, Overall (in.): 68.88"	
	Weight (lbs.): 663 lbs.	
	Compatibility	
	Tractor HP Required (min. - max.): 25 - 45HP	
	Tractor Weight MINIMUM (lbs.): 2600 lbs.	
	COG (in): 45.6"	
	Hitch	
	Hitch Type: 3-point	
	iMatch Compatible: No	
	Hitch Category: 1	
	Hitch Position: Offset	
	Offset Range: Left of Center (21.5"), Fully Extended - (83")	
	Hydraulic Offset: Standard	
	Blades	
	Blade Type: Hammers (std); Y-Blade (service)	
	Number of Hammers: 32	
	Type of Blades/ Hammers: 19 / 21	
	Blade Tip Speed (ft/min): 8622	
	Rotor	
	Rotor Diameter (in.): 5"	
	Rotor Speed (rpm): 2600 rpm	
	Rotor Thickness (mm.): 8 mm.	
	Rotor Work Diameter (in.): 12.63"	
	Rotor Bearing Type: SPHERICAL ROLLER 22207	
	Drives	
	Gear Box Speed (rpm): 540 rpm	
	Drive Belts: 2 - SPB Lp=1160	
	Gauge Roller Diameter (in.): 5.5"	
	Other	
	Hydraulic Quick Coupler Size (in.): 1/2"	
	Frame Thickness (mm.): 3 mm.	
	Side Frame Thickness (mm.): 4 mm.	

Copyright © Deere & Company. All Rights Reserved.

FL1061S - 61" FLAIL MOWER (SIDE OFFSET)

Code	Description	List price
	Roller Bearing Diameter (in): 2.4" Rear Roller Bearing Type: D30 D62 B20 2206E 2RS1 Belt adjustment: Screw adjustment Primary Pulley Diameter (mm.): 225 mm. Secondary Pulley Diameter (mm.): 140 mm. Hood Height (in.): 15.35" Side Case Height (in.): 25.2" PTO Yoke Height (in.): 19.29"	
	BASE MACHINE	
04K1XF	FL1061S - 61" FLAIL MOWER (SIDE OFFSET)	USD $7,180.00
	DESTINATION AND LANGUAGE **Basic Factory Options** **DESTINATION**	
0202	United States	No Added Cost
	OPERATOR'S MANUAL AND DECALS	
0409	English	No Added Cost
0413	French	No Added Cost
0437	Spanish	No Added Cost

Copyright © Deere & Company. All Rights Reserved.

FL1163S - 63" FLAIL MOWER (SIDE OFFSET)

Code	Description	List price
04M1XF	**FL1163S - 63" FLAIL MOWER (SIDE OFFSET)**	
	Dimensions	
	Capacity, Cutting (in.): 1.18"	
	Height, Cutting (in.): 0.98" /1.96" /2.99"	
	Height, Overall (in.): 39"	
	Length, Overall (in.): 79.5"	
	Width, Cutting (in): 63"	
	Width, Overall (in.): 77.16"	
	Weight (lbs.): 936 lbs.	
	Compatibility	
	Tractor HP Required (min. - max.): 45 - 75HP	
	Tractor Weight MINIMUM (lbs.): 3700 lbs.	
	COG (in): 45.6"	
	Hitch	
	Hitch Type: 3-point	
	iMatch Compatible: No	
	Hitch Category: 1	
	Hitch Position: Offset	
	Offset Range: Left of Center (12"), Fully Extended - (94.5")	
	Hydraulic Offset: Standard	
	Blades	
	Blade Type: Hammers (std); Y-Blade (service)	
	Number of Hammers: 22	
	Type of Blades/ Hammers: 18 / 20	
	Blade Tip Speed (ft/min): 8937	
	Rotor	
	Rotor Diameter (in.): 5"	
	Rotor Speed (rpm): 2278 rpm	
	Rotor Thickness (mm.): 8 mm.	
	Rotor Work Diameter (in.): 15"	
	Rotor Bearing Type: SPHERICAL ROLLER 22207	
	Drives	
	Gear Box Speed (rpm): 540 rpm	
	Drive Belts: 3 - SPB Lp=1320	
	Gauge Roller Diameter (in.): 5.5"	
	Other	
	Hydraulic Quick Coupler Size (in.): 1/2"	
	Frame Thickness (mm.): 3 mm.	
	Side Frame Thickness (mm.): 5 mm.	

Copyright © Deere & Company. All Rights Reserved.

FL1163S - 63" FLAIL MOWER (SIDE OFFSET)

Code	Description	List price
	Roller Bearing Diameter (in): 2.835" Rear Roller Bearing Type: YAR 207-2FW/VA201 Belt adjustment: Screw adjustment Primary Pulley Diameter (mm.): 225 mm. Secondary Pulley Diameter (mm.): 160 mm. Hood Height (in.): 18.89" Side Case Height (in.): 24.01" PTO Yoke Height (in.): 23.62"	
	BASE MACHINE	
04M1XF	FL1163S - 63" FLAIL MOWER (SIDE OFFSET)	USD $8,310.00
	DESTINATION AND LANGUAGE **Basic Factory Options** **DESTINATION**	
0202	United States	No Added Cost
	OPERATOR'S MANUAL AND DECALS	
0409	English	No Added Cost
0413	French	No Added Cost
0437	Spanish	No Added Cost

Copyright © Deere & Company. All Rights Reserved.

FL1169S - 69" FLAIL MOWER (SIDE OFFSET)

Code	Description	List price
04N1XF	**FL1169S - 69" FLAIL MOWER (SIDE OFFSET)**	
	Dimensions	
	Capacity, Cutting (in.): 1.18"	
	Height, Cutting (in.): 0.98" /1.96" /2.99"	
	Height, Overall (in.): 39"	
	Length, Overall (in.): 79.5"	
	Width, Cutting (in): 69"	
	Width, Overall (in.): 83.04"	
	Weight (lbs.): 981 lbs.	
	Compatibility	
	Tractor HP Required (min. - max.): 50 - 75HP	
	Tractor Weight MINIMUM (lbs.): 3700 lbs.	
	COG (in): 45.6"	
	Hitch	
	Hitch Type: 3-point	
	iMatch Compatible: No	
	Hitch Category: 1	
	Hitch Position: Offset	
	Offset Range: Left of Center (12"), Fully Extended (100")	
	Hydraulic Offset: Standard	
	Blades	
	Blade Type: Hammers (std); Y-Blade (service)	
	Number of Hammers: 24	
	Type of Blades/ Hammers: 18 / 20	
	Blade Tip Speed (ft/min): 8937	
	Rotor	
	Rotor Diameter (in.): 5"	
	Rotor Speed (rpm): 2278 rpm	
	Rotor Thickness (mm.): 8 mm.	
	Rotor Work Diameter (in.): 15"	
	Rotor Bearing Type: SPHERICAL ROLLER 22207	
	Drives	
	Gear Box Speed (rpm): 540 rpm	
	Drive Belts: 3 - SPB Lp=1320	
	Gauge Roller Diameter (in.): 5.5"	
	Other	
	Hydraulic Quick Coupler Size (in.): 1/2"	
	Frame Thickness (mm.): 3 mm.	

Copyright © Deere & Company. All Rights Reserved.

FL1169S - 69" FLAIL MOWER (SIDE OFFSET)

Code	Description	List price
	Side Frame Thickness (mm.): 5 mm. Roller Bearing Diameter (in): 2.835" Rear Roller Bearing Type: YAR 207-2FW/VA201 Belt adjustment: Screw adjustment Primary Pulley Diameter (mm.): 225 mm. Secondary Pulley Diameter (mm.): 160 mm. Hood Height (in.): 18.89" Side Case Height (in.): 24.01" PTO Yoke Height (in.): 23.62"	
	BASE MACHINE	
04N1XF	FL1169S - 69" FLAIL MOWER (SIDE OFFSET)	USD $8,585.00
	DESTINATION AND LANGUAGE **Basic Factory Options** **DESTINATION**	
0202	United States	No Added Cost
	OPERATOR'S MANUAL AND DECALS	
0409	English	No Added Cost
0413	French	No Added Cost
0437	Spanish	No Added Cost

Copyright © Deere & Company. All Rights Reserved.

FL1272S - 72" FLAIL MOWER (SIDE OFFSET)

Code	Description	List price
04R1XF	**FL1272S - 72" FLAIL MOWER (SIDE OFFSET)**	
	Dimensions	
	Capacity, Cutting (in.): 1.57"	
	Height, Cutting (in.): 1.18" /1.96" /3.14"	
	Height, Overall (in.): 45"	
	Length, Overall (in.): 91.4"	
	Width, Cutting (in): 72"	
	Width, Overall (in.): 94.92"	
	Weight (lbs.): 1484 lbs.	
	Compatibility	
	Tractor HP Required (min. - max.): 40 - 105HP	
	Tractor Weight MINIMUM (lbs.): 5300 lbs.	
	COG (in): 54.7"	
	Hitch	
	Hitch Type: 3-point	
	iMatch Compatible: No	
	Hitch Category: 2	
	Hitch Position: Offset	
	Offset Range: Left of Center (13.5"), Fully Extended (115")	
	Hydraulic Offset: Standard	
	Blades	
	Blade Type: Hammers (std); Y-Blade (service)	
	Number of Hammers: 22	
	Type of Blades/ Hammers: 8 / 10	
	Blade Tip Speed (ft/min): 10039	
	Rotor	
	Rotor Diameter (in.): 5.5"	
	Rotor Speed (rpm): 2354 rpm	
	Rotor Thickness (mm.): 10 mm.	
	Rotor Work Diameter (in.): 16.29"	
	Rotor Bearing Type: SPHERICAL ROLLER 21309	
	Drives	
	Gear Box Speed (rpm): 540 rpm	
	Drive Belts: 3 - SPB Lp=1320	
	Gauge Roller Diameter (in.): 6.62"	
	Other	
	Hydraulic Quick Coupler Size (in.): 1/2"	

Copyright © Deere & Company. All Rights Reserved.

FL1272S - 72" FLAIL MOWER (SIDE OFFSET)

Code	Description	List price
	Frame Thickness (mm.): 4 mm. Side Frame Thickness (mm.): 8 mm. Roller Bearing Diameter (in): 3.15" Rear Roller Bearing Type: D40 D80 B23 62208 2RS2 Belt adjustment: Screw adjustment Primary Pulley Diameter (mm.): 225 mm. Secondary Pulley Diameter (mm.): 160 mm. Hood Height (in.): 19.68" Side Case Height (in.): 24.4" PTO Yoke Height (in.): 23.62"	
	BASE MACHINE	
04R1XF	FL1272S - 72" FLAIL MOWER (SIDE OFFSET)	USD $11,460.00
	DESTINATION AND LANGUAGE **Basic Factory Options** **DESTINATION**	
0202	United States	No Added Cost
	OPERATOR'S MANUAL AND DECALS	
0409	English	No Added Cost
0413	French	No Added Cost
0437	Spanish	No Added Cost

Copyright © Deere & Company. All Rights Reserved.

GM1048E Economy Rear Discharge Grooming Mower

Code	Description	List price
0461XF	**GM1048E Economy Rear Discharge Grooming Mower** 4 Rubber Swivel Tires 11 Gauge Reinforced Deck Spindle Shafts Greased from the Top for Easy Service Single Belt Drive with Automatic Belt Idler Rugged 30-HP Gearbox One Piece Balanced Steel Pulleys High Blade Speed Floating Top Hitch iMatch Compatible (Quick-Attach System) Working Width: 48 In. Overall Machine Width: 51 In. Machine Weight: 340 lbs. HP Requirements: 16 - 30 HP Deck Thickness: 11 Gauge Cutting Height from 1 In. to 4 In. Category I Hitch Blade Tip Speed: 13,188 Ft./Minute Type: Rear Discharge Front Antiscalping Roller: Optional Mulching Kit: Optional Rotor RPM: 3,037 RPM Driveline: 1-3/8 In. ASAE Category II Shipping Weight: 398 lbs. Set-up Time: 30 Minute 1 Year Warranty	
	BASE MACHINE *iMatch and iMatchconversion kit ordered separately.*	
0461XF	GM1048E Economy Rear Discharge Grooming Mower	USD $3,617.00
	DESTINATION AND LANGUAGE **Field Installed Options** **OPERATOR'S MANUAL AND DECALS**	
9200	French Operators Manual and Decal Kit (GM10E Series)	No Added Cost
	FRAME **Field Installed Options**	

Copyright © Deere & Company. All Rights Reserved.

GM1048E Economy Rear Discharge Grooming Mower

Code	Description	List price
	ROLLERS	
9450	Front Anti-Scalping Roller	USD $164.00
	CONVERSION KIT	
9630	I-Match Conversion Kit	USD $522.00
	CUTTING UNITS **Field Installed Options** **MULCH KITS**	
9690	Mulching Kit *For GM1048E.*	USD $414.00
	MISCELLANEOUS **ATTACHMENTS FOR FIELD CONVERSION** **MISCELLANEOUS**	
5BP004600	Mulching Kit (GM1048E)	USD $500.51
5BP950959B	French Manual Decal (GM10E Series)	USD $0.00
5BP001600	Front Antiscalping Roller	USD $207.91
5BP006750	iMatch Conversion Kit *Fits GM1048E, GM1060E, and GM1072E. Must also order longer 5BP0500404 driveline from parts for GM1048E or GM1060E.*	USD $761.20
BLV11199	John Deere Quik-Knect Driveline Yoke Bundle *Tractor Receiver Part number: BLV10953* *At least one tractor receiver bundle is needed per tractor. This bundle is removable and can be used on various tractors within the compatibility.* *One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).*	USD $300.30

Copyright © Deere & Company. All Rights Reserved.

GM1060E Economy Rear Discharge Grooming Mower

Code	Description	List price
0462XF	**GM1060E Economy Rear Discharge Grooming Mower** 4 Rubber Swivel Tires 11 Gauge Reinforced Deck Spindle Shafts Greased from the Top for Easy Service Single Belt Drive with Automatic Belt Idler Rugged 30-HP Gearbox One Piece Balanced Steel Pulleys High Blade Speed Floating Top Hitch iMatch Compatible (Quick-Attach System) Working Width: 60 In. Overall Machine Width: 63 In. Machine Weight: 375 lbs. HP Requirements: 18 - 30 HP Deck Thickness: 11 Gauge Cutting Height from 1 In. to 4 In. Category I Hitch Blade Tip Speed: 14,763 Ft./Minute Type: Rear Discharge Front Antiscalping Roller: Optional Mulching Kit: Optional Rotor RPM: 2,803 RPM Driveline: 1-3/8 In. ASAE Category II Shipping Weight: 470 lbs. Set-up Time: 30 Minute 1 Year Warranty	
	BASE MACHINE *iMatch and iMatchconversion kit ordered separately.*	
0462XF	GM1060E Economy Rear Discharge Grooming Mower	USD $3,731.00
	DESTINATION AND LANGUAGE **Field Installed Options** **OPERATOR'S MANUAL AND DECALS**	
9200	French Operators Manual and Decal Kit (GM10E Series)	No Added Cost
	FRAME **Field Installed Options**	

Copyright © Deere & Company. All Rights Reserved.

GM1060E Economy Rear Discharge Grooming Mower

Code	Description	List price
	ROLLERS	
9450	Front Anti-Scalping Roller	USD $164.00
	CONVERSION KIT	
9630	I-Match Conversion Kit	USD $522.00
	CUTTING UNITS **Field Installed Options** **MULCH KITS**	
9690	Mulching Kit *For GM1060E.*	USD $474.00
	MISCELLANEOUS **ATTACHMENTS FOR FIELD CONVERSION** **MISCELLANEOUS**	
5BP005600	Mulching Kit (GM1060E)	USD $657.80
5BP950959B	French Manual Decal (GM10E Series)	USD $0.00
5BP001600	Front Antiscalping Roller	USD $207.91
5BP006750	iMatch Conversion Kit *Fits GM1048E, GM1060E, and GM1072E. Must also order longer 5BP0500404 driveline from parts for GM1048E or GM1060E.*	USD $761.20
BLV11199	John Deere Quik-Knect Driveline Yoke Bundle *Tractor Receiver Part number: BLV10953* *At least one tractor receiver bundle is needed per tractor. This bundle is removable and can be used on various tractors within the compatibility.* *One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).*	USD $300.30

Copyright © Deere & Company. All Rights Reserved.

GM1072E Economy Rear Discharge Grooming Mower

Code	Description	List price
0463XF	**GM1072E Economy Rear Discharge Grooming Mower** 4 Rubber Swivel Tires 11 Gauge Reinforced Deck Spindle Shafts Greased from the Top for Easy Service Single Belt Drive with Automatic Belt Idler Rugged 30-HP Gearbox One Piece Balanced Steel Pulleys High Blade Speed Floating Top Hitch iMatch Compatible (Quick-Attach System) Working Width: 72 In. Overall Machine Width: 74 In. Machine Weight: 440 lbs. HP Requirements: 22 - 30 HP Deck Thickness: 11 Gauge Cutting Height from 1 In. to 4 In. Category I Hitch Blade Tip Speed: 14,566 Ft./Minute Type: Rear Discharge Front Antiscalping Roller: Optional Mulching Kit: Optional Rotor RPM: 2,278 RPM Driveline: 1-3/8 In. ASAE Category II Shipping Weight: 540 lbs. Set-up Time: 30 Minute 1 Year Warranty	
	BASE MACHINE *iMatch and iMatchconversion kit ordered separately.*	
0463XF	GM1072E Economy Rear Discharge Grooming Mower	USD $4,108.00
	DESTINATION AND LANGUAGE **Field Installed Options** **OPERATOR'S MANUAL AND DECALS**	
9200	French Operators Manual and Decal Kit (GM10E Series)	No Added Cost
	FRAME **Field Installed Options**	

Copyright © Deere & Company. All Rights Reserved.

GM1072E Economy Rear Discharge Grooming Mower

Code	Description	List price
	ROLLERS	
9450	Front Anti-Scalping Roller	USD $164.00
	CONVERSION KIT	
9630	I-Match Conversion Kit	USD $522.00
	CUTTING UNITS **Field Installed Options** **MULCH KITS**	
9690	Mulching Kit *For GM1072E.*	USD $514.00
	MISCELLANEOUS **ATTACHMENTS FOR FIELD CONVERSION** **MISCELLANEOUS**	
5BP006600	Mulching Kit (GM1072E)	USD $623.71
5BP950959B	French Manual Decal (GM10E Series)	USD $0.00
5BP001600	Front Antiscalping Roller	USD $207.91
5BP006750	iMatch Conversion Kit *Fits GM1048E, GM1060E, and GM1072E. Must also order longer 5BP0500404 driveline from parts for GM1048E or GM1060E.*	USD $761.20
BLV11199	John Deere Quik-Knect Driveline Yoke Bundle *Tractor Receiver Part number: BLV10953* *At least one tractor receiver bundle is needed per tractor. This bundle is removable and can be used on various tractors within the compatibility.* *One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).*	USD $300.30

Copyright © Deere & Company. All Rights Reserved.

FM4012 Flex Wing Grooming Mower

Code	Description	List price
0901XF	**FM4012 Flex Wing Grooming Mower**	
	Dimensions	
	Working Width (in.) (Max): 12 ft.	
	Working Length (in.) (Max): 11' 8"	
	Transport Dimensions (LxWxH): 11'3" x 7'7" x 10'x3"	
	Weight	
	Operating Weight: 1,999 lbs.	
	Shipping Weight: 2,005 lbs.	
	Operating tongue: 218 lbs.	
	Transport tongue: 384 lbs.	
	Tractor requirements	
	Engine HP Requirements: 540 RPM	
	PTO hp Range: 25-60 PTO HP	
	Gearbox	
	Ratio: 1:2.5 (wing), 1:1.92 (center)	
	Splitter Gearbox: 1:1	
	Mower Deck Gearbox: 25 hp (wing) 30 hp (center)	
	Drive	
	Type: Gear Box over V-Belt	
	Wing driveline: ASAE Category III	
	Input driveline: ASAE Category III CV	
	Hitch	
	Type: Adjustable Clevis	
	Category (Drawbar): 1	
	Adjustment: 4 positions	
	iMatch / Quick hitch: Not Applicable	
	Belts	
	Type: B-Section, Kevlar	
	Cutting	
	Cutting Width: 12 ft.	
	Cutting Width, Center deck: 60 in.	
	Cutting Width, Wing deck: 48 in.	
	Cutting Height, Range, in. (cm): 1.5” to 4.5”	
	Cutting Height, Adjustment: .5" increments (spacer)	
	Deck	
	Thickness, gauge: 10 Gauge	
	Overlap: 6"	
	Lift cylinders: 3 x 10"	
	Wing travel, degrees: 20 degrees up and down	

Copyright © Deere & Company. All Rights Reserved.

FM4012 Flex Wing Grooming Mower

Code	Description	List price
	Discharge type: Rear Discharge Blades Blade Tip Speed: 17, 900 ft./min (Center Deck) / 18,200 ft./min (Wing Decks) Number of Blades: 9 Blade Spindles: Ductile Iron, lubed for life; Sealed, ball bearing Spindle type: steel Spindle bearings: ball Overlap: Minimum 1.25 in. Dimensions, type 1: (9) .25 x 2.5 In. Tires Transport Tires: 2 ea. 20.5 x 8.8 in. Gauge Wheels Size: 8x3.5 in. Quantity: 10 Type: Solid Rubber Rollers Front and Rear Anti-Scalping Roller: Option (field installed) Lighting and safety Transport Lights: Option (field installed) Auto-Engage Transport Latch: Yes Markings: SMV Rear Chain Shields: Option (field installed) Warranty Warranty Machine Warranty: 1 Year Machine Warranty Spindle Warranty: 1 Year Spindle Warranty Gearbox Warranty: 6 Year Gearbox Warranty	
	BASE MACHINE	
0901XF	FM4012 Flex Wing Grooming Mower	USD $19,125.00
	DESTINATION AND LANGUAGE **Basic Factory Options** **DESTINATION**	
0202	United States	In Base Price
	OPERATOR'S MANUAL AND DECALS	
0409	English	In Base Price
0413	French	No Added Cost

Copyright © Deere & Company. All Rights Reserved.

FM4012 Flex Wing Grooming Mower

Code	Description	List price
0437	Spanish	No Added Cost
	FRAME **Field Installed Options** **CHAIN ENCLOSURES**	
9645	Rear Chain Shield	USD $412.00
	ATTACHMENTS FOR FIELD CONVERSION **CHAIN ENCLOSURES**	
5WD616077	Rear Chain Shield - 60" Deck *Note: Each deck requires (1) - 5WD616077 for center deck and (2) - 5WD626442 for the wing decks.*	USD $182.60
	HYDRAULICS **Field Installed Options** **HYDRAULIC KITS**	
9000	Hydraulic Wing Latch Release Kit	USD $706.00
	ATTACHMENTS FOR FIELD CONVERSION **HYDRAULIC KITS**	
5WD1029535	Hydraulic Wing Latch Release Kit	USD $910.80
	LIGHTS **Field Installed Options** **LIGHTING KITS**	
9705	Light Bar	USD $595.00
	MISCELLANEOUS **Field Installed Options** **ROLLERS**	
9640	Front Anti-Scalp Roller Kit	USD $130.00
9641	Rear Anti-Scalp Roller Kit	USD $80.00
	ATTACHMENTS FOR FIELD CONVERSION **ROLLERS**	
5WD618210	Rear Anti-Scalp Roller Kit *Note: Need to order Qty. 3 if ordering for all decks*	USD $138.60
5WD616079	Front Anti-Scalp Roller Kit *Note: Need to order Qty. 3 if ordering for all decks*	USD $103.40

Copyright © Deere & Company. All Rights Reserved.

FM4112 Flex Wing Grooming Mower

Code	Description	List price
0911XF	**FM4112 Flex Wing Grooming Mower**	
	Dimensions	
	Working Width (in.) (Max): 12.1ft (3.7m)	
	Working Length (in.) (Max): 171.3”	
	Transport Dimensions (LxWxH): 166.6 x 87.8 x 74 in	
	Weight	
	Operating Weight: 2811 lbs.	
	Shipping Weight: Shipping Weight: 2819 lbs.	
	Operating tongue: 336 lbs.	
	Transport tongue: 688 lbs.	
	Tractor requirements|	
	Engine HP Requirements: Tractor PTO Speed: 540 rpm	
	PTO hp Range: HP Requirements (Min.): 30 hp	
	Gearbox	
	Ratio: 1:1.9	
	Splitter Gearbox: 100 HP (74.6 kW)	
	Mower Deck Gearbox: 40 HP (29.8 kW)	
	Drive	
	Type: Gearbox over belt	
	Wing driveline: Category 3	
	Input driveline: Category 4 CV	
	Hitch	
	Type: Drawbar, Swivel	
	Category (Drawbar): 1 or 2	
	Adjustment: Self-leveling, multi-position	
	iMatch / Quick hitch: Not compatible	
	Belts	
	Type: V-belt	
	Adjustments: Spring Loaded Idler w/ Pivot	
	Cutting	
	Cutting Width: Cutting Width: 12'	
	Cutting Width, Center deck: 60"	
	Cutting Width, Wing deck: 48"	
	Cutting Height, Range, in. (cm): Cutting Height Range (in.)	
	1.5-5"	
	Cutting Height, Adjustment: 1/2" Spacers on casters	
	Deck	
	Thickness, gauge: 7 gauge	
	Overlap: 6 or 8.75"	

Copyright © Deere & Company. All Rights Reserved.

FM4112 Flex Wing Grooming Mower

Code	Description	List price
	Lift cylinders: 3.5 x 10 in. (8.9 x 25.4 cm) Wing travel, degrees: Up 25 and down 15 degrees Discharge type: Rear Blades Blade Tip Speed: Blade Speed: 18,000 (ft./per minute) Number of Blades: Number of Blades: 9 Blade Spindles: Blade Spindles: 9 Spindle type: Cast Iron Spindle bearings: Triple Ball Overlap: 1.5" Dimensions, type 1: 0.25 x 2.5 in (0.6 x 6.4 cm) Composition: Heat Treated - Alloy Steel Tires Transport Wheels: (2) 20.5" x 8.0" - 10 ply Caster Wheels Size: 15" x 6.00" - 6 ply Quantity: 8 Type: Pneumatic Bearings: Powder metal bushing Rollers Front and Rear Anti-Scalping Roller: Option (Field Installed) Lighting and safety Transport Lights: Standard Auto-Engage Transport Latch: Standard Markings: SMV Rear Chain Shields: Optional Warranty Warranty Machine Warranty: 1 Year Machine Warranty Spindle Warranty: 3 Year Spindle Warranty Gearbox Warranty: 10 Year Gearbox Warranty Front and Rear Anti-Scalping Roller: Option (Field Installed) Rear Chain Shield Option: Option (Field Installed) Hydraulic Wing Latch Release Kit: Option (Field Installed)	
	BASE MACHINE	
0911XF	FM4112 Flex Wing Grooming Mower	USD $25,716.00
	DESTINATION AND LANGUAGE	

Copyright © Deere & Company. All Rights Reserved.

FM4112 Flex Wing Grooming Mower

Code	Description	List price
	Basic Factory Options **DESTINATION**	
0202	United States	In Base Price
	OPERATOR'S MANUAL AND DECALS	
0409	English	In Base Price
0413	French	No Added Cost
0437	Spanish	No Added Cost
	FRAME **Field Installed Options** **CHAIN ENCLOSURES**	
9645	Rear Chain Shield	USD $411.00
	ATTACHMENTS FOR FIELD CONVERSION **CHAIN ENCLOSURES**	
5WD626442	Rear Chain Shield - 48" *FM4112 requires: (2) - 5WD626442 for the wing decks AND (1) - 5WD616077 for the center deck*	USD $225.51
5WD616077	Rear Chain Shield - 60" Deck *Note: FM4112 requires: (1) 5WD616007 for center deck AND (2) 5WD626442 for the wing decks*	USD $182.60
	HYDRAULICS **Field Installed Options** **HYDRAULIC KITS**	
9000	Hydraulic Wing Latch Release Kit	USD $697.00
	ATTACHMENTS FOR FIELD CONVERSION **HYDRAULICS**	
5WD1032454	Hydraulic Wing Latch Release Kit	USD $882.20
	MISCELLANEOUS **Field Installed Options** **ROLLERS**	
9640	Front Anti-Scalp Roller Kit	USD $390.00
9641	Rear Anti-Scalp Roller Kit	USD $240.00
	ATTACHMENTS FOR FIELD CONVERSION **MISCELLANEOUS**	

Copyright © Deere & Company. All Rights Reserved.

FM4112 Flex Wing Grooming Mower

Code	Description	List price
5WD618210	Rear Anti-Scalp Roller Kit	USD $138.60
5WD616079	Front Anti-Scalp Roller Kit	USD $103.40

Copyright © Deere & Company. All Rights Reserved.

FM4115 Flex Wing Grooming Mower

Code	Description	List price
0921XF	**FM4115 Flex Wing Grooming Mower**	
	Dimensions	
	Working Width (in.) (Max): 15.2ft (4.6m)	
	Working Length (in.) (Max): 182.2”	
	Transport Dimensions (LxWxH): 176.3 x 96.7 x 83.6 in	
	Weight	
	Operating Weight: 3446 lbs.	
	Shipping Weight: Shipping Weight: 3454 lbs.	
	Operating tongue: 336 lbs.	
	Transport tongue: 754 lbs.	
	Tractor requirements	
	Engine HP Requirements: Tractor PTO Speed: 540 rpm	
	PTO hp Range: HP Requirements (Min.): 35 hp	
	Gearbox	
	Ratio: 1:1.9	
	Splitter Gearbox: 100 HP (74.6 kW)	
	Mower Deck Gearbox: 40 HP (29.8 kW)	
	Drive	
	Type: Gearbox over belt	
	Wing driveline: Category 3	
	Input driveline: Category 4 CV	
	Hitch	
	Type: Drawbar, Swivel	
	Category (Drawbar): 1 or 2	
	Adjustment: Self-leveling, multi-position	
	iMatch / Quick hitch: Not compatible	
	Belts	
	Type: V-belt	
	Adjustments: Spring Loaded Idler w/ Pivot	
	Cutting	
	Cutting Width: Cutting Width: 15'	
	Cutting Width, Center deck: 72"	
	Cutting Width, Wing deck: 60"	
	Cutting Height, Range, in. (cm): Cutting Height Range (in.)	
	1.5-5"	
	Cutting Height, Adjustment: 1/2" Spacers on casters	
	Deck	
	Thickness, gauge: 7 gauge	
	Overlap: 6 or 8.75"	

Copyright © Deere & Company. All Rights Reserved.

FM4115 Flex Wing Grooming Mower

Code	Description	List price
	Lift cylinders: 3.5 x 10 in. (8.9 x 25.4 cm) Wing travel, degrees: Up 25 and down 15 degrees Discharge type: Rear Blades Blade Tip Speed: Blade Speed: 18,000 (ft./per minute) Number of Blades: Number of Blades: 9 Blade Spindles: Blade Spindles: 9 Spindle type: Cast Iron Spindle bearings: Triple Ball Overlap: 1.5" Dimensions, type 1: 0.25 x 2.5 in (0.6 x 6.4 cm) Composition: Heat Treated - Alloy Steel Tires Transport Wheels: (2) 20.5" x 8.0" - 10 ply Caster Wheels Size: 18" x 9.50" - 8 ply Quantity: 10 Type: Pneumatic Bearings: Powder metal bushing Rollers Front and Rear Anti-Scalping Roller: Option (Field Installed) Lighting and safety Transport Lights: Standard Auto-Engage Transport Latch: Standard Markings: SMV Rear Chain Shields: Optional Warranty Warranty Machine Warranty: 1 Year Machine Warranty Spindle Warranty: 3 Year Spindle Warranty Gearbox Warranty: 10 Year Gearbox Warranty Front and Rear Anti-Scalping Roller: Option (Field Installed) Rear Chain Shield Option: Option (Field Installed) Hydraulic Wing Latch Release Kit: Option (Field Installed)	
	BASE MACHINE	
0921XF	FM4115 Flex Wing Grooming Mower	USD $27,658.00
	DESTINATION AND LANGUAGE	

Copyright © Deere & Company. All Rights Reserved.

FM4115 Flex Wing Grooming Mower

Code	Description	List price
	Basic Factory Options **DESTINATION**	
0202	United States	In Base Price
	OPERATOR'S MANUAL AND DECALS	
0409	English	In Base Price
0413	French	No Added Cost
0437	Spanish	No Added Cost
	FRAME **Field Installed Options** **CHAIN ENCLOSURES**	
9645	Rear Chain Shield	USD $466.00
	ATTACHMENTS FOR FIELD CONVERSION **CHAIN ENCLOSURES**	
5WD616077	Rear Chain Shield - 60" Deck *Note: FM4115 requires: (2) 5WD616077 for wing decks and (1) 5WD616076 for the center deck.*	USD $182.60
5WD616076	REAR CHAIN SHIELD - 72" Deck *FM4115 requires: (1) 5WD616076 for the center deck and (2) 5WD616077 for the wing decks.*	USD $205.71
	HYDRAULICS **Field Installed Options** **HYDRAULIC KITS**	
9000	Hydraulic Wing Latch Release Kit	USD $697.00
	ATTACHMENTS FOR FIELD CONVERSION **HYDRAULICS**	
5WD1032454	Hydraulic Wing Latch Release Kit	USD $882.20
	MISCELLANEOUS **Field Installed Options** **ROLLERS**	
9640	Front Anti-Scalp Roller Kit	USD $390.00
9641	Rear Anti-Scalp Roller Kit	USD $240.00
	ATTACHMENTS FOR FIELD CONVERSION **MISCELLANEOUS**	

Copyright © Deere & Company. All Rights Reserved.

FM4115 Flex Wing Grooming Mower

Code	Description	List price
5WD616079	Front Anti-Scalp Roller Kit	USD $103.40
5WD618210	Rear Anti-Scalp Roller Kit	USD $138.60

Copyright © Deere & Company. All Rights Reserved.

GM1190 Rear Discharge Grooming Mower with Chain Shield

Code	Description	List price
0471XF	**GM1190 Rear Discharge Grooming Mower with Chain Shield** Type: Rear Discharge Tractor PTO Speed: 540 RPM Tractor Horsepower: 25 to 50 HP Shipping Weight: 1347 lbs. Mower Deck Gearbox HP: 50 HP Hitch: Category I Gearbox Ratio: 1:1.69 Driveline: Category IV Drive Type: Gearbox Over (2) V-Belts Deck Thickness: 7 Gauge Steel Plate Cutting Width: 90 In. Cutting Height Range: 1-1/2 In. to 8 In. Cutting Height Adjustment: Adjustable Arm Caster Wheels: (4) 13 In. x 5 In. Solid Caster Wheel Bearings: Tapered Roller Bearings Blade Tip Speed: 15,570 FPM Blade Spindles: 3 Cast Iron Blade Spindle Bearings: Tapered Roller Blade Overlap: 1-1/4 In. Blade Dimensions: (6) 1/4 In. x 2-1/2 In. Blade Composition: Heat-Treated Alloy Steel Belts: Power Band, B Section, Kevlar Belt Adjustment: Spring-Loaded Idler Assembly/Set-Up Time: 45 Minutes (Approximate) Approximate Operating Weight: 1,200 lbs. Front Center Roller Kit: Optional	
	BASE MACHINE	
0471XF	*iMatch and iMatch conversion kit ordered separately.* GM1190 Rear Discharge Grooming Mower with Chain Shield	USD $8,195.00
	FRAME	

Copyright © Deere & Company. All Rights Reserved.

GM1190 Rear Discharge Grooming Mower with Chain Shield

Code	Description	List price
	Field Installed Options **CONVERSION KIT**	
9000	iMatch Conversion Kit *Excludes economy series.*	USD $245.00
	ROLLERS	
9010	Front Roller Kit *Contains 1 roller.*	USD $170.00
	WHEELS AND TIRES **Basic Factory Options** **WHEELS AND TIRES**	
3010	Solid Tires	In Base Price
	MISCELLANEOUS **ATTACHMENTS FOR FIELD CONVERSION** **MISCELLANEOUS**	
5WD1032828	Front Roller Kit - Contains 1 Roller (GM1190) *Serial Number 1XFGM11XKB0000121 and above.*	USD $218.91
5WD1032830	iMatch Conversion Kit *For GM1190. Serial Number 1XFGM11XKB0000121 and above.*	USD $317.91
5WD1005400	iMatch Conversion Kit *For GM1190. Serial Number 1XFGM11XKB0000120 and below.*	USD $378.42

Copyright © Deere & Company. All Rights Reserved.

GM2109R Rear Discharge Grooming Mower with Rear Chain Shields and Front Antiscalping Roller

Code	Description	List price
0491XF	**GM2109R Rear Discharge Grooming Mower with Rear Chain Shields and Front Antiscalping Roller** Free Swinging Kick Back Blades Double Belt Drive with No Idler One Piece Balanced Steel Pulleys iMatch Compatible (Quick-Attach System) 4 Swivel Tires - Solid or Pneumatic Type: Rear Discharge Tractor PTO Speed: 540 RPM Tractor Horsepower: 30 to 70 HP Shipping Weight: 1608 lbs. Mower Deck Gearbox HP: 70 HP Hitch: Category I Gearbox Ratio: 1:2:08 Driveline: 1-3/8 In. ASAE Category IIII Drive Type: Gearbox Over V/Belt Deck Thickness: 8 Gauge Reinforced Deck Cutting Width: 110 In. Cutting Height Range: From 1.3 In. to 5.3 In. Cutting Height Adjustment: Spacer On Caster Caster Wheels: (4) 12 In. x 4 In. Solid or 13 In. x 6.5 In. (4 Ply, with Tubes) Air Caster Wheel Bearings: Shielded Roller Bearings Blade Tip Speed: 14,998 FPM Blade Spindles: (3) Cast Iron Blade Spindle Bearings: Shielded Tapered Bearings (2) Per Spindle Blade Composition: Heat-Treated Alloy Steel Blade Overlap: 1-1/8 In. Blade Dimensions: (6) 15-7/8 In. x 2-3/4 In. x 1/4 In.	

Copyright © Deere & Company. All Rights Reserved.

GM2109R Rear Discharge Grooming Mower with Rear Chain Shields and Front Antiscalping Roller

Code	Description	List price
	Belts: CX, Polyester/Cogged Belt Adjustment: Single Point, Slotted Track Adjustment - No Idlers Assembly/Set-Up Time: 30 Minutes (Approximate) Approximate Operating Weight: 1490 lbs. Front Center Roller Kit: Standard 1 Year Warranty	
	BASE MACHINE	
0491XF	*iMatch and iMatchconversion kit ordered separately.* GM2109R Rear Discharge Grooming Mower with Rear Chain Shields and Front Antiscalping Roller	USD $10,773.00
	FRAME **Field Installed Options** **CONVERSION KIT**	
9630	I-Match Conversion Kit	USD $471.00
	WHEELS AND TIRES **Basic Factory Options** **WHEELS AND TIRES**	
3050	Solid Gauge Wheel Tires	In Base Price
3040	Pneumatic Gauge Wheel Tires	USD $230.00
	MISCELLANEOUS **ATTACHMENTS FOR FIELD CONVERSION** **MISCELLANEOUS**	
5BP002800	iMatch Conversion Kit	USD $657.80
BLV11178	John Deere Quik-Knect Driveline Yoke Bundle *Tractor Receiver Part number: BLV10953* *At least one tractor receiver bundle is needed per tractor.* *This bundle is removable and can be used on various tractors within the compatibility.* *One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).*	USD $300.30

Copyright © Deere & Company. All Rights Reserved.

GM2190R Rear Discharge Grooming Mower with Rear Chain Shields and Front Antiscalping Roller

Code	Description	List price
0492XF	**GM2190R Rear Discharge Grooming Mower with Rear Chain Shields and Front Antiscalping Roller** Free Swinging Kick Back Blades Double Belt Drive with No Idler One Piece Balanced Steel Pulleys iMatch Compatible (Quick-Attach System) 4 Swivel Tires - Solid or Pneumatic Type: Rear Discharge Tractor PTO Speed: 540 RPM Tractor Horsepower: 30 to 70 HP Shipping Weight: 1198 lbs. Mower Deck Gearbox HP: 70 HP Hitch: Category I Gearbox Ratio: 1:2:08 Driveline: 1-3/8 In. ASAE Category IIII Drive Type: Gearbox Over V/Belt Deck Thickness: 8 Gauge Reinforced Deck Cutting Width: 90 In. Cutting Height Range: From 1.3 In. to 5.3 In. Cutting Height Adjustment: Spacer On Caster Caster Wheels: (4) 12 In. x 4 In. Solid or 13 In. x 6.5 In. (4 Ply, with Tubes) Air Caster Wheel Bearings: Shielded Roller Bearings Blade Tip Speed: 14,106 FPM Blade Spindles: (3) Cast Iron Blade Spindle Bearings: Shielded Tapered Bearings (2) Per Spindle Blade Composition: Heat-Treated Alloy Steel Blade Overlap: 1-3/8 In. Blade Dimensions: (6) 13 In. x 2-3/4 In. x 1/4 In.	

Copyright © Deere & Company. All Rights Reserved.

GM2190R Rear Discharge Grooming Mower with Rear Chain Shields and Front Antiscalping Roller

Code	Description	List price
	Belts: CX, Polyester/Cogged Belt Adjustment: Single Point, Slotted Track Adjustment - No Idlers Assembly/Set-Up Time: 30 Minutes (Approximate) Approximate Operating Weight: 1102 lbs. Front Center Roller Kit: Standard 1 Year Warranty	
	BASE MACHINE	
0492XF	*iMatch and iMatchconversion kit ordered separately.* GM2190R Rear Discharge Grooming Mower with Rear Chain Shields and Front Antiscalping Roller	USD $9,221.00
	FRAME **Field Installed Options** **CONVERSION KIT**	
9630	I-Match Conversion Kit	USD $471.00
	WHEELS AND TIRES **Basic Factory Options** **WHEELS AND TIRES**	
3050	Solid Gauge Wheel Tires	In Base Price
3040	Pneumatic Gauge Wheel Tires	USD $230.00
	MISCELLANEOUS **ATTACHMENTS FOR FIELD CONVERSION** **MISCELLANEOUS**	
5BP002800	iMatch Conversion Kit	USD $657.80
BLV11178	John Deere Quik-Knect Driveline Yoke Bundle *Tractor Receiver Part number: BLV10953* *At least one tractor receiver bundle is needed per tractor. This bundle is removable and can be used on various tractors within the compatibility.* *One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).*	USD $300.30

Copyright © Deere & Company. All Rights Reserved.

GM2060R Rear Discharge Grooming Mower with Rear Chain Shields

Code	Description	List price
0481XF	**GM2060R Rear Discharge Grooming Mower with Rear Chain Shields** High Blade Speed iMatch Compatible (Quick-Attach System) 4 Swivel Tires - Solid or Pneumatic Spindle Shafts Greased from the Top for Easy Service 20 to 50 HP Type: Rear Discharge Tractor PTO Speed: 540 RPM Shipping Weight: 609 lbs. Mower Deck Gearbox HP: 50 HP Hitch: Category I Gearbox Ratio: 1:3:09 (Spiral Gears) Driveline: 1-3/8 In. ASAE Category III Drive Type: Gear Box over V/Belt Deck Thickness: 8 Gauge Reinforced Deck Cutting Width: 60 In. Cutting Height Range: 1 In. to 5 In. Cutting Height Adjustment: Spacer On Caster Caster Wheels: (4) 10 In. x 3.2 In. Solid or 11 In. x 4 In. (4 Ply, with Tubes) Pneumatic Caster Wheel Bearings: Shielded Roller Bearings Blade Tip Speed: 16,929 FPM Blade Spindles: 3 Cast Iron Blade Spindle Bearings: Shielded Ball Bearings (2) Per Spindle Blade Composition: Heat-Treated Alloy Steel Blade Overlap: 1-1/8 In. Blade Dimensions: (3) 20-3/16 In. x 2 In. x 1/4 In. Belts: 5VX, Polyester/Cogged	

Copyright © Deere & Company. All Rights Reserved.

GM2060R Rear Discharge Grooming Mower with Rear Chain Shields

Code	Description	List price
	Belt Adjustment: Single Point, Slotted Track Adjustment - No Idlers Front Roller Kit: Optional Assembly/Set-Up Time: 30 Minutes (Approximate) Approximate Operating Weight: 550 lbs. Mulching Kit Available 1 Year Warranty	
	BASE MACHINE	
0481XF	*iMatch and iMatchconversion kit ordered separately.* GM2060R Rear Discharge Grooming Mower with Rear Chain Shields	USD $4,984.00
	FRAME **Field Installed Options** **ROLLERS**	
9450	Front Anti-Scalping Roller	USD $186.00
	CONVERSION KIT	
9630	I-Match Conversion Kit	USD $471.00
	CUTTING UNITS **Field Installed Options** **MULCH KITS**	
9690	Mulching Kit *GM2060*	USD $479.00
	WHEELS AND TIRES **Basic Factory Options** **WHEELS AND TIRES**	
3050	Solid Gauge Wheel Tires	In Base Price
3040	Pneumatic Gauge Wheel Tires	USD $97.00
	MISCELLANEOUS **ATTACHMENTS FOR FIELD CONVERSION** **MISCELLANEOUS**	
5BP045700	Mulching Kit (GM2060)	USD $578.60
5BP0099915	Front Antiscalping Roller	USD $225.51
5BP002800	iMatch Conversion Kit	USD $657.80

Copyright © Deere & Company. All Rights Reserved.

GM2060R Rear Discharge Grooming Mower with Rear Chain Shields

Code	Description	List price
BLV11200	John Deere Quik-Knect Driveline Yoke Bundle *Tractor Receiver Part number: BLV10953* *At least one tractor receiver bundle is needed per tractor. This bundle is removable and can be used on various tractors within the compatibility.* *One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).*	USD $300.30

Copyright © Deere & Company. All Rights Reserved.

GM2084R Rear Discharge Grooming Mower with Rear Chain Shields and Front Antiscalping Roller

Code	Description	List price
0483XF	**GM2084R Rear Discharge Grooming Mower with Rear Chain Shields and Front Antiscalping Roller** Three High-Suction Blades Standard iMatch Compatible (Quick-Attach System) 4 Swivel Tires - Solid or Pneumatic Spindle Shafts Greased from the Top for Easy Service Type: Rear Discharge Tractor PTO Speed: 540 RPM Tractor Horsepower: 25 to 50 HP Shipping Weight: 769 lbs. Mower Deck HP: 50 HP Hitch: Category I Gearbox Ratio: 1:3:09 (Spiral Gears) Driveline: 1-3/8 In. ASAE Category III Drive Type: Gearbox Over V/Belt Deck Thickness: 8 Gauge Reinforced Deck Cutting Width: 84 In. Cutting Height Range: 1 In. to 5 In. Cutting Height Adjustment: Spacer On Caster Caster Wheels: (4) 10 In. x 3.2 In. Solid or 11 In. x 4 In. (4 Ply, with Tubes) Pneumatic Caster Wheel Bearings: Shielded Roller Bearings Blade Tip Speed: 16,338 FPM Blade Spindles: 3 Cast Iron Blade Spindle Bearings: Shielded Ball Bearings (2) Per Spindle Blade Composition: Heat-Treated Alloy Steel Blade Overlap: 1-1/2 In. Blade Dimensions: (3) 28-1/2 In. x 2-1/4 In. Belts: 5VX, Polyester/Cogged	

Copyright © Deere & Company. All Rights Reserved.

GM2084R Rear Discharge Grooming Mower with Rear Chain Shields and Front Antiscalping Roller

Code	Description	List price
	Belt Adjustment: Single Point, Slotted Track Adjustment - No Idlers Front Roller Kit: Standard Assembly/Set-Up Time: 30 Minutes (Approximate) Approximate Operating Weight: 690 lbs. Mulching Kit Available 1 Year Warranty	
	BASE MACHINE	
0483XF	*iMatch and iMatchconversion kit ordered separately.* GM2084R Rear Discharge Grooming Mower with Rear Chain Shields and Front Antiscalping Roller	USD $6,118.00
	FRAME **Field Installed Options** **CONVERSION KIT**	
9630	I-Match Conversion Kit	USD $471.00
	CUTTING UNITS **Field Installed Options** **MULCH KITS**	
9690	Mulching Kit *GM2084*	USD $649.00
	WHEELS AND TIRES **Basic Factory Options** **WHEELS AND TIRES**	
3050	Solid Gauge Wheel Tires	In Base Price
3040	Pneumatic Gauge Wheel Tires	USD $97.00
	MISCELLANEOUS **ATTACHMENTS FOR FIELD CONVERSION** **MISCELLANEOUS**	
5BP047700	Mulching Kit (GM2084)	USD $785.40
5BP002800	iMatch Conversion Kit	USD $657.80
BLV11200	John Deere Quik-Knect Driveline Yoke Bundle *Tractor Receiver Part number: BLV10953* *At least one tractor receiver bundle is needed per tractor.*	USD $300.30

Copyright © Deere & Company. All Rights Reserved.

GM2084R Rear Discharge Grooming Mower with Rear Chain Shields and Front Antiscalping Roller

Code	Description	List price
	This bundle is removable and can be used on various tractors within the compatibility. *One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).*	

Copyright © Deere & Company. All Rights Reserved.

GM4060 Rear Discharge Grooming Mower

Code	Description	List price
0601XF	**GM4060 Rear Discharge Grooming Mower** Tractor PTO Horsepower: 15 to 35 HP Type: Rear Discharge Tractor PTO Speed: 540 RPM Operating Weight: 481 lbs. Hitch: Category I iMatch Quick Hitch: Factory Ready Driveline: Category 3 Drive Type: Gearbox Over V-Belt Deck Thickness: 10 Gauge Steel Plate Cutting Width: 60 In. Cutting Height Range: 1.5 in. to 5 In. Cutting Height Adjustment: Spacer On Caster Caster Wheels: (4) 8 In. x 3-1/4 In. Solid Caster Wheel Bearings: Roller Bearings Blade Tip Speed: 17,900 FPM Blade Spindles: 3 Cast Iron Blade Spindle Bearings: Greaseless Sealed Bearings Blade Overlap: 1-1/4 In. Blade Dimensions: (3) 1/4 In. x 2-1/2 In. Blade Composition: Heat-Treated Alloy Steel Belts: B Section, Aramid/Kevlar Belt Adjustment: Spring-Loaded Idler Assembly/Set-Up Time: 30 Minutes (Approximate) Front Roller Kit: Optional Rear Roller Kit: Optional Chain Guard: Optional	
	BASE MACHINE	
0601XF	GM4060 Rear Discharge Grooming Mower	USD $5,188.00
	DESTINATION AND LANGUAGE **Basic Factory Options** **DESTINATION**	

Copyright © Deere & Company. All Rights Reserved.

GM4060 Rear Discharge Grooming Mower

Code	Description	List price
0202	United States	In Base Price
	OPERATOR'S MANUAL AND DECALS	
0409	English OM	In Base Price
0413	French OM & Decal Kit	No Added Cost
0437	Spanish OM & Decal Kit	No Added Cost
	ATTACHMENTS FOR FIELD CONVERSION **OPERATOR'S MANUAL AND DECALS**	
5WD616090	SPANISH OM and DECAL KIT	USD $537.91
5WD613747	FRENCH OM and DECAL KIT	USD $525.80
	MISCELLANEOUS **Field Installed Options** **MISCELLANEOUS**	
9640	Front anti-scalp roller kit	USD $130.00
9641	Rear anti-scalp roller kit	USD $80.00
9642	Rear chain shield (60)	USD $149.00
	ATTACHMENTS FOR FIELD CONVERSION **MISCELLANEOUS**	
BLV10953	John Deere Quik Knect™ PTO receiver	USD $225.50
BLV11178	John Deere Quik-Knect Driveline Yoke Bundle	USD $300.30
5WD618210	Rear Anti-Scalp Roller Kit	USD $138.60
5WD616079	Front Anti-Scalp Roller Kit	USD $103.40
5WD616077	Rear Chain Shield - 60" Deck	USD $182.60

Copyright © Deere & Company. All Rights Reserved.

GM4072 Rear Discharge Grooming Mower

Code	Description	List price
0621XF	**GM4072 Rear Discharge Grooming Mower** Tractor PTO Horsepower: 25 to 35 HP Type: Rear Discharge Tractor PTO Speed: 540 RPM Operating Weight: 538 lbs. Hitch: Category I iMatch Quick Hitch: Factory Ready Driveline: Category 3 Drive Type: Gearbox Over V-Belt Deck Thickness: 10 Gauge Steel Plate Cutting Width: 72 In. Cutting Height Range: 1.5 In. to 5 In. Cutting Height Adjustment: Spacer On Caster Caster Wheels: (4) 8 In. x 3-1/4 In. Solid Caster Wheel Bearings: Roller Bearings Blade Tip Speed: 18,000 FPM Blade Spindles: 3 Cast Iron Blade Spindle Bearings: Greaseless Sealed Bearings Blade Overlap: 1 1/4 In. Blade Dimensions: (3) 1/4 In. x 2-1/2 In. Blade Composition: Heat-Treated Alloy Steel Belts: B Section, Aramid/Kevlar Belt Adjustment: Spring-Loaded Idler Assembly/Set-Up Time: 30 Minutes (Approximate) Front Roller Kit: Optional Rear Roller Kit: Optional Chain Guard: Optional	
	BASE MACHINE	
0621XF	GM4072 Rear Discharge Grooming Mower	USD $5,420.00
	DESTINATION AND LANGUAGE **Basic Factory Options** **DESTINATION**	

Copyright © Deere & Company. All Rights Reserved.

GM4072 Rear Discharge Grooming Mower

Code	Description	List price
0202	United States	In Base Price
	OPERATOR'S MANUAL AND DECALS	
0409	English OM	In Base Price
0413	French OM & Decal Kit	No Added Cost
0437	Spanish OM & Decal Kit	No Added Cost
	ATTACHMENTS FOR FIELD CONVERSION **OPERATOR'S MANUAL AND DECALS**	
5WD616090	SPANISH OM and DECAL KIT	USD $537.91
5WD613747	FRENCH OM and DECAL KIT	USD $525.80
	MISCELLANEOUS **Field Installed Options** **MISCELLANEOUS**	
9640	Front anti-scalp roller kit	USD $130.00
9641	Rear anti-scalp roller kit	USD $80.00
9643	Rear chain shield (72)	USD $169.00
	ATTACHMENTS FOR FIELD CONVERSION **MISCELLANEOUS**	
BLV10953	John Deere Quik Knect™ PTO receiver	USD $225.50
BLV11178	John Deere Quik-Knect Driveline Yoke Bundle	USD $300.30
5WD616079	Front Anti-Scalp Roller Kit	USD $103.40
5WD618210	Rear Anti-Scalp Roller Kit	USD $138.60
5WD616076	REAR CHAIN SHIELD - 72" Deck	USD $205.71

Copyright © Deere & Company. All Rights Reserved.

GM4084 Rear Discharge Grooming Mower

Code	Description	List price
0631XF	**GM4084 Rear Discharge Grooming Mower** Tractor PTO Horsepower: 25 to 35 HP Type: Rear Discharge Tractor PTO Speed: 540 RPM Operating Weight: 538 lbs. Hitch: Category I iMatch Quick Hitch: Factory Ready Driveline: Category 3 Drive Type: Gearbox Over V-Belt Deck Thickness: 10 Gauge Steel Plate Cutting Width: 72 In. Cutting Height Range: 1.5 In. to 5 In. Cutting Height Adjustment: Spacer On Caster Caster Wheels: (4) 8 In. x 3-1/4 In. Solid Caster Wheel Bearings: Roller Bearings Blade Tip Speed: 18,000 FPM Blade Spindles: 3 Cast Iron Blade Spindle Bearings: Greaseless Sealed Bearings Blade Overlap: 1 1/4 In. Blade Dimensions: (3) 1/4 In. x 2-1/2 In. Blade Composition: Heat-Treated Alloy Steel Belts: B Section, Aramid/Kevlar Belt Adjustment: Spring-Loaded Idler Assembly/Set-Up Time: 30 Minutes (Approximate) Front Roller Kit: Optional Rear Roller Kit: Optional Chain Guard: Optional	
	BASE MACHINE	
0631XF	GM4084 Rear Discharge Grooming Mower	USD $6,196.00
	DESTINATION AND LANGUAGE **Basic Factory Options** **DESTINATION**	

Copyright © Deere & Company. All Rights Reserved.

GM4084 Rear Discharge Grooming Mower

Code	Description	List price
0202	United States	In Base Price
	OPERATOR'S MANUAL AND DECALS	
0409	English OM	In Base Price
0413	French OM & Decal Kit	No Added Cost
0437	Spanish OM & Decal Kit	No Added Cost
	ATTACHMENTS FOR FIELD CONVERSION **OPERATOR'S MANUAL AND DECALS**	
5WD613747	FRENCH OM and DECAL KIT	USD $525.80
5WD616090	SPANISH OM and DECAL KIT	USD $537.91
	MISCELLANEOUS **Field Installed Options** **MISCELLANEOUS**	
9640	Front anti-scalp roller kit	USD $130.00
9641	Rear anti-scalp roller kit	USD $80.00
9644	Rear chain shield (84)	USD $193.00
	ATTACHMENTS FOR FIELD CONVERSION **MISCELLANEOUS**	
5WD616078	REAR CHAIN SHIELD (84)	USD $235.40
BLV10953	John Deere Quik Knect™ PTO receiver	USD $225.50
BLV11178	John Deere Quik-Knect Driveline Yoke Bundle	USD $300.30
5WD616079	Front Anti-Scalp Roller Kit	USD $103.40
5WD618210	Rear Anti-Scalp Roller Kit	USD $138.60

Copyright © Deere & Company. All Rights Reserved.

Material Collection System - 14-Bu 3-Bag

Code	Description	List price
0721XF	**Material Collection System - 14-Bu 3-Bag** 14-BU 3-BAG Material Collection System 3-Bag Collection Hopper Capacity: 14 Bushels Hitch: CAT I 3-point Mounted iMatch Compatible Rear PTO Gearbox Driven Blower 5 Blade High Efficiency Synthetic 15" Impeller Impeller Speed: 2250 RPM Steel Impeller Housing Boot to Blower Hose Diameter: 8 inches Bag Material: Frame Material: Sight Glass Fill Indicator or Wireless Fill Alarm Sensor Option High Effeciency Blow Molded Inducer and Transition Chute Easy-To-Empty Bags Fully and Evenly Filled Bags Tool-less access to chute for easy clog removal Tool-less boot removal and installation for quick changing of implements	
	BASE MACHINE	
0721XF	Material Collection System - 14-Bu 3-Bag	USD $3,885.00
	DESTINATION AND LANGUAGE **Basic Factory Options** **DESTINATION**	
0202	United States	No Added Cost
0184	Canada	No Added Cost
0205	Quebec, Canada	No Added Cost
	OPERATOR'S MANUAL	
0409	English OM	No Added Cost
0413	French OM	No Added Cost
0437	Spanish OM	No Added Cost
	DECK BOOT **Basic Factory Options** **DECK BOOT** *Includes boot, hardware, and hose*	

Copyright © Deere & Company. All Rights Reserved.

Material Collection System - 14-Bu 3-Bag

Code	Description	List price
2963	54D DECK BOOT KIT (MY19 and Older) *Only Available with 2551 Electric DFS*	USD ($41.00)
2964	54D DECK BOOT KIT (MY20+) *Only Available with 2551 Electric DFS*	USD ($52.00)
2962	60D DECK BOOT KIT	No Added Cost
	MISCELLANEOUS **Additional Factory Options** **MISCELLANEOUS**	
9702	Fill Sensor (Wireless)	USD $146.00
9315	Caster Wheel Storage Kit	USD $58.00
9701	Road Lighting Kit (1E, 1R, 2R) *Note: Includes ROPS light extension brackets and extension harnesses, SMV*	USD $198.00
	ATTACHMENTS FOR FIELD CONVERSION **MISCELLANEOUS**	
5CS1020	ROAD LIGHT KIT - 3R	USD $523.60
5CS1011	60D BOOT KIT	USD $478.51
5CS1007	SPANISH OM & DECAL KIT - MC2014	USD $201.31
5CS1009	54D BOOT KIT (MY19 AND OLDER)	USD $462.00
5CS1010	54D BOOT KIT (MY20+)	USD $444.40
5CS1018	CASTER WHEEL STORAGE KIT	USD $73.71

Copyright © Deere & Company. All Rights Reserved.

Material Collection System - 20-Bu Dump from Seat

Code	Description	List price
0731XF	**Material Collection System - 20-Bu Dump from Seat** 20-BU Dump from Seat - Material Collection System Aluminum Hopper Capacity: 20 Bushels Hitch: CAT I 3-point Mounted iMatch Compatible Mechanical Dump From Operator Seat or Electric Option Rear PTO Gearbox Driven Blower 5 Blade High Efficiency Synthetic 15" Impeller Impeller Speed: 2250-3250 RPM Steel Impeller Housing Boot to Blower Hose Diameter: 8 inches Frame Material: Sight Glass Fill Indicator or Wireless Fill Alarm Sensor Option High Effeciency Blow Molded Inducer and Transition Chute Tool-less access to chute for easy clog removal Tool-less boot removal and installation for quick changing of implements	
	BASE MACHINE	
0731XF	Material Collection System - 20-Bu Dump from Seat	USD $5,137.00
	DESTINATION AND LANGUAGE **Basic Factory Options** **DESTINATION**	
0202	United States	No Added Cost
0184	Canada	No Added Cost
0205	Quebec, Canada	No Added Cost
	OPERATOR'S MANUAL	
0409	English OM	No Added Cost
0413	French OM	No Added Cost
0437	Spanish OM	No Added Cost
	DECK BOOT **Basic Factory Options** **DECK BOOT**	
	Includes boot, hardware, and hose	
2963	54D DECK BOOT KIT (MY19 and Older) *Only Available with 2551 Electric DFS*	USD ($41.00)

Copyright © Deere & Company. All Rights Reserved.

1 July 2024

Material Collection System - 20-Bu Dump from Seat

Code	Description	List price
2964	54D DECK BOOT KIT (MY20+) *Only Available with 2551 Electric DFS*	USD ($52.00)
2962	60D DECK BOOT KIT	No Added Cost
2961	72D DECK BOOT KIT (2RLC,3R)	USD ($43.00)
	UNLOAD MATERIAL **Basic Factory Options** **DUMP FROM SEAT**	
2251	ELECTRIC DUMP-FROM-SEAT (1E, 1R, 2R) *Includes Wiring harness and Switch for 1E, 1R, 2R Tractors and Electric Actuator*	No Added Cost
2252	ELECTRIC DUMP-FROM-SEAT (3R) *Includes Wiring harness and Switch for 3R Tractors and Electric Actuator*	USD ($61.00)
	MISCELLANEOUS **Additional Factory Options** **MISCELLANEOUS**	
9702	Fill Sensor (Wireless)	USD $146.00
9315	Caster Wheel Storage Kit	USD $58.00
9701	Road Lighting Kit (1E, 1R, 2R) *Note: Includes ROPS light extension brackets and extension harnesses, SMV*	USD $198.00
9700	Road Lighting Kit (3R) *Note : Includes 7-pin connector, tail lamps, and SMV sign*	USD $476.00
	ATTACHMENTS FOR FIELD CONVERSION **MISCELLANEOUS**	
5CS1018	CASTER WHEEL STORAGE KIT	USD $73.71
5CS1011	60D BOOT KIT	USD $478.51
5CS1019	ROAD LIGHT KIT - 1E, 1R, 2R	USD $217.80
5CS1013	72D BOOT KIT 2RLC, 3R	USD $457.60
5CS1010	54D BOOT KIT (MY20+)	USD $444.40
5CS1006	FRENCH OM & DECAL KIT - MC2120	USD $255.20
5CS1020	ROAD LIGHT KIT - 3R	USD $523.60

Copyright © Deere & Company. All Rights Reserved.

Material Collection System - 20-Bu Dump from Seat

Code	Description	List price
5CS1017	FILL SENSOR (Wireless)	USD $184.80
5CS1008	SPANISH OM & DECAL KIT - MC2120	USD $281.60
5CS1009	54D BOOT KIT (MY19 AND OLDER)	USD $462.00

Copyright © Deere & Company. All Rights Reserved.

RC2048 Lift-Type Rotary Cutter

Code	Description	List price
0511XF	**RC2048 Lift-Type Rotary Cutter** Cutting Width: 48 In. (1220 mm) Cutting Height: 1.5 to 9 In. (38 to 229 mm) Cutting Capacity (Diameter):0 to 1 In. (0 to 25 mm) Cutting Chamber Depth: 7.5 In. (190 mm) Tractor PTO HP Range: 18 - 45 HP Tractor PTO: 540 RPM Implement PTO: ASABE Category III PTO Hitch: Lift-Type Category I, Adaptable to II, iMatch, and AutoHitch Compatible Overall Width: 51 In. (1,291.4 mm) Overall Length: 86.6 In. (2,199.6 mm) Deck Shape: Flat-open Round Back Deck Type: Single Deck Thickness: 11 Gauge (3 mm) Skirt Thickness: 11 Gauge (3 mm) PTO Driveline Options: Shear Bolt or Slip Clutch Drivelines Available Gear Case HP Rating: 45 HP Blade Type: Heat Treated, Suction Type Blades Blade Thickness: 0.5 In. (13 mm) Blade Width: 3 In. (76 mm) Blade Tip Speed: 13,090 fpm (66.5 m/s) Blade Pan Type: Round Pan-Type Blade Holder Blade Pan Diameter: 22.3 In. (567 mm) Solid Laminated Tire	
	BASE MACHINE *iMatch Hitch required if going on a 4M or 4R tractor equipped with R3/R4 tires to avoid possible interference between tractor tires and cutter front shield* *IMPORTANT: Use front and rear enclosures in areas where thrown objects could be hazardous.* *iMatch Hitch required with 2305 Tractor to facilitate driveline length.*	

Copyright © Deere & Company. All Rights Reserved.

RC2048 Lift-Type Rotary Cutter

Code	Description	List price
	Includes solid laminated tire kit	
0511XF	RC2048 Lift-Type Rotary Cutter	USD $1,955.00
	DESTINATION AND LANGUAGE **Field Installed Options** **OPERATOR'S MANUAL AND DECALS**	
904N	French OM & Decal Kit (RC20)	USD $145.00
	DRIVELINES **Basic Factory Options** **DRIVELINES**	
1000	Driveline with Slip Clutch *Recommended*	USD $172.00
1010	Driveline with Shear Bolt	In Base Price
	FRAME AND FEATURES **Basic Factory Options** **ENCLOSURES**	
	Use enclosures in areas where thrown objects could be hazardous.	
2000	Front and Rear Chain Enclosure *Note: Recommended*	USD $251.00
2010	Front Rubber with Foot Guards and Rear Metal Enclosure	In Base Price
2020	Front Chain and No Rear Enclosure	USD $62.00
	MISCELLANEOUS **ATTACHMENTS FOR FIELD CONVERSION** **MISCELLANEOUS**	
5TIFC711289	French Operator's Manual and Decal Kit for RC20 Series Rotary Cutters	USD $188.11
BLV11201	John Deere Quik-Knect Driveline Yoke Bundle *BLV11201 is compatible with:* *- RC2048 w/ Slip Clutch Driveline Serial Number Range 048199 & up* *- RC2048 w/ Shear Pin Driveline Serial Number Range 040602 & up* *Tractor Receiver Part number: BLV10953* *At least one tractor receiver bundle is needed per tractor.* *This bundle is removable and can be used on various tractors within the compatibility.*	USD $373.56

Copyright © Deere & Company. All Rights Reserved.

RC2048 Lift-Type Rotary Cutter

Code	Description	List price
	One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).	

Copyright © Deere & Company. All Rights Reserved.

RC2060 Lift-Type Rotary Cutter

Code	Description	List price
0512XF	**RC2060 Lift-Type Rotary Cutter** Cutting Width: 60 In. (1524 mm) Cutting Height: 1.5 to 9 In. (38 to 229 mm) Cutting Capacity (Diameter): 0 to 1 In. (0 to 25 mm) Cutting Chamber Depth: 7.5 In. (190 mm) Tractor PTO HP Range: 19 - 65 HP Tractor PTO: 540 RPM Implement PTO: ASABE Category III PTO Hitch: Lift-Type Category I, Adaptable to II, iMatch, and AutoHitch Compatible Overall Width: 63 In. (1,600.2 mm) Overall Length: 101.2 In. (2,570.5 mm) Deck Shape: Flat-open Round Back Deck Type: Single Deck Thickness: 11 Gauge (3 mm) Skirt Thickness: 11 Gauge (3 mm) PTO Driveline Options: Shear Bolt or Slip Clutch Drivelines Available Gear Case HP Rating: 65 HP Blade Type: Heat Treated, Suction Type Blades Blade Thickness: 0.5 In. (13 mm) Blade Width: 3 In. (76 mm) Blade Tip Speed: 14,355 fpm (72.8 m/s) Blade Pan Type: Round Pan-Type Blade Holder Blade Pan Diameter: 22.3 In. (567 mm) Solid Laminated Tire (Included)	
	BASE MACHINE *iMatch Hitch required if going on a 4M or 4R tractor equipped with R3/R4 tires to avoid possible interference between tractor tires and cutter front shield* *Includes solid laminated tire kit*	
0512XF	RC2060 Lift-Type Rotary Cutter	USD $2,200.00
	DESTINATION AND LANGUAGE **Field Installed Options** **OPERATOR'S MANUAL AND DECALS**	
904N	French OM & Decal Kit (RC20)	USD $145.00
	DRIVELINES **Basic Factory Options**	

Copyright © Deere & Company. All Rights Reserved.

RC2060 Lift-Type Rotary Cutter

Code	Description	List price
	DRIVELINES	
1000	Driveline with Slip Clutch *Recommended*	USD $186.00
1010	Driveline with Shear Bolt	In Base Price
	FRAME AND FEATURES **Basic Factory Options** **ENCLOSURES**	
	Use enclosures in areas where thrown objects could be hazardous.	
2000	Front and Rear Chain Enclosure *Note: Recommended*	USD $304.00
2010	Front Rubber with Foot Guards and Rear Metal Enclosure	In Base Price
2020	Front Chain and No Rear Enclosure	USD $74.00
	MISCELLANEOUS **ATTACHMENTS FOR FIELD CONVERSION** **MISCELLANEOUS**	
5TIFC711289	French Operator's Manual and Decal Kit for RC20 Series Rotary Cutters	USD $188.11
BLV11201	John Deere Quik-Knect Driveline Yoke Bundle *BLV11201 is compatible with:* *- RC2060 and RC2072 w/ Slip Clutch Driveline Serial Number Range 063419 & up* *- RC2060 and RC2072 w/ Shear Pin Driveline Serial Number Range 048269 & up* *Tractor Receiver Part number: BLV10953* *At least one tractor receiver bundle is needed per tractor. This bundle is removable and can be used on various tractors within the compatibility.* *One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).*	USD $373.56

Copyright © Deere & Company. All Rights Reserved.

RC2072 Lift-Type Rotary Cutter

Code	Description	List price
0513XF	**RC2072 Lift-Type Rotary Cutter** Cutting Width: 72 In. (1,830 mm) Cutting Height: 1.5 to 9 In. (38 to 229 mm) Cutting Capacity (Diameter): 0 to 1 In. (0 to 25 mm) Cutting Chamber Depth: 7.5 In. (190 mm) Tractor PTO HP Range: 25 - 65 HP Tractor PTO: 540 RPM Implement PTO: ASABE Category III PTO Hitch: Lift-Type Category I, Adaptable to II, iMatch, and AutoHitch Compatible Overall Width: 75 In. (1,905 mm) Overall Length: 111.5 In. (2,832.1 mm) Deck Shape: Flat-open Round Back Deck Type: Single Deck Thickness: 11 Gauge (3 mm) Skirt Thickness: 11 Gauge (3 mm) PTO Driveline Options: Shear Bolt or Slip Clutch Drivelines Available Gear Case HP Rating: 65 HP Blade Type: Heat Treated, Suction Type Blades Blade Thickness: 0.5 In. (13 mm) Blade Width: 3 In. (76 mm) Blade Tip Speed: 14,955 fpm (76 m/s) Blade Pan Type: Round Pan-Type Blade Holder Blade Pan Diameter: 28.5 In. (723.9 mm) Solid Laminated Tire (Included)	
	BASE MACHINE *iMatch Hitch required if going on a 4M or 4R tractor equipped with R3/R4 tires to avoid possible interference between tractor tires and cutter front shield* *Includes solid laminated tire kit*	
0513XF	RC2072 Lift-Type Rotary Cutter	USD $2,524.00
	DESTINATION AND LANGUAGE **Field Installed Options** **OPERATOR'S MANUAL AND DECALS**	
904N	French OM & Decal Kit (RC20)	USD $145.00
	DRIVELINES	

Copyright © Deere & Company. All Rights Reserved.

RC2072 Lift-Type Rotary Cutter

Code	Description	List price
	Basic Factory Options **DRIVELINES**	
1000	Driveline with Slip Clutch *Recommended*	USD $186.00
1010	Driveline with Shear Bolt	In Base Price
	FRAME AND FEATURES **Basic Factory Options** **ENCLOSURES**	
	Use enclosures in areas where thrown objects could be hazardous.	
2000	Front and Rear Chain Enclosure *Note: Recommended*	USD $422.00
2010	Front Rubber with Foot Guards and Rear Metal Enclosure	In Base Price
2020	Front Chain and No Rear Enclosure	USD $113.00
	MISCELLANEOUS **ATTACHMENTS FOR FIELD CONVERSION** **MISCELLANEOUS**	
5TIFC711289	French Operator's Manual and Decal Kit for RC20 Series Rotary Cutters	USD $188.11
BLV11201	John Deere Quik-Knect Driveline Yoke Bundle *BLV11201 is compatible with:* *- RC2060 and RC2072 w/ Slip Clutch Driveline Serial Number Range 063419 & up* *- RC2060 and RC2072 w/ Shear Pin Driveline Serial Number Range 048269 & up* *Tractor Receiver Part number: BLV10953* *At least one tractor receiver bundle is needed per tractor. This bundle is removable and can be used on various tractors within the compatibility.* *One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).*	USD $373.56

Copyright © Deere & Company. All Rights Reserved.

RC2084 Lift-Type Rotary Cutter

Code	Description	List price
0514XF	**RC2084 Lift-Type Rotary Cutter**	
	Cutting Width: 84 In. (2,134 mm)	
	Cutting Height: 1.75 to 11 In. (44.45 to 279.4 mm)	
	Cutting Capacity (Diameter): 0 to 1 In. (0 to 25 mm)	
	Cutting Chamber Depth: 9.75 In. (248 mm)	
	Tractor PTO HP Range: 45 - 90 HP	
	Tractor PTO: 540 RPM	
	Implement PTO: ASABE Category IIII PTO	
	Hitch: Lift-Type Category II, Category II Quick Hitch Compatible	
	Overall Width: 88 In. (2,235 mm)	
	Overall Length: 124 In. (3,150 mm)	
	Deck Shape: Flat-open Round Back	
	Deck Type: Single	
	Deck Thickness: 10 Gauge (3.4 mm)	
	Skirt Thickness: 10 Gauge (3.4 mm)	
	PTO Driveline Options: Slip Clutch Standard	
	Gear Case HP Rating: 90 HP	
	Blade Type: Heat Treated, Suction Type Blades	
	Blade Thickness: 0.5 In. (13 mm)	
	Blade Width: 3 In. (76 mm)	
	Blade Tip Speed: 14,380 fpm (73 m/s)	
	Blade Pan Type: Round Pan-Type Blade Holder	
	Blade Pan Diameter: 32.5 In. (825.5 mm)	
	Tire Options: Single or Dual Laminated Tire	
	BASE MACHINE	
	iMatch Hitch required if going on a 4M or 4R tractor equipped with R3/R4 tires to avoid possible interference between tractor tires and cutter front shield	
	Includes Driveline with Slip Clutch	
0514XF	RC2084 Lift-Type Rotary Cutter	USD $4,686.00
	DESTINATION AND LANGUAGE	
	Field Installed Options	
	OPERATOR'S MANUAL AND DECALS	
904N	French OM & Decal Kit (RC20)	USD $145.00
	FRAME AND FEATURES	
	Basic Factory Options	
	ENCLOSURES	
	Use enclosures in areas where thrown objects could be hazardous.	

Copyright © Deere & Company. All Rights Reserved.

RC2084 Lift-Type Rotary Cutter

Code	Description	List price
2000	Front and Rear Chain Enclosure	In Base Price
	WHEELS AND TIRES **Basic Factory Options** **WHEELS AND TIRES**	
3000	Laminated Tire	In Base Price
3010	Dual Tire Laminated	USD $133.00
	MISCELLANEOUS **ATTACHMENTS FOR FIELD CONVERSION** **MISCELLANEOUS**	
5TIFC711289	French Operator's Manual and Decal Kit for RC20 Series Rotary Cutters	USD $188.11
BLV11203	John Deere Quik-Knect Driveline Yoke Bundle *BLV11203 is compatible with RC2084 w/ Slip Clutch Driveline Serial Number Range 105933 & up* *Tractor Receiver Part number: BLV10953* *At least one tractor receiver bundle is needed per tractor.* *This bundle is removable and can be used on various tractors within the compatibility.* *One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).*	USD $376.37

Copyright © Deere & Company. All Rights Reserved.

RC4048 Rotary Cutter

Code	Description	List price
2701XF	**RC4048 Rotary Cutter** Overall Width: 52.3 in. Overall Length: 90.3 in Overall Weight: 410 lbs. CAPACITY Cutting Width: 48 In. (1220 mm) Cutting Height: 2 to 9 In. Cutting Capacity (Diameter): 0 to 1 In. (0 to 25 mm) Cutting Chamber Depth: 7 In. (178 mm) TRACTOR COMPATIBILITY Tractor PTO HP Range: 15-40 HP Tractor PTO: 540 RPM Implement PTO: ASABE Category III PTO Gear Case HP Rating: 40 HP HITCH Type: Lift-Type Category: I iMatch Compatible: Yes AutoHitch Compatible: no DECK Deck Shape: Flat-open Round Back Deck Type: Single Deck Thickness: 12 Gauge (2.79 mm) Skirt Thickness: 12 Gauge (2.79mm) DRIVELINE PTO Driveline Options: Slip Clutch Drivelines Quick-Knect™ compatible: Yes BLADES Blade Tip Speed: 13,100 Blade Type: Heat Treated, Suction Type Blades Blade Thickness: 0.5 In. (13 mm) Blade Width: 3 In. (76 mm) Blade Pan Type: Oval Pan-Type Blade Holder Blade Pan Diameter: 9.25 x 20.5 in. (235 x 622 cm) WHEELS Quantity: 1 Tire: Laminated Tire Diameter laminated: 16 in. (406 mm) Width laminated: 4 in. (101.6 mm)	

Copyright © Deere & Company. All Rights Reserved.

RC4048 Rotary Cutter

Code	Description	List price
	SAFETY Markings: Standard Front deflector: Front Chain Shield Rear deflector: Rear Chain Shield Warranty: 1 year, Gear Box - 3 years Chain Shields: Front & Rear Standard	
	BASE MACHINE	
	Rotary Cutters come in multiples of 2 per order *IMPORTANT: Use front and rear enclosures in areas where thrown objects could be hazardous.*	
2701XF	RC4048 Rotary Cutter	USD $2,608.00
	DESTINATION AND LANGUAGE **Basic Factory Options** **DESTINATION**	
0202	United States	No Added Cost
	OPERATOR'S MANUAL AND DECALS	
	OM & Decal Kits come in a quantity of 2 per order	
0409	English OM and Decals Kit	No Added Cost
0413	French OM and Decals Kit	No Added Cost
0437	Spanish Om and Decals Kit	No Added Cost
	MISCELLANEOUS **Field Installed Options** **MISCELLANEOUS**	
	Miscellaneous Options come in a quantity of 2 per order	
9864	Skid Shoes (Replaceable)	USD $82.00
	ATTACHMENTS FOR FIELD CONVERSION **MISCELLANEOUS**	
5WD1038335	Skid Shoes (Replaceable)	USD $100.11
BLV10953	John Deere Quik Knect™ PTO receiver	USD $225.50
BLV11178	John Deere Quik-Knect Driveline Yoke Bundle	USD $300.30

Copyright © Deere & Company. All Rights Reserved.