



Gator GS

Code	Description	List price
0664XF	Gator GS ENGINE:14.25 HP* (10.63 kW) 402cc (24.5 cu in) Single Cylinder Overhead Valve (OHV) Air-Cooled with Electronic Fuel Injection (EFI)Full Pressure Lubrication5.2 Gal (20 L) Fuel TankELECTRICAL:12V 440 CCA BatteryStarter/GeneratorTRANSAXLE/TRANSMISSION:Continuously Variable Transmission (CVT) Single-Speed Transaxle19.5 MPH (31.4 KM/H) Maximum SpeedSelf-Adjusting Drum BrakesSTEERING/SUSPENSION:Self-Compensating Double Reduction Helical Rack-and-Pinion SteeringIndependent Automotive-Style Strut Front SuspensionSwing Arm with Coil Spring Over Shock Rear SuspensionFRAME/STYLED PARTS:Robotic welded automotive ladder-style steel frame protected with a multi-step full-immersion phosphate treatment, electro-deposition epoxy-based coating, and an electrostatic applied polyester/urethane powder topcoatCustom-formulated thermoplastic olefin painted with a two-part top coat of high-luster automotive- grade polyurethaneOPERATOR STATION:High-Back Bucket SeatsWalk-Through PlatformGlove BoxHour MeterTwo Cup HoldersDIMENSIONS:119.37 in (303.2 cm) Long x 49.3 in (125.3 cm) Wide x 74.02 in (188 cm) High4.5 in (11.5 cm) minimum ground clearance1500 lb (680.4 kg) total payload capacity1500 lb (544.3 kg) towing capacityCARGO BOX:41.1 in (104.4 cm) Long x 45.9 in (116.6 cm) Wide x 11.9 in (30.2 cm) High800 lb (362.9 kg) load capacityTilting BoxHinged TailgateTIRES:20x10-10 4-ply Turf Tires Front and RearMISCELLANEOUS:Rear Receiver HitchSun CanopyWindshield*Engine HP is Provided by the Engine Manufacturer to be Used For Comparison Purposes Only, Actual Operating HP will be Less.	
	BASE MACHINE <i>Windshields are now included in-base starting with MY26.</i> <i>Base Machine Suggested List Price Does Not Include \$950 USD Destination Charge.</i> <i>Not Available for Sale in the State of California</i>	
0664XF	Gator GS	USD \$15,869.00
	DESTINATION AND LANGUAGE Basic Factory Options DESTINATION	



Gator GS

Code	Description	List price
001A	United States / Canada OPERATOR'S MANUAL	In Base Price
0443	Operator's Manual - English	In Base Price
8014	CARGO BOX Additional Factory Options CARGO BOX Cargo Box Mat	USD \$150.00
9008	Field Installed Options CARGO BOX LIFT Cargo Box Power Lift	USD \$1,921.00
9904	UTILITY AND PROTECTION PACKAGES Field Installed Options PROTECTION PACKAGE Front Brush Guard	USD \$398.00
183N	MACHINE CONNECTIVITY Basic Factory Options CONNECTIVITY HARDWARE JDLINK™ Modem <i>Includes factory installed harness and all required brackets.</i> <i>Includes field installed JDLINK™ M Modem - 4G capable.</i> <i>Option code is REQUIRED for ALL countries where JDLINK™ is AVAILABLE. Reference JDLINK™ Compatibility document in Sales Manual for a complete list of country availability.</i> <i>JDLINK™ connectivity can be enabled in John Deere Operations Center. Connectivity service is subject to country availability.</i> <i>JDLINK™ connectivity links you to your work and results, your team, your advisors, your dealer, and your equipment. See Ag Sales Manual for details.</i>	In Base Price



Gator GS Electric

Code	Description	List price
0672XF	Gator GS Electric DRIVE SYSTEM / ELECTRICAL: 5 kW (6.7 HP) Drive Motor 48V System with 8 Trojan T-105 Batteries 17.5 MPH (28.2 KM/H) Maximum Speed Self-Adjusting Drum Brakes STEERING/SUSPENSION: Self-Compensating Double Reduction Helical Rack-and-Pinion Steering Independent Automotive-Style Strut Front Suspension Swing Arm with Coil Spring Over Shock Rear Suspension FRAME/STYLED PARTS: Robotic welded automotive ladder-style steel frame protected with a multi-step full-immersion phosphate treatment, electro-deposition epoxy-based coating, and an electrostatic applied polyester/urethane powder topcoat Custom-formulated thermoplastic olefin painted with a two-part top coat of high-luster automotive- grade polyurethane OPERATOR STATION: High-Back Bucket Seats Walk-Through Platform Glove Box Hour Meter Two Cup Holders DIMENSIONS: 119.37 in (303.2 cm) Long x 49.3 in (125.3 cm) Wide x 74.02 in (188 cm) High 4.5 in (11.5 cm) minimum ground clearance 1500 lb (680.4 kg) total payload capacity 1500 lb (544.3 kg) towing capacity CARGO BOX: 41.1 in (104.4 cm) Long x 45.9 in (116.6 cm) Wide x 11.9 in (30.2 cm) High 800 lb (362.9 kg) load capacity Tilting Box Hinged Tailgate	



Gator GS Electric

Code	Description	List price
	TIRES: 20x10-10 4-ply Turf Tires Front and Rear MISCELLANEOUS: Rear Receiver Hitch Sun Canopy	
0672XF	BASE MACHINE <i>Base Machine Suggested List Price Does Not Include \$950 USD Destination Charge.</i> Gator GS Electric	USD \$15,799.00
001A	DESTINATION AND LANGUAGE Basic Factory Options DESTINATION United States / Canada	In Base Price
0443	OPERATOR'S MANUAL Operator's Manual - English	In Base Price
BUC11761	ATTACHMENTS FOR FIELD CONVERSION OPERATOR'S MANUAL AND DECAL KIT Gator GS - Spanish Kit <i>Includes Spanish Operator's Manual and Spanish Label Kit</i>	USD \$359.51
9003	OPERATOR'S STATION AND CONTROLS Field Installed Options WINDSHIELD Windshield, Folding Clear	USD \$401.00
BUC11679	ATTACHMENTS FOR FIELD CONVERSION WINDSHIELD Hinged poly windshield	USD \$416.23
BUC11678	ROOF Sun Canopy	USD \$874.19
9904	UTILITY AND PROTECTION PACKAGES Field Installed Options PROTECTION PACKAGE Front Brush Guard	USD \$379.00



Gator GS Electric

Code	Description	List price
	GUARDS ATTACHMENTS FOR FIELD CONVERSION FRONT BRUSH GUARD	
BUC11681	Front Brush Guard	USD \$392.69



Gator GS Electric

Code	Description	List price
0673XF	Gator GS Electric DRIVE SYSTEM / ELECTRICAL: 5 kW (6.7 HP) Drive Motor 51.2V system with a Lithium Ion battery option, or a 48V system with an 8 Trojan T-105 batteries option 17.5 MPH (28.2 KM/H) Maximum Speed Self-Adjusting Drum Brakes STEERING/SUSPENSION: Self-Compensating Double Reduction Helical Rack-and-Pinion Steering Independent Automotive-Style Strut Front Suspension Swing Arm with Coil Spring Over Shock Rear Suspension FRAME/STYLED PARTS: Robotic welded automotive ladder-style steel frame protected with a multi-step full-immersion phosphate treatment, electro-deposition epoxy-based coating, and an electrostatic applied polyester/urethane powder topcoat Custom-formulated thermoplastic olefin painted with a two-part top coat of high-luster automotive- grade polyurethane OPERATOR STATION: High-Back Bucket Seats Walk-Through Platform Glove Box Hour Meter Two Cup Holders DIMENSIONS: 119.37 in (303.2 cm) Long x 49.3 in (125.3 cm) Wide x 74.02 in (188 cm) High 4.5 in (11.5 cm) minimum ground clearance 1500 lb (680.4 kg) total payload capacity 1500 lb (544.3 kg) towing capacity CARGO BOX: 41.1 in (104.4 cm) Long x 45.9 in (116.6 cm) Wide x 11.9 in (30.2 cm) High 800 lb (362.9 kg) load capacity Tilting Box	



Gator GS Electric

Code	Description	List price
	Hinged Tailgate TIRES: 20x10-10 4-ply Turf Tires Front and Rear MISCELLANEOUS: Rear Receiver Hitch Sun Canopy	
	BASE MACHINE <i>Base Machine Suggested List Price Does Not Include \$950 USD Destination Charge.</i>	
0673XF	Gator GS Electric	USD \$15,799.00
	DESTINATION AND LANGUAGE Basic Factory Options DESTINATION	
001A	United States / Canada	In Base Price
	OPERATOR'S MANUAL	
0443	Operator's Manual - English	In Base Price
	ATTACHMENTS FOR FIELD CONVERSION OPERATOR'S MANUAL AND DECAL KIT	
BUC11761	Gator GS - Spanish Kit <i>Includes Spanish Operator's Manual and Spanish Label Kit</i>	USD \$359.51
	ELECTRICAL Basic Factory Options BATTERIES	
3350	LEAD ACID BATTERIES <i>Eight Trojan® T-105 batteries - 48V (6V × 8)</i>	In Base Price
3351	LITHIUM ION BATTERY <i>51.2V Lithium Ion Battery</i>	USD \$2,667.00
	OPERATOR'S STATION AND CONTROLS Field Installed Options WINDSHIELD	
9003	Windshield, Folding Clear	USD \$409.00
	ATTACHMENTS FOR FIELD CONVERSION	



Gator GS Electric

Code	Description	List price
	WINDSHIELD	
BUC11679	Hinged poly windshield	USD \$416.23
	ROOF	
BUC11678	Sun Canopy	USD \$874.19
	UTILITY AND PROTECTION PACKAGES	
	Field Installed Options	
	PROTECTION PACKAGE	
9904	Front Brush Guard	USD \$387.00
	MACHINE CONNECTIVITY	
	Basic Factory Options	
	CONNECTIVITY HARDWARE	
183N	JDLink™ Modem <i>Includes factory installed harness and all required brackets.</i> <i>Includes field installed JDLink™ M Modem - 4G capable.</i> <i>Option code is REQUIRED for ALL countries where JDLink™ is AVAILABLE. Reference JDLink™ Compatibility document in Sales Manual for a complete list of country availability.</i> <i>JDLink™ connectivity can be enabled in John Deere Operations Center. Connectivity service is subject to country availability.</i> <i>JDLink™ connectivity links you to your work and results, your team, your advisors, your dealer, and your equipment. See Ag Sales Manual for details.</i>	In Base Price
	GUARDS	
	ATTACHMENTS FOR FIELD CONVERSION	
	FRONT BRUSH GUARD	
BUC11681	Front Brush Guard	USD \$392.69

**Gator GS (ALDI)**

Code	Description	List price
0662XF	Gator GS (ALDI) ENGINE: 14.25 HP* (10.63 kW) 402cc (24.5 cu in) Single Cylinder Overhead Valve (OHV) Air-Cooled with Electronic Fuel Injection (EFI) Full Pressure Lubrication 5.2 Gal (20 L) Fuel Tank ELECTRICAL: 12V 440 CCA Battery Starter/Generator TRANSAXLE/TRANSMISSION: Continuously Variable Transmission (CVT) Single-Speed Transaxle 17.5 MPH (28.2 KM/H) Maximum Speed Self-Adjusting Drum Brakes STEERING/SUSPENSION: Self-Compensating Double Reduction Helical Rack-and- Pinion Steering Independent Automotive-Style Strut Front Suspension Swing Arm with Coil Spring Over Shock Rear Suspension FRAME/STYLED PARTS: Robotic welded automotive ladder-style steel frame protected with a multi-step full-immersion phosphate treatment, electro-deposition epoxy-based coating, and an electrostatic applied polyester/urethane powder topcoat Custom-formulated thermoplastic olefin painted with a two-part top coat of high-luster automotive- grade polyurethane OPERATOR STATION: High-Back Bucket Seats Walk-Through Platform Glove Box Hour Meter Two Cup Holders DIMENSIONS: 119.37 in (303.2 cm) Long x 49.3 in (125.3 cm) Wide x	



Gator GS (ALDI)

Code	Description	List price
	74.02 in (188 cm) High 4.5 in (11.5 cm) minimum ground clearance 1500 lb (680.4 kg) total payload capacity 1500 lb (544.3 kg) towing capacity CARGO BOX: 41.1 in (104.4 cm) Long x 45.9 in (116.6 cm) Wide x 11.9 in (30.2 cm) High 800 lb (362.9 kg) load capacity Tilting Box Hinged Tailgate TIRES: 20x10-10 4-ply Turf Tires Front and Rear MISCELLANEOUS: Rear Receiver Hitch Sun Canopy *Engine HP is Provided by the Engine Manufacturer to be Used For Comparison Purposes Only, Actual Operating HP will be Less.	
	BASE MACHINE <i>Base Machine Suggested List Price Does Not Include \$950 USD Destination Charge. Not Available for Sale in the State of California</i>	
0662XF	Gator GS (ALDI)	USD \$14,999.00
	DESTINATION AND LANGUAGE Basic Factory Options DESTINATION	
001A	United States / Canada	In Base Price
	OPERATOR'S MANUAL	
0443	Operator's Manual - English	In Base Price
	ATTACHMENTS FOR FIELD CONVERSION OPERATOR'S MANUAL AND DECAL KIT	
BUC11761	Gator GS - Spanish Kit <i>Includes Spanish Operator's Manual and Spanish Label Kit</i>	USD \$359.51
	OPERATOR'S STATION AND CONTROLS Field Installed Options	



Gator GS (ALDI)

Code	Description	List price
9003	WINDSHIELD	
	Windshield, Folding Clear	USD \$401.00
BUC11679	ATTACHMENTS FOR FIELD CONVERSION	
	WINDSHIELD	
BUC11679	Hinged poly windshield	USD \$416.23
BUC11678	ROOF	
	Sun Canopy	USD \$874.19
9904	UTILITY AND PROTECTION PACKAGES	
	Field Installed Options	
9904	PROTECTION PACKAGE	
	Front Brush Guard	USD \$379.00
BUC11681	GUARDS	
	ATTACHMENTS FOR FIELD CONVERSION	
BUC11681	FRONT BRUSH GUARD	
BUC11681	Front Brush Guard	USD \$392.69

**Gator GS (ALDI)**

Code	Description	List price
0663XF	Gator GS (ALDI) ENGINE: 14.25 HP* (10.63 kW) 402cc (24.5 cu in) Single Cylinder Overhead Valve (OHV) Air-Cooled with Electronic Fuel Injection (EFI) Full Pressure Lubrication 5.2 Gal (20 L) Fuel Tank ELECTRICAL: 12V 440 CCA Battery Starter/Generator TRANSAXLE/TRANSMISSION: Continuously Variable Transmission (CVT) Single-Speed Transaxle 17.5 MPH (28.2 KM/H) Maximum Speed Self-Adjusting Drum Brakes STEERING/SUSPENSION: Self-Compensating Double Reduction Helical Rack-and- Pinion Steering Independent Automotive-Style Strut Front Suspension Swing Arm with Coil Spring Over Shock Rear Suspension FRAME/STYLED PARTS: Robotic welded automotive ladder-style steel frame protected with a multi-step full-immersion phosphate treatment, electro-deposition epoxy-based coating, and an electrostatic applied polyester/urethane powder topcoat Custom-formulated thermoplastic olefin painted with a two-part top coat of high-luster automotive- grade polyurethane OPERATOR STATION: High-Back Bucket Seats Walk-Through Platform Glove Box Hour Meter Two Cup Holders DIMENSIONS: 119.37 in (303.2 cm) Long x 49.3 in (125.3 cm) Wide x	



Gator GS (ALDI)

Code	Description	List price
	74.02 in (188 cm) High 4.5 in (11.5 cm) minimum ground clearance 1500 lb (680.4 kg) total payload capacity 1500 lb (544.3 kg) towing capacity CARGO BOX: 41.1 in (104.4 cm) Long x 45.9 in (116.6 cm) Wide x 11.9 in (30.2 cm) High 800 lb (362.9 kg) load capacity Tilting Box Hinged Tailgate TIRES: 20x10-10 4-ply Turf Tires Front and Rear MISCELLANEOUS: Rear Receiver Hitch Sun Canopy *Engine HP is Provided by the Engine Manufacturer to be Used For Comparison Purposes Only, Actual Operating HP will be Less.	
	BASE MACHINE <i>Base Machine Suggested List Price Does Not Include \$950 USD Destination Charge. Not Available for Sale in the State of California</i>	
0663XF	Gator GS (ALDI)	USD \$14,999.00
	DESTINATION AND LANGUAGE Basic Factory Options DESTINATION	
001A	United States / Canada	In Base Price
	OPERATOR'S MANUAL	
0443	Operator's Manual - English	In Base Price
	ATTACHMENTS FOR FIELD CONVERSION OPERATOR'S MANUAL AND DECAL KIT	
BUC11761	Gator GS - Spanish Kit <i>Includes Spanish Operator's Manual and Spanish Label Kit</i>	USD \$359.51
	OPERATOR'S STATION AND CONTROLS Field Installed Options	



Gator GS (ALDI)

Code	Description	List price
WINDSHIELD		
9003	Windshield, Folding Clear	USD \$409.00
ATTACHMENTS FOR FIELD CONVERSION		
WINDSHIELD		
BUC11679	Hinged poly windshield	USD \$416.23
ROOF		
BUC11678	Sun Canopy	USD \$874.19
UTILITY AND PROTECTION PACKAGES		
Field Installed Options		
PROTECTION PACKAGE		
9904	Front Brush Guard	USD \$387.00
MACHINE CONNECTIVITY		
Basic Factory Options		
CONNECTIVITY HARDWARE		
183N	JDLink™ Modem <i>Includes factory installed harness and all required brackets.</i> <i>Includes field installed JDLink™ M Modem - 4G capable.</i> <i>Option code is REQUIRED for ALL countries where JDLink™ is AVAILABLE. Reference JDLink™ Compatibility document in Sales Manual for a complete list of country availability.</i> <i>JDLink™ connectivity can be enabled in John Deere Operations Center. Connectivity service is subject to country availability.</i> <i>JDLink™ connectivity links you to your work and results, your team, your advisors, your dealer, and your equipment. See Ag Sales Manual for details.</i>	In Base Price
GUARDS		
ATTACHMENTS FOR FIELD CONVERSION		
FRONT BRUSH GUARD		
BUC11681	Front Brush Guard	USD \$392.69

**Gator GS Electric (ALDI)**

Code	Description	List price
0671XF	Gator GS Electric (ALDI) DRIVE SYSTEM / ELECTRICAL: 5 kW (6.7 HP) Drive Motor 48V System with 8 Trojan T-105 Batteries 17.5 MPH (28.2 KM/H) Maximum Speed Self-Adjusting Drum Brakes STEERING/SUSPENSION: Self-Compensating Double Reduction Helical Rack-and-Pinion Steering Independent Automotive-Style Strut Front Suspension Swing Arm with Coil Spring Over Shock Rear Suspension FRAME/STYLED PARTS: Robotic welded automotive ladder-style steel frame protected with a multi-step full-immersion phosphate treatment, electro-deposition epoxy-based coating, and an electrostatic applied polyester/urethane powder topcoat Custom-formulated thermoplastic olefin painted with a two-part top coat of high-luster automotive- grade polyurethane OPERATOR STATION: High-Back Bucket Seats Walk-Through Platform Glove Box Hour Meter Two Cup Holders DIMENSIONS: 119.37 in (303.2 cm) Long x 49.3 in (125.3 cm) Wide x 74.02 in (188 cm) High 4.5 in (11.5 cm) minimum ground clearance 1500 lb (680.4 kg) total payload capacity 1500 lb (544.3 kg) towing capacity CARGO BOX: 41.1 in (104.4 cm) Long x 45.9 in (116.6 cm) Wide x 11.9 in (30.2 cm) High 800 lb (362.9 kg) load capacity Tilting Box Hinged Tailgate	



Gator GS Electric (ALDI)

Code	Description	List price
	TIRES: 20x10-10 4-ply Turf Tires Front and Rear MISCELLANEOUS: Rear Receiver Hitch Sun Canopy	
	BASE MACHINE	
	<i>Base Machine Suggested List Price Does Not Include \$950 USD Destination Charge.</i>	
0671XF	Gator GS Electric (ALDI)	USD \$15,249.00
	DESTINATION AND LANGUAGE	
	Basic Factory Options	
	DESTINATION	
001A	United States / Canada	In Base Price
	OPERATOR'S MANUAL	
0443	Operator's Manual - English	In Base Price
	ATTACHMENTS FOR FIELD CONVERSION	
	OPERATOR'S MANUAL AND DECAL KIT	
BUC11761	Gator GS - Spanish Kit <i>Includes Spanish Operator's Manual and Spanish Label Kit</i>	USD \$359.51
	OPERATOR'S STATION AND CONTROLS	
	Field Installed Options	
	WINDSHIELD	
9003	Windshield, Folding Clear	USD \$387.00
	ATTACHMENTS FOR FIELD CONVERSION	
	WINDSHIELD	
BUC11679	Hinged poly windshield	USD \$416.23
	ROOF	
BUC11678	Sun Canopy	USD \$874.19
	UTILITY AND PROTECTION PACKAGES	
	Field Installed Options	
	PROTECTION PACKAGE	
9904	Front Brush Guard	USD \$366.00



Gator GS Electric (ALDI)

Code	Description	List price
	GUARDS ATTACHMENTS FOR FIELD CONVERSION FRONT BRUSH GUARD	
BUC11681	Front Brush Guard	USD \$392.69